

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRIMLESS

### A35643-

#### DESCRIPTION

Clicktrack 25 - Trimless - 1000mm / 39 3/8" Aluminum Profile - Black - Max 3000mm / 118 1/8"

#### GENERAL


Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Trimless  
 Mounting Location: Ceiling  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 1000  
 Length (in): 39 3/8  
 Width (mm): 119  
 Width (in): 4 11/16  
 Height (mm): 52  
 Height (in): 2 1/16  
 Fixture Finish: BLK  
 Fixture Material: Extruded Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A380052-

#### DESCRIPTION

Magiq 4 Korona - Insert for Hypro 30 / 2LOOK4 25 Magtrack - 16.3W LED (Zhaga Standard) - Black - 2700K / 3000K / 4000K - Reflector 10° / 20° / 40°

#### GENERAL

Series: Magiq  
 Subseries: Magiq 4 Cell  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 167  
 Length (in): 6 <sup>9</sup>/<sub>16</sub>  
 Width (mm): 30  
 Width (in): 1 <sup>3</sup>/<sub>16</sub>  
 Height (mm): 55  
 Height (in): 2 <sup>3</sup>/<sub>16</sub>  
 Light Distribution: Direct  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 16.3  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 1050  
 Upon Request: 0-10Vdc Dimming / DALI

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 4  
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000  
 Max. Delivered Lumen (lm): 780 / 850 / 862 / 880  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Reflector°: 10 / 20 / 40  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A380062-

#### DESCRIPTION

Magiq 4 - Insert for Hypro 30 / 2LOOK4 25 Magtrack - 16.3W LED (Zhaga Standard) - Black - 2700K / 3000K / 4000K - Reflector: 10° / 20° / 40°

#### GENERAL

Series: Clicktrack  
 Subseries: Magiq 4 Cell  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 167  
 Length (in): 6 <sup>9</sup>/<sub>16</sub>  
 Width (mm): 30  
 Width (in): 1 <sup>3</sup>/<sub>16</sub>  
 Height (mm): 55  
 Height (in): 2 <sup>3</sup>/<sub>16</sub>  
 Light Distribution: Direct  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 16.3  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 1050  
 Upon Request: 0-10Vdc Dimming / DALI

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000  
 Max. Delivered Lumen (lm): 780 / 850 / 862 / 880  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Reflector°: 10 / 20 / 40  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

## A3CLK25-TRI-SYS COMPONENTS

### A380106-

#### DESCRIPTION

Hangover 75 - Indirect Diffuser

#### GENERAL

Series: Hangover

Subseries: Hangover 75

Brand: Prolicht

Division: Architectural

#### PHYSICAL

Shape: Round

Diameter (mm): 70

Diameter (in): 2 <sup>3</sup>/<sub>4</sub>

Fixture Finish: RED / ORG / YEL / GRN / BLU

Fixture Material: Acrylic


#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



68mm 2 <sup>1</sup>/<sub>16</sub>"





PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A38801

#### DESCRIPTION

Clicktrack 25 - Trimless - End Cap - Black

#### GENERAL



Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Length (mm): 68  
 Length (in): 2 <sup>11</sup>/<sub>16</sub>  
 Width (mm): 9  
 Width (in): 6/16  
 Height (mm): 52  
 Height (in): 2 <sup>1</sup>/<sub>16</sub>  
 Weight (kg): 0.026  
 Weight (lbs): 0.057  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A38802

#### DESCRIPTION

Clicktrack 25 - Trimless - Linear Coupler - Black

#### GENERAL


Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 142  
 Length (in): 5 <sup>9</sup>/<sub>16</sub>  
 Width (mm): 18  
 Width (in): 11/16  
 Height (mm): 16  
 Height (in): 10/16  
 Weight (kg): 0.02  
 Weight (lbs): 0.044  
 Fixture Finish: BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A38803

#### DESCRIPTION

Clicktrack - Trimless - 48V Power Feed - Black

#### GENERAL


Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 143  
 Length (in): 5 <sup>10</sup>/<sub>16</sub>  
 Width (mm): 16  
 Width (in): 10/16  
 Height (mm): 18  
 Height (in): 11/16  
 Weight (kg): 0.042  
 Weight (lbs): 0.09  
 Fixture Finish: BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A38804

#### DESCRIPTION

Clicktrack 25 - Trimless - Corner Coupler 90° - Black

#### GENERAL


Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Length (mm): 1073  
 Length (in): 42 <sup>1</sup>/<sub>4</sub>"  
 Width (mm): 1073  
 Width (in): 42 <sup>1</sup>/<sub>4</sub>"  
 Height (mm): 52  
 Height (in): 2 <sup>1</sup>/<sub>16</sub>"  
 Weight (kg): 4.596  
 Weight (lbs): 10.13  
 Fixture Finish: BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	


## A3CLK25-TRI-SYS COMPONENTS

### A38805

**DESCRIPTION**  
Clicktrack 25 - Trimless - Vertical Coupler 90° - Black

**GENERAL**  
Series: Clicktrack  
Subseries: Clicktrack 25  
Brand: Prolicht  
Division: Architectural

**PHYSICAL**  
Length (mm): 1028  
Length (in): 40 1/2  
Width (mm): 1028  
Width (in): 40 1/2  
Height (mm): 52  
Height (in): 2 1/16  
Weight (kg): 4.541  
Weight (lbs): 10  
Fixture Finish: BLK  
Fixture Material: Aluminum



## A3CLK25-TRI-SYS COMPONENTS

### A38806

#### DESCRIPTION

Clicktrack 25 - Trimless - Frame Alignment Kit

#### GENERAL



Series: Clicktrack  
 Subseries: Clicktrack 25  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Length (mm): 67  
 Length (in): 2 <sup>10</sup>/<sub>16</sub>  
 Width (mm): 50  
 Width (in): 1 <sup>15</sup>/<sub>16</sub>  
 Height (mm): 19  
 Height (in): 12/16  
 Weight (kg): 0.033  
 Weight (lbs): 0.07  
 Fixture Finish: BLK

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A3T078-

#### DESCRIPTION

Centriq - Track Head - 30mm / 1 3/16" - 4.3W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°

#### GENERAL

Series: Centriq  
 Subseries: Centriq 125  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 30  
 Diameter (in): 1 3/16  
 Length (mm): 170  
 Length (in): 6 11/16  
 Height (mm): 99  
 Height (in): 3 7/8  
 Light Distribution: Adjustable / Direct  
 Weight (kg): 0.063  
 Weight (lbs): 0.139  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 4.3  
 Total Output Wattage (W): 3.9  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 340  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Delivered Lumen Range: 100 - 499 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 260 / 270 / 290  
 Nominal Lumen (lm): 343.9 / 359.9 / 391.8  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Optic°: 24 / 32  
 Adjustability: Rotational 360°; Tilt 90°  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20





## A3CLK25-TRI-SYS COMPONENTS

### A3T079-

#### DESCRIPTION

Centriq - Track Head - 40mm / 1 9/16" - 6.31W LED (Zhaga Standard) - 2700K / 3000K / 4000K

#### GENERAL

Series: Centriq \_\_\_\_\_  
 Brand: Prolicht \_\_\_\_\_  
 Division: Architectural \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_  
 Diameter (mm): 40 \_\_\_\_\_  
 Diameter (in): 1 9/16 \_\_\_\_\_  
 Length (mm): 170 \_\_\_\_\_  
 Length (in): 6 11/16 \_\_\_\_\_  
 Height (mm): 113 \_\_\_\_\_  
 Height (in): 4 7/16 \_\_\_\_\_  
 Light Distribution: Adjustable / Direct \_\_\_\_\_  
 Weight (kg): 0.117 \_\_\_\_\_  
 Weight (lbs): 0.258 \_\_\_\_\_  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR \_\_\_\_\_  
 Fixture Material: Aluminum \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 1 - 9 W \_\_\_\_\_  
 Lamp Type: LED (Zhaga Standard) \_\_\_\_\_  
 Input Wattage (W): 6.31 \_\_\_\_\_  
 Total Output Wattage (W): 5.74 \_\_\_\_\_  
 Dimming: Non-Dimmable / 0-10V Dimming \_\_\_\_\_  
 Driver Included: No \_\_\_\_\_  
 Driver Type: Constant Voltage - 120Vac \_\_\_\_\_  
 Driver Class: Class 2 \_\_\_\_\_  
 Input Voltage (V): 48 \_\_\_\_\_

#### LED


Delivered Lumen Range: 100 - 499 lm \_\_\_\_\_  
 Number of LEDs: 1 \_\_\_\_\_  
 Color Temperature (°K): 2700 / 3000 / 4000 \_\_\_\_\_  
 Max. Delivered Lumen (lm): 360 / 390 / 420 \_\_\_\_\_  
 Nominal Lumen (lm): 448.1 / 483.1 / 513.9 \_\_\_\_\_  
 CRI: >90 CRI \_\_\_\_\_  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request) \_\_\_\_\_

#### OPTICAL

Beam Angle: 10 \_\_\_\_\_  
 Adjustability: Rotational 360°; Tilt 90° \_\_\_\_\_  
 Upon Request: Special Beam Angles \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_  
 IP rating: IP20 \_\_\_\_\_



## A3CLK25-TRI-SYS COMPONENTS

### A3T080-

#### DESCRIPTION

Centriq - Track Head - 40mm / 1 9/16" - 6.6W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable - Reflector: 20°/31°/36°/40°/50°

#### GENERAL

Series: Centriq  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 40  
 Diameter (in): 1 9/16  
 Length (mm): 170  
 Length (in): 6 11/16  
 Height (mm): 113  
 Height (in): 4 7/16  
 Light Distribution: Adjustable / Direct  
 Weight (kg): 0.144  
 Weight (lbs): 0.318  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.5  
 Total Output Wattage (W): 5.9  
 Driver Included: No

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 468 / 490 / 520  
 Nominal Lumen (lm): 732 / 769 / 780  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Reflector°: 20 / 40 / 50  
 Optic°: 31 / 36  
 Adjustability: Rotational 360°; Tilt 90°  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A3T081-

#### DESCRIPTION

Centriq - Track Head - 55mm / 2 3/16" - 9.2W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable

#### GENERAL

Series: Centriq  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 55  
 Diameter (in): 2 3/16  
 Length (mm): 170  
 Length (in): 6 11/16  
 Height (mm): 137  
 Height (in): 5 3/8  
 Light Distribution: Adjustable / Direct  
 Weight (kg): 0.54  
 Weight (lbs): 1.19  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 9.2  
 Total Output Wattage (W): 8.4  
 Driver Included: No

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 486 / 524 / 548  
 Nominal Lumen (lm): 625.3 / 660.1 / 712.4  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Reflector: 9  
 Adjustability: Rotational 360°; Tilt 90°  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T082-

#### DESCRIPTION

Centriq - Track Head - 55mm / 2 3/16" - 12.1W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable - 15° / 17° / 25° / 33° / 35° / 46°

#### GENERAL

Series: Centriq  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 55  
 Diameter (in): 2 3/16  
 Length (mm): 170  
 Length (in): 6 11/16  
 Height (mm): 137  
 Height (in): 5 3/8  
 Light Distribution: Adjustable / Direct  
 Weight (kg): 0.548  
 Weight (lbs): 1.21  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 11.8  
 Total Output Wattage (W): 11.2  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 600  
 Upon Request: 0-10Vdc dimming

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 720 / 760 / 820  
 Nominal Lumen (lm): 1196 / 1257 / 1275  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Reflector°: 17 / 33 / 46  
 Optic°: 15 / 25 / 35  
 Adjustability: Rotational 360°; Tilt 90°  
 Upon Request: Special Beam Angles

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A3T086-

#### DESCRIPTION

LED (Zhaga Standard)line - Light Insert - 620mm/24 7/16" - 6.7W / 8W LED (Zhaga Standard) - 2700K / 000K / 4000K - Dimmable

#### GENERAL

Series: Clicktrack  
 Subseries: Ledline  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 620  
 Length (in): 24 7/16  
 Width (mm): 23  
 Width (in): 7/8  
 Height (mm): 43  
 Height (in): 1 11/16  
 Light Distribution: Direct  
 Weight (kg): 0.405  
 Weight (lbs): 0.89  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL


Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.6 / 7.9  
 Total Output Wattage (W): 6 / 7.2  
 Dimming: 0-10V Dimming  
 Driver Included: No

#### LED

Delivered Lumen Range: 100 - 499 lm  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 360 / 540  
 Nominal Lumen (lm): 600 / 900  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A3T087-

#### DESCRIPTION

LED (Zhaga Standard)line - Light Insert - 820mm / 32 5/16" - 8.9W / 10.7W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable

#### GENERAL

Series: Clicktrack  
 Subseries: Ledline  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 820  
 Length (in): 32 5/16  
 Width (mm): 23  
 Width (in): 7/8  
 Height (mm): 43  
 Height (in): 1 11/16  
 Light Distribution: Direct  
 Weight (kg): 0.531  
 Weight (lbs): 1.17  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL


Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 8.8 / 10.6  
 Total Output Wattage (W): 8 / 9.6  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Input Voltage (V): 48

#### LED

Delivered Lumen Range: 500 - 999 lm  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 480 / 720  
 Nominal Lumen (lm): 800 / 1200  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

## A3CLK25-TRI-SYS COMPONENTS

### A3T088-

#### DESCRIPTION

LED (Zhaga Standard)line - Light Insert - 1020mm / 40 3/16" - 11.1W / 13.3W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable

#### GENERAL

Series: Clicktrack  
 Subseries: Ledline  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 1020  
 Length (in): 40 3/16  
 Width (mm): 23  
 Width (in): 7/8  
 Height (mm): 43  
 Height (in): 1 11/16  
 Light Distribution: Direct  
 Weight (kg): 0.655  
 Weight (lbs): 1.44  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL


Input Wattage Range: 10 - 19 W  
 Input Wattage (W): 11.0 / 13.2  
 Total Output Wattage (W): 10 / 12  
 Driver Included: No

#### LED

Delivered Lumen Range: 500 - 999 lm  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 600 / 900  
 Nominal Lumen (lm): 1000 / 1500  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20





PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A3T089-

#### DESCRIPTION

LED (Zhaga Standard)line - Light Insert - 1220mm / 48 1/16" - 13.3W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable

#### GENERAL

Series: Clicktrack  
 Subseries: Ledline  
 Brand: Prolicht  
 Division: Architectural

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 1220  
 Length (in): 48 1/16  
 Width (mm): 23  
 Width (in): 7/8  
 Height (mm): 43  
 Height (in): 1 11/16  
 Light Distribution: Direct  
 Weight (kg): 0.764  
 Weight (lbs): 1.684  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL


Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 13.2 / 15.8  
 Total Output Wattage (W): 12 /  
 Dimming: 0-10V Dimming  
 Driver Included: No

#### LED

Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 720 / 1080  
 Nominal Lumen (lm): 1200  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS

### A3T090-

#### DESCRIPTION

Snooker - Track Head - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K

#### GENERAL

Series: Snooker  
 Subseries: Snooker Modular System  
 Brand: Prolicht  
 Division: Architectural  
 Subcategory: Spots

#### PHYSICAL

Shape: Round  
 Diameter (mm): 72  
 Diameter (in): 2 <sup>13</sup>/<sub>16</sub>  
 Length (mm): 170  
 Length (in): 6 <sup>11</sup>/<sub>16</sub>  
 Height (mm): 72  
 Height (in): 2 <sup>13</sup>/<sub>16</sub>  
 Max. Overall Height (mm): 2072  
 Max. Overall Height (in): 81 <sup>9</sup>/<sub>16</sub>  
 Light Distribution: Downlight  
 Weight (kg): 0.506  
 Weight (lbs): 1.12  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL



Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 100 - 499 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000  
 Max. Delivered Lumen (lm): 270 / 290 / 304 / 310  
 Nominal Lumen (lm): 448 / 483 / 504 / 514  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS

### A3T091-

#### DESCRIPTION

Snooker Shine - Track Head - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Diffuser Shine Ring

#### GENERAL

Series: Snooker  
 Subseries: Snooker Modular System  
 Brand: Prolicht  
 Division: Architectural  
 Subcategory: Spots

#### PHYSICAL

Shape: Round  
 Diameter (mm): 72  
 Diameter (in): 2 <sup>13</sup>/<sub>16</sub>  
 Length (mm): 170  
 Length (in): 6 <sup>11</sup>/<sub>16</sub>  
 Height (mm): 72  
 Height (in): 2 <sup>13</sup>/<sub>16</sub>  
 Max. Overall Height (mm): 2072  
 Max. Overall Height (in): 81 <sup>9</sup>/<sub>16</sub>  
 Light Distribution: Direct  
 Weight (kg): 0.506  
 Weight (lbs): 1.12  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum Die Cast

#### ELECTRICAL


Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming

#### LED

Delivered Lumen Range: 100 - 499 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 280 / 310 / 330  
 Nominal Lumen (lm): 448.1 / 483.1 / 513.9  
 CRI: >90 CRI  
 Upon Request: Special Color Temperature \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T117

#### DESCRIPTION

Hangover Plug - Track Head - 28mm / 1 1/8" x 150mm / 5 7/8" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/34°/55°/58°

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Spots

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Length (mm): 166  
 Length (in): 6 9/16  
 Height (mm): 150  
 Height (in): 5 7/8  
 Max. Overall Height (mm): 2150  
 Max. Overall Height (in): 84 5/8  
 Light Distribution: Downlight  
 Weight (kg): 0.2  
 Weight (lbs): 0.44  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 100 - 499 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL



Optic°: 24 / 32 / 34 / 55 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20  
 Zaneen Group Inc. © 2024, T 1800-388-3382, F 416-247-9319, www.zaneen.com

Available for International specifications by adding 'INT' at the end of the existing Model #. For assistance on 'custom' specifications, contact zteam@zaneen.com. In a constant effort to supply the best product, we reserve the right to change specifications or materials without notice. The most recent specification sheets are found at zaneen.com



PROJECT
TYPE
NOTES
QUANTITY
DATE

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T118-

#### DESCRIPTION

Hangover Plug - Track Head - 28mm / 1 1/8" x 300mm / 11 13/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/34°/55°/58°

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Pendant

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Height (mm): 300  
 Height (in): 11 13/16  
 Max. Overall Height (mm): 2300  
 Max. Overall Height (in): 90 9/16  
 Light Distribution: Downlight  
 Weight (kg): 0.32  
 Weight (lbs): 0.706  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Optic°: 24 / 32 / 34 / 55 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T119-

#### DESCRIPTION

Hangover Plug - Track Head - 28mm / 1 1/8" x 450mm / 17 11/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/34°/55°/58°

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Pendant

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Height (mm): 450  
 Height (in): 17 11/16  
 Max. Overall Height (mm): 2450  
 Max. Overall Height (in): 96 7/16  
 Light Distribution: Downlight  
 Weight (kg): 0.32  
 Weight (lbs): 0.706  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED



Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Optic°: 24 / 32 / 34 / 55 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T120-

#### DESCRIPTION

Hangover Plug Shine - Track Head - 28mm / 1 1/8" x 150mm / 5 7/8" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/58° - Shine Ring

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Pendant

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Length (mm): 166  
 Length (in): 6 9/16  
 Height (mm): 150  
 Height (in): 5 7/8  
 Max. Overall Height (mm): 2150  
 Max. Overall Height (in): 84 5/8  
 Light Distribution: Downlight  
 Weight (kg): 0.2  
 Weight (lbs): 0.44  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL


Optic°: 24 / 32 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20  
 Zaneen Group Inc. © 2024, T 1800-388-3382, F 416-247-9319, www.zaneen.com

Available for International specifications by adding 'INT' at the end of the existing Model #. For assistance on 'custom' specifications, contact zteam@zaneen.com. In a constant effort to supply the best product, we reserve the right to change specifications or materials without notice. The most recent specification sheets are found at zaneen.com





PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T121-

#### DESCRIPTION

Hangover Plug Shine - Track Head - 28mm / 1 1/8" x 300mm / 11 13/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/58° - Shine Ring

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Pendant

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Height (mm): 300  
 Height (in): 11 13/16  
 Max. Overall Height (mm): 2300  
 Max. Overall Height (in): 90 3/16  
 Light Distribution: Downlight  
 Weight (kg): 0.32  
 Weight (lbs): 0.706  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 120  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Optic°: 24 / 32 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T122-

#### DESCRIPTION

Hangover Plug - Track Head - 28mm / 1 1/8" x 450mm / 17 11/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32°/58° - Shine Ring

#### GENERAL

Series: Clicktrack  
 Subseries: Hangover Plug Standard (Track Insert)  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Pendant

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 28  
 Diameter (in): 1 1/8  
 Height (mm): 450  
 Height (in): 17 11/16  
 Max. Overall Height (mm): 2450  
 Max. Overall Height (in): 96 7/16  
 Light Distribution: Downlight  
 Weight (kg): 0.32  
 Weight (lbs): 0.706  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 4,000mm Cable - Black

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6.4  
 Total Output Wattage (W): 5.8  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 120  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 328 / 363 / 386  
 CRI: >90 CRI  
 Upon Request: \*\*\*3500K available in minimum quantities (larger quantities upon request)

#### OPTICAL

Optic°: 24 / 32 / 58

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T129-

#### DESCRIPTION

Hangover 40 - Track Head - 150mm / 5 7/8" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40°/50°

#### GENERAL

Series: Hangover \_\_\_\_\_

Subseries: Hangover 40 \_\_\_\_\_

Brand: Prolicht \_\_\_\_\_

Division: Architectural \_\_\_\_\_

Mounting Type: Track \_\_\_\_\_

Mounting Location: Ceiling \_\_\_\_\_

Subcategory: Downlight \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_

Diameter (mm): 40 \_\_\_\_\_

Diameter (in): 1 9/16 \_\_\_\_\_

Height (mm): 150 \_\_\_\_\_

Height (in): 5 7/8 \_\_\_\_\_

Max. Overall Height (mm): 2150 \_\_\_\_\_

Max. Overall Height (in): 84 5/8 \_\_\_\_\_

Light Distribution: Downlight \_\_\_\_\_

Weight (kg): 0.433 \_\_\_\_\_

Weight (lbs): 0.955 \_\_\_\_\_

Diffuser: Shine Ring 1-6 \_\_\_\_\_

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR \_\_\_\_\_

Fixture Material: Aluminum \_\_\_\_\_

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 10 - 19 W \_\_\_\_\_

Lamp Type: LED (Zhaga Standard) \_\_\_\_\_

Input Wattage (W): 10 \_\_\_\_\_

Total Output Wattage (W): 9.1 \_\_\_\_\_

Dimming: Non-Dimmable \_\_\_\_\_

Driver Included: No \_\_\_\_\_

Driver Type: Constant Voltage - Universal \_\_\_\_\_

Driver Class: Class 2 \_\_\_\_\_

Input Voltage (V): 48 \_\_\_\_\_

Constant Current (mA): 500 \_\_\_\_\_

Upon Request: 0-10Vdc dimming / DALI dimming \_\_\_\_\_

#### LED

Delivered Lumen Range: 500 - 999 lm \_\_\_\_\_

Number of LEDs: 1 \_\_\_\_\_

Color Temperature (°K): 2700 / 3000 / 4000 \_\_\_\_\_

Max. Delivered Lumen (lm): 788 / 829 / 840 \_\_\_\_\_

Nominal Lumen (lm): 1016 / 1068 / 1082 \_\_\_\_\_

CRI: >90 CRI \_\_\_\_\_

Lamp Life (hrs): 50000 \_\_\_\_\_


#### OPTICAL

Reflector°: 40 / 50 \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_

IP rating: IP20 \_\_\_\_\_



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T130-

#### DESCRIPTION

Hangover 40 - Track Head - 300mm / 11 13/16" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40°/50°

#### GENERAL

Series: Hangover

Subseries: Hangover 40

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder

Diameter (mm): 40

Diameter (in): 1 9/16

Height (mm): 300

Height (in): 11 13/16

Max. Overall Height (mm): 2300

Max. Overall Height (in): 90 9/16

Light Distribution: Downlight

Weight (kg): 0.666

Weight (lbs): 1.468

Diffuser: Shine Ring 1-6

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 10

Total Output Wattage (W): 9.1

Dimming: Non-Dimmable

Driver Included: No

Driver Location: Remote

Driver Type: Constant Voltage - Universal

Driver Class: Class 2

Input Voltage (V): 48

Constant Current (MA): 500

Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 500 - 999 lm

Number of LEDs: 1

Color Temperature (°K): 2700 / 3000 / 4000

Max. Delivered Lumen (lm): 788 / 829 / 840

Nominal Lumen (lm): 1016 / 1068 / 1082

CRI: >90 CRI


#### OPTICAL

Reflector°: 40 / 50

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T131-

#### DESCRIPTION

Hangover 40 - Track Head - 450mm / 17 11/16" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40°/50°

#### GENERAL

Series: Hangover \_\_\_\_\_

Subseries: Hangover 40 \_\_\_\_\_

Brand: Prolicht \_\_\_\_\_

Division: Architectural \_\_\_\_\_

Mounting Type: Track \_\_\_\_\_

Mounting Location: Ceiling \_\_\_\_\_

Subcategory: Downlight \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_

Diameter (mm): 40 \_\_\_\_\_

Diameter (in): 1 9/16 \_\_\_\_\_

Height (mm): 450 \_\_\_\_\_

Height (in): 17 11/16 \_\_\_\_\_

Max. Overall Height (mm): 2450 \_\_\_\_\_

Max. Overall Height (in): 96 7/16 \_\_\_\_\_

Light Distribution: Downlight \_\_\_\_\_

Weight (kg): 0.856 \_\_\_\_\_

Weight (lbs): 1.887 \_\_\_\_\_

Diffuser: Shine Ring 1-6 \_\_\_\_\_

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR \_\_\_\_\_

Fixture Material: Aluminum \_\_\_\_\_

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 10 - 19 W \_\_\_\_\_

Lamp Type: LED (Zhaga Standard) \_\_\_\_\_

Input Wattage (W): 10 \_\_\_\_\_

Total Output Wattage (W): 9.1 \_\_\_\_\_

Dimming: Non-Dimmable \_\_\_\_\_

Driver Included: No \_\_\_\_\_

Driver Location: Remote \_\_\_\_\_

Driver Type: Constant Voltage - Universal \_\_\_\_\_

Driver Class: Class 2 \_\_\_\_\_

Input Voltage (V): 48 \_\_\_\_\_

Constant Current (mA): 500 \_\_\_\_\_

Upon Request: 0-10Vdc dimming / DALI dimming \_\_\_\_\_

#### LED

Delivered Lumen Range: 500 - 999 lm \_\_\_\_\_

Number of LEDs: 1 \_\_\_\_\_

Color Temperature (°K): 2700 / 3000 / 4000 \_\_\_\_\_

Max. Delivered Lumen (lm): 788 / 829 / 840 \_\_\_\_\_

Nominal Lumen (lm): 1016 / 1068 / 1082 \_\_\_\_\_

CRI: >90 CRI \_\_\_\_\_


#### OPTICAL

Reflector°: 40 / 50 \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_

IP rating: IP20 \_\_\_\_\_



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T132-

#### DESCRIPTION

Hangover Plug 40 - Track Head - 150mm / 5 7/8" - 10W LED  
(Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40° / 50°

#### GENERAL

Series: Hangover

Subseries: Hangover Plug 40

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder

Diameter (mm): 40

Diameter (in): 1 9/16

Height (mm): 150

Height (in): 5 7/8

Max. Overall Height (mm): 2150

Max. Overall Height (in): 84 5/8

Light Distribution: Downlight

Weight (kg): 0.433

Weight (lbs): 0.955

Diffuser: Shine Ring 1-6

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 10

Total Output Wattage (W): 8.1

Dimming: Non-Dimmable

Driver Included: No

Driver Location: Remote

Driver Type: Constant Voltage - Universal

Driver Class: Class 2

Input Voltage (V): 48

Constant Current (mA): 500

Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 500 - 999 lm

Number of LEDs: 1

Color Temperature (°K): 2700 / 3000 / 4000

Max. Delivered Lumen (lm): 788 / 829 / 840

Nominal Lumen (lm): 1016 / 1068 / 1082

CRI: >90 CRI


#### OPTICAL

Reflector°: 40 / 50

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T133-

#### DESCRIPTION

Hangover Plug 40 - Track Head - 300mm / 11 13/16" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40°/50°

#### GENERAL

Series: Hangover \_\_\_\_\_

Subseries: Hangover Plug 40 \_\_\_\_\_

Brand: Prolicht \_\_\_\_\_

Division: Architectural \_\_\_\_\_

Mounting Type: Track \_\_\_\_\_

Mounting Location: Ceiling \_\_\_\_\_

Subcategory: Downlight \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_

Diameter (mm): 40 \_\_\_\_\_

Diameter (in): 1 9/16 \_\_\_\_\_

Height (mm): 300 \_\_\_\_\_

Height (in): 11 13/16 \_\_\_\_\_

Max. Overall Height (mm): 2300 \_\_\_\_\_

Max. Overall Height (in): 90 9/16 \_\_\_\_\_

Light Distribution: Downlight \_\_\_\_\_

Weight (kg): 0.666 \_\_\_\_\_

Weight (lbs): 1.468 \_\_\_\_\_

Diffuser: Shine Ring 1-6 \_\_\_\_\_

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR \_\_\_\_\_

Fixture Material: Aluminum \_\_\_\_\_

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 10 - 19 W \_\_\_\_\_

Lamp Type: LED (Zhaga Standard) \_\_\_\_\_

Input Wattage (W): 10 \_\_\_\_\_

Total Output Wattage (W): 8.1 \_\_\_\_\_

Dimming: Non-Dimmable \_\_\_\_\_

Driver Included: No \_\_\_\_\_

Driver Location: Remote \_\_\_\_\_

Driver Type: Constant Voltage - Universal \_\_\_\_\_

Driver Class: Class 2 \_\_\_\_\_

Input Voltage (V): 48 \_\_\_\_\_

Constant Current (mA): 500 \_\_\_\_\_

Upon Request: 0-10Vdc dimming / DALI dimming \_\_\_\_\_

#### LED

Delivered Lumen Range: 500 - 999 lm \_\_\_\_\_

Number of LEDs: 1 \_\_\_\_\_

Color Temperature (°K): 2700 / 3000 / 4000 \_\_\_\_\_

Max. Delivered Lumen (lm): 788 / 829 / 840 \_\_\_\_\_

Nominal Lumen (lm): 1016 / 1068 / 1082 \_\_\_\_\_

CRI: >90 CRI \_\_\_\_\_


#### OPTICAL

Reflector°: 40 / 50 \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_

IP rating: IP20 \_\_\_\_\_





PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T134-

#### DESCRIPTION

Hangover Plug 40 - Track Head - 450mm / 17 11/16" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 40°/50°

#### GENERAL

Series: Hangover  
 Subseries: Hangover Plug 40  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 40  
 Diameter (in): 1 9/16  
 Height (mm): 450  
 Height (in): 17 11/16  
 Max. Overall Height (mm): 2450  
 Max. Overall Height (in): 96 7/16  
 Light Distribution: Downlight  
 Weight (kg): 0.856  
 Weight (lbs): 1.887  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 10  
 Total Output Wattage (W): 8.1  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 788 / 829 / 840  
 Nominal Lumen (lm): 1016 / 1068 / 1082  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000

#### OPTICAL

Reflector: 40 / 50

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T135-

#### DESCRIPTION

Hangover 75 - Track Head - 150mm / 5 7/8" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Reflector 18°/36°/52°

#### GENERAL

Series: Hangover  
 Subseries: Hangover 75  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 75  
 Diameter (in): 2 15/16  
 Height (mm): 150  
 Height (in): 5 7/8  
 Max. Overall Height (mm): 2150  
 Max. Overall Height (in): 84 5/8  
 Light Distribution: Downlight  
 Weight (kg): 0.433  
 Weight (lbs): 0.955  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 10  
 Total Output Wattage (W): 8.1  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 898 / 944 / 956  
 Nominal Lumen (lm): 1016 / 1068 / 1082  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000

#### OPTICAL

Reflector: 18 / 36 / 52

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T136-

#### DESCRIPTION

Hangover 75 - Track Head - 150mm / 5 7/8" - Dir / Ind - 20.8W LED (Zhaga Standard) - 2700K/3000K/4000K - Reflector 18°/36°/52°

#### GENERAL

Series: Hangover  
 Subseries: Hangover 75  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 75  
 Diameter (in): 2 15/16  
 Height (mm): 150  
 Height (in): 5 7/8  
 Max. Overall Height (mm): 2150  
 Max. Overall Height (in): 84 5/8  
 Light Distribution: Direct / Indirect  
 Weight (kg): 0.433  
 Weight (lbs): 0.955  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 20 - 29 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 20.8  
 Total Output Wattage (W): 19  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 1729 - 1837  
 CRI: >90 CRI  
 Lamp Life (hrs): 50000

#### OPTICAL

Reflector°: 18 / 36 / 52

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T137-

#### DESCRIPTION

Hangover 75 - Track Head - 300mm / 11 13/16" - 10W LED (Zhaga Standard) - 2700K/3000K/4000K - Reflector 18°/36°/52°

#### GENERAL

Series: Hangover  
 Subseries: Hangover 75  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 75  
 Diameter (in): 2 15/16  
 Height (mm): 300  
 Height (in): 11 13/16  
 Max. Overall Height (mm): 2300  
 Max. Overall Height (in): 90 9/16  
 Light Distribution: Downlight  
 Weight (kg): 0.666  
 Weight (lbs): 1.468  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 10  
 Total Output Wattage (W): 8.1  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (mA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Delivered Lumen Range: 500 - 999 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 898 / 944 / 956  
 Nominal Lumen (lm): 1016 / 1068 / 1082  
 CRI: >90 CRI

#### OPTICAL

Reflector°: 18 / 36 / 52

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T138-

#### DESCRIPTION

Hangover 75 - Track Head - 300mm / 11 13/16" - Dir / Ind - 20.8W LED (Zhaga Standard) - 2700K/3000K/4000K - Reflector 18°/36°/52°

#### GENERAL

Series: Hangover

Subseries: Hangover 75

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder

Diameter (mm): 75

Diameter (in): 2 15/16

Height (mm): 300

Height (in): 11 13/16

Max. Overall Height (mm): 2300

Max. Overall Height (in): 90 3/16

Light Distribution: Downlight

Weight (kg): 0.666

Weight (lbs): 1.468

Diffuser: Shine Ring 1-6

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 20 - 29 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 20.8

Total Output Wattage (W): 19

Dimming: Non-Dimmable

Driver Included: No

Driver Type: Constant Voltage - Universal

Input Voltage (V): 48

Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 1000 - 1999 lm

Number of LEDs: 1

Color Temperature (°K): 2700 / 3000 / 4000

Max. Delivered Lumen (lm): 1729 - 1837

CRI: >90 CRI

Lamp Life (hrs): 50000


#### OPTICAL

Reflector°: 18 / 36 / 52

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T139-

#### DESCRIPTION

Hangover Plug 75 - Track Head - 150mm / 5 7/8" - 6W LED (Zhaga Standard) - 2700K/3000K/4000K - Optics 9°/24°/39°

#### GENERAL

Series: Hangover  
 Subseries: Hangover Plug 75  
 Brand: Prolicht  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 75  
 Diameter (in): 2 15/16  
 Height (mm): 150  
 Height (in): 5 7/8  
 Max. Overall Height (mm): 2150  
 Max. Overall Height (in): 84 5/8  
 Light Distribution: Downlight  
 Weight (kg): 0.433  
 Weight (lbs): 0.955  
 Diffuser: Shine Ring 1-6  
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
 Fixture Material: Aluminum  
 Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 1 - 9 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 6  
 Total Output Wattage (W): 5.4  
 Dimming: Non-Dimmable  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Input Voltage (V): 48  
 Constant Current (MA): 500  
 Upon Request: 0-10Vdc dimming / DALI dimming

#### LED


Delivered Lumen Range: 100 - 499 lm  
 Number of LEDs: 1  
 Color Temperature (°K): 2700 / 3000 / 4000  
 Max. Delivered Lumen (lm): 385 / 408 / 442  
 Nominal Lumen (lm): 455.22 / 482 / 522.17  
 CRI: >90 CRI

#### OPTICAL

Optic°: 9 / 24 / 39

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A3CLK25-TRI-SYS COMPONENTS TRACK

### A3T140-

#### DESCRIPTION

Hangover Plug 75 - Track Head - 150mm / 5 7/8" - Dir / Ind - 10W LED (Zhaga Standard) - 2700K/3000K/4000K - Optics 9°/24°/39°

#### GENERAL

Series: Hangover

Subseries: Hangover Plug 75

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Downlight

#### PHYSICAL

Shape: Cylinder

Diameter (mm): 75

Diameter (in): 2 15/16

Height (mm): 150

Height (in): 5 7/8

Max. Overall Height (mm): 2150

Max. Overall Height (in): 84 5/8

Light Distribution: Downlight

Weight (kg): 0.433

Weight (lbs): 0.955

Diffuser: Shine Ring 1-6

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

Cable Details: 2,000mm or 6000mm Cable - Options: White / Black / Orange / Red

#### ELECTRICAL

Input Wattage Range: 10 - 19 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 10

Total Output Wattage (W): 8.1

Dimming: Non-Dimmable

Driver Included: No

Driver Location: Remote

Driver Type: Constant Voltage - Universal

Driver Class: Class 2

Input Voltage (V): 48

Constant Current (MA): 500

Upon Request: 0-10Vdc dimming / DALI dimming

#### LED

Delivered Lumen Range: 500 - 999 lm

Number of LEDs: 1

Color Temperature (°K): 2700 / 3000 / 4000

Max. Delivered Lumen (lm): 708 - 788

CRI: >90 CRI

Lamp Life (hrs): 50000


#### OPTICAL

Optic°: 9 / 24 / 39

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

## A3CLK25-TRI-SYS COMPONENTS

### ENCP50

#### DESCRIPTION

Empty Metal Enclosure for Driver - IP20 - Indoor Rated

#### GENERAL

Division: Architectural : Components

#### PHYSICAL

Shape: Rectangle

Length (mm): 670

Length (in): 26 <sup>3</sup>/<sub>8</sub>

Width (mm): 44

Width (in): 1 <sup>3</sup>/<sub>4</sub>

Height (mm): 38


Height (in): 1 <sup>1</sup>/<sub>2</sub>

Gasket: 1554JGASKET

Fixture Material: Metal

#### RATINGS AND CERTIFICATIONS

IP rating: IP20





### LEGEND

	floor-mounted		pivotable		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

### IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

### IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)