

A3GB-SUS-SYS COMPONENTS

A380012

DESCRIPTION

G-Board Power Supply Unit - 48V - 96W - 0-10V Driver with Interface

GENERAL

Brand: Prolicht
Division: Architectural


ELECTRICAL

Input Wattage (W): 96
Dimming: 0-10V Dimming
Input Voltage (V): 48

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A380041-

DESCRIPTION

Hangover Plug Shine - Track Head - 28mm / 1 1/8" x 300mm / 11 13/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug Standard (Track Insert)
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Downlight
Weight (kg): 0.451
Weight (lbs): 0.99
Diffuser: Shine Ring 1-6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum
Cable Details: 2,000mm or 4,000mm Cable - Black

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.4
Total Output Wattage (W): 5.8
Dimming: 0-10V Dimming
Driver Included: No
Driver Location: External
Input Voltage (V): 120

LED

Delivered Lumen Range: 100 - 499 lm
Number of LEDs: 1
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 328 / 363 / 386
Nominal Lumen (lm): 448 / 483 / 514
CRI: >90 CRI
Upon Request: Special Color Temperature


OPTICAL

Optic°: 24 / 32 / 58
Upon Request: Special Beam Angles

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A380042-

DESCRIPTION

Hangover Plug - Track Head - 28mm / 1 1/8" x 450mm / 17 11/16" - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Lens 24°/32° / 58° -

GENERAL

Series: Hangover
Subseries: Hangover Plug Standard (Track Insert)
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Downlight
Weight (kg): 0.468
Weight (lbs): 1.03
Diffuser: Shine Ring 1-6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.4
Total Output Wattage (W): 5.8
Dimming: 0-10V Dimming
Driver Included: No
Driver Location: External
Input Voltage (V): 120
Constant Current (MA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Number of LEDs: 1
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 328 / 363 / 386
Nominal Lumen (lm): 448 / 483 / 514
CRI: >90 CRI
Upon Request: Special Color Temperature


OPTICAL

Optic°: 24 / 32 / 58
Upon Request: Special Beam Angles

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A380043-

DESCRIPTION

Hangover Plug Decor - Blank Track Head - 28mm / 1 1/8" x 300mm / 11 13/16" -

GENERAL

Series: Hangover
Subseries: Hangover Plug Standard (Track Insert)
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 300
Height (in): 11 13/16
Weight (kg): 0.32
Weight (lbs): 0.706
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Lamp Type: LED (Zhaga Standard)

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A380044-

DESCRIPTION

Hangover Plug Decor - Blank Track Head - 28mm / 1 1/8" x 450mm / 17 11/16" -

GENERAL

Series: Hangover
Subseries: Hangover Plug Standard (Track Insert)
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 450
Height (in): 17 11/16
Weight (kg): 0.32
Weight (lbs): 0.706
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast


ELECTRICAL

Lamp Type: LED (Zhaga Standard)

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A380077-

DESCRIPTION

G-Board for Gravity Lift - Suspension

GENERAL



Series: Snooker
Subseries: Snooker G-Board for Gravity Lift
Brand: Prolicht
Division: Architectural
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Modular

PHYSICAL

Shape: Abstract
Length (mm): 990
Length (in): 39
Width (mm): 745
Width (in): 29 5/16
Height (mm): 50
Height (in): 1 15/16
Weight (kg): 5.4
Weight (lbs): 11.91
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3GB-SUS-SYS COMPONENTS

A380106-

DESCRIPTION

Hangover 75 - Indirect Diffuser

GENERAL

Series: Hangover
Subseries: Hangover 75
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Round
Diameter (mm): 70
Diameter (in): 2 3/4
Fixture Finish: RED / ORG / YEL / GRN / BLU
Fixture Material: Acrylic

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS SURFACE

A380107-

DESCRIPTION

Hangover Plug 40 - 150mm / 5 7/8" - 10.9W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable - Reflector 40° / 50°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural
Mounting Type: Surface
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Downlight
Weight (kg): 0.452
Weight (lbs): 9.96
Diffuser: Shine Ring 1-6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10.9
Total Output Wattage (W): 10
Dimming: 0-10V Dimming
Driver Included: No
Input Voltage (V): 48

LED

Delivered Lumen Range: 500 - 999 lm
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 788 / 829 / 840
Nominal Lumen (lm): 1016 / 1068 / 1082
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 40 / 50

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS SURFACE

A380108-

DESCRIPTION

Hangover Plug 40 - Track Head - 300mm / 11 13/16" - 10W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable - Reflector - 40°/50°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural
Mounting Type: Surface
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Downlight
Weight (kg): 0.463
Weight (lbs): 1.02
Diffuser: Shine Ring 1-6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10.9
Total Output Wattage (W): 10
Dimming: 0-10V Dimming
Driver Included: No
Input Voltage (V): 48

LED

Delivered Lumen Range: 500 - 999 lm
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 788 / 829 / 840
Nominal Lumen (lm): 1016 / 1068 / 1082
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Reflector°: 40 / 50

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A380111-

DESCRIPTION

Hangover Plug 75 - Track Head -150mm / 5 7/8" - 6.6W LED (Zhaga Standard) - 2700K / 3000K / 4000K - Dimmable - Lens 9° / 24° / 39°

GENERAL

Series: Hangover
Subseries: Hangover Plug 75
Brand: Prolicht
Division: Architectural
Mounting Type: Surface
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Cylinder
Diameter (mm): 75
Diameter (in): 2 15/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Downlight
Weight (kg): 0.532
Weight (lbs): 1.17
Diffuser: Shine Ring 1-6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.6
Total Output Wattage (W): 6
Dimming: 0-10V Dimming
Driver Included: No
Input Voltage (V): 48

LED


Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 385 / 408 / 442
Nominal Lumen (lm): 455.22 / 482 / 522.17
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Optic°: 9 / 24 / 39

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3GB-SUS-SYS COMPONENTS

A380364-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Recessed Ø28mm / 1 1/8" x 150mm / 5 7/8" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 33° / 66°

GENERAL

Series: Hangover
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: External
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (MA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 404 / 427 / 454 / 463
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Optic°: 22 / 33 / 66

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

PROJECT
TYPE
NOTES
QUANTITY
DATE

A38818-

DESCRIPTION

Snooker Decor - Track - Blank Globe -

GENERAL


Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 72
Height (in): 2 13/16
Weight (kg): 0.733
Weight (lbs): 1.62
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3GB-SUS-SYS COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A38862-

DESCRIPTION

Snooker - Track- Suspension Insert for Gravity Lift - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K

GENERAL

Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.733
Weight (lbs): 1.62
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.5
Total Output Wattage (W): 5.8
Dimming: 0-10V Dimming
Driver Included: No
Driver Location: External
Input Voltage (V): 48
Constant Current (MA): 500

LED



Delivered Lumen Range: 100 - 499 lm
Number of LEDs: 1
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 270 / 290 / 310
Nominal Lumen (lm): 448 / 483 / 514
CRI: >90 CRI
Upon Request: Special Color Temperature 3500K available in minimum quantities (larger quantities upon request)

OPTICAL

Beam Angle: 55
Upon Request: 55° Beam Angle: Dual Focus lens technology - very low UGR

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3GB-SUS-SYS COMPONENTS

A38866-

DESCRIPTION

Snooker - Track - Suspension Insert - 6.4W LED (Zhaga Standard) - 2700K / 3000K / 4000K

GENERAL

Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.733
Weight (lbs): 1.6
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.5
Total Output Wattage (W): 5.8
Driver Included: No
Driver Location: External
Input Voltage (V): 48
Constant Current (MA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Number of LEDs: 1
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 270 / 290 / 310
Nominal Lumen (lm): 448 / 483 / 514
CRI: >90 CRI
Upon Request: Special Color Temperature 3500K available in minimum quantities (larger quantities upon request)


OPTICAL

Beam Angle: 55
Upon Request: 55° Beam Angle: Dual Focus lens technology - very low UGR

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A3895199

DESCRIPTION

G-50 Channel | Gravity Lift - Surface Profile - Mounting Gauge - 1 Pair

GENERAL

Series: G-Board
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 1280
Length (in): 50 3/8
Width (mm): 25
Width (in): 1
Height (mm): 30
Height (in): 1 3/16
Weight (kg): 1.662
Weight (lbs): 3.66
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3GB-SUS-SYS COMPONENTS

A38954

DESCRIPTION

Mechanical Gravity Lift for G-Board

GENERAL

Series: Snooker
Subseries: Snooker G-Board for Gravity Lift
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 350
Length (in): 13 3/4
Width (mm): 42
Width (in): 1 5/8
Height (mm): 105
Height (in): 4 1/8
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)