

A3HY40-SUR-SYS COMPONENTS

A380114

DESCRIPTION
Idaho / Hypro 40 System - Per Meter - Opal Diffuser


GENERAL
Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL
Shape: Rectangle
Length (mm): Max. 3000
Length (in): Max. 118 1/9
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Diffuser: PMMA - Opal Diffuser - Per Meter
Fixture Material: Aluminum

ELECTRICAL
Lamp Type: LED (Zhaga Standard)

RATINGS AND CERTIFICATIONS
Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380115

DESCRIPTION

Idaho / Hypro 40 System - 1128mm - Opal Diffuser

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 1128
Length (in): 44 7/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.221
Weight (lbs): 0.49
Diffuser: PMMA - Opal Diffuser - Per Meter
Fixture Material: Aluminum


ELECTRICAL

Lamp Type: LED (Zhaga Standard)

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380118

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - Rico Cover - Per Meter -
Transparent / Black

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): Max. 3000mm
Length (in): Max. 118 1/9
Width (mm): 29
Width (in): 1 3/8
Height (mm): 50
Height (in): 2
Weight (kg): 0.138
Weight (lbs): 0.304
Diffuser: PMMA - Transparent / Black
Fixture Material: Aluminum


ELECTRICAL

Lamp Type: LED (Zhaga Standard)

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380251-

DESCRIPTION

Snooker Metal - Insert for Hypro 40 Suspension - 6.4W LED - 2700K / 3000K / 3500K / 4000K, CRI90, Chrome - Optic: 32° / 58° - Shine Ring

GENERAL

Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Sphere
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 71
Height (in): 2 13/16
Weight (kg): 0.26
Fixture Finish: CHR
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.0
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (mA): 500mA
Upon Request: DALI dimming

LED

Delivered Lumen Range: 100 - 499 lm
Number of LEDs: 1
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 284 / 300 / 319 / 325
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380258-

DESCRIPTION

Hypline 40 - Linear Insert 705mm / 27 3/4" for HYPRO 40
Recessed: LED 17W Max. - CRI 90 - Non-Dimming / 0-10V
Dimming - 2700K / 3000K / 3500K / 4000K

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 705
Length (in): 27 3/4
Width (mm): 29
Width (in): 1 1/8
Height (mm): 50
Height (in): 1 15/16
Light Distribution: Direct
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 15.6
Total Output Wattage (W): 14.2
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350



LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1233 / 1281 / 1338 / 1365
Nominal Lumen (lm): 2028 / 2107 / 2199 / 2244
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380260-

DESCRIPTION

Hypline 40 - Linear Insert 705mm / 27 3/4" for HYPRO 40 Surface:
LED 17W Max. - CRI 90 - Non-Dimming / 0-10V Dimming - 2700K /
3000K / 3500K / 4000K

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 705
Length (in): 27 3/4
Width (mm): 29
Width (in): 1 1/8
Height (mm): 50
Height (in): 1 15/16
Light Distribution: Direct
Fixture Material: Metal

ELECTRICAL



Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 15.6
Total Output Wattage (W): 14.2
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350

LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1233 / 1281 / 1338 / 1365
Nominal Lumen (lm): 2028 / 2107 / 2199 / 2244
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380268-

DESCRIPTION

Hypline 40 - Linear Insert 1128mm / 44 7/16" for HYPRO 40
Surface: LED 26.4W Max. - CRI 90 - Non-Dimming / 0-10V
Dimming - 2700K / 3000K / 3500K / 4000K

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 1128
Length (in): 44 7/16
Width (mm): 29
Width (in): 1 1/8
Height (mm): 50
Height (in): 1 15/16
Light Distribution: Direct
Fixture Material: Metal

ELECTRICAL



Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 24.9
Total Output Wattage (W): 22.6
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350

LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1973 / 2050 / 2139 / 2183
Nominal Lumen (lm): 3245 / 3371 / 3519 / 3591
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380276-

DESCRIPTION

Hypline 40 - Linear Insert 1408mm / 55 7/16" for HYPRO 40
Surface: LED 33W Max. - CRI 90 - Non-Dimming / 0-10V Dimming
- 2700K / 3000K / 3500K / 4000K

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 1408
Length (in): 55 7/16
Width (mm): 29
Width (in): 1 1/8
Height (mm): 50
Height (in): 1 15/16
Light Distribution: Direct
Fixture Material: Metal

ELECTRICAL



Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 32.2
Total Output Wattage (W): 29.3
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350

LED

Delivered Lumen Range: 2000 - 2999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2467 / 2562 / 2674 / 2729
Nominal Lumen (lm): 4057 / 4214 / 4399 / 4489
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380291-

DESCRIPTION

Oiko Pro In - Ø65mm / 2-1/2" Track Spot LED Insert for Hypro 40
Surface: 20W LED Max. 2700K / 3000K / 3500K / 4000K - CRI90 -
34° - Dimmable

GENERAL

Series: Oiko Pro
Subseries: Oiko Pro In
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Length (mm): 482
Length (in): 19
Width (mm): 65
Width (in): 2 5/16
Height (mm): 177
Height (in): 6 15/16
Light Distribution: Direct
Weight (kg): 0.661
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 19.9
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (MA): 500

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1410 / 1517 / 1571 / 1603
Nominal Lumen (lm): 1905 / 2050 / 2123 / 2166
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 34
Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380293-

DESCRIPTION

Oiko Pro In - Ø65mm / 2-1/2" Track Spot LED Insert for Hypro 40
Surface: 20W LED Max. 2700K / 3000K / 3500K / 4000K - CRI90 -
50° - Dimmable

GENERAL

Series: Oiko Pro
Subseries: Oiko Pro In
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Length (mm): 482
Length (in): 19
Width (mm): 65
Width (in): 2 5/16
Height (mm): 166
Height (in): 6 9/16
Light Distribution: Direct
Weight (kg): 0.661
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 19.9
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1547 / 1665 / 1724 / 1759
Nominal Lumen (lm): 1905 / 2050 / 2123 / 2166
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 50
Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380295-

DESCRIPTION

Oiko Pro In - Ø65mm / 2-1/2" Track Spot LED Insert for Hypro 40
Surface: 20W LED Max. 2700K / 3000K / 3500K / 4000K - CRI90 -
60° - Dimmable

GENERAL

Series: Oiko Pro
Subseries: Oiko Pro In
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Length (mm): 482
Length (in): 19
Width (mm): 65
Width (in): 2 5/16
Height (mm): 166
Height (in): 6 9/16
Light Distribution: Direct
Weight (kg): 0.661
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 19.9
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1699 / 1829 / 1893 / 1932
Nominal Lumen (lm): 1905 / 1517 / 2123 / 2166
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 60
Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380297-

DESCRIPTION

Oiko Pro In - Ø65mm / 2-1/2" Track Spot LED Insert for Hypro 40 Surface Wallwash: 20W LED Max. 2700K / 3000K / 3500K / 4000K - CRI90 - Dimmable

GENERAL

Series: Oiko Pro
Subseries: Oiko Pro In
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Length (mm): 482
Length (in): 19
Width (mm): 65
Width (in): 2 9/16
Height (mm): 166
Height (in): 6 9/16
Light Distribution: Direct
Weight (kg): 0.661
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 19.9
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1516 / 1632 / 1690 / 1724
Nominal Lumen (lm): 1905 / 1517 / 2123 / 2166
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: Wall wash
Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380299-

DESCRIPTION

Oiko Pro In - Ø65mm / 2-1/2" Track Spot LED Insert for Hypro 40
Surface: 20W LED Max. 2700K / 3000K / 3500K / 4000K - CRI90 -
14° - Dimmable

GENERAL

Series: Oiko Pro
Subseries: Oiko Pro In
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Length (mm): 482
Length (in): 19
Width (mm): 65
Width (in): 2 9/16
Height (mm): 166
Height (in): 6 9/16
Light Distribution: Direct
Weight (kg): 0.661
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 20.5
Total Output Wattage (W): 18.6
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1278 / 1377 / 1432 / 1461
Nominal Lumen (lm): 1668 / 1797 / 1905 / 1907
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 14
Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380332-

DESCRIPTION

Centriq In 65 Flex - Hypro 40 - Surface - Spot Insert - 65mm / 2 9/16" - 21W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflector: 14° / 30° / 44°

GENERAL

Series: Centriq
Subseries: Centriq In Flex
Brand: Prolicht
Division: Architectural
Subcategory: Spots

PHYSICAL

Shape: Cylinder
Diameter (mm): 65
Diameter (in): 2 9/16
Length (mm): 375
Length (in): 14 3/4
Height (mm): 170
Height (in): 6 11/16
Light Distribution: Adjustable / Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 20
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Upon Request: 0 - 10V Dimming

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1127 / 1214 / 1262 / 1288
Nominal Lumen (lm): 1688 / 1797 / 1869 / 1907
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Reflector°: 14 / 30 / 44
Adjustability: Rotational 360°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380333-

DESCRIPTION

Centriq In 65 - Hypro 40 - Surface - Spot Insert - 65mm / 2 9/16" - 23W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Lens Pack

GENERAL

Series: Centriq
Subseries: Centriq In
Brand: Prolicht
Division: Architectural
Subcategory: Spots

PHYSICAL

Shape: Cylinder
Diameter (mm): 65
Diameter (in): 2 9/16
Length (mm): 375
Length (in): 14 3/4
Height (mm): 165
Height (in): 6 1/2
Light Distribution: Adjustable / Direct
Diffuser: Lens Pack - No Lens / Opal / Linear Spread Lens / Honeycomb / Spread Lens
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 20
Total Output Wattage (W): 18.1
Dimming: Non-Dimmable
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Upon Request: 0 - 10V Dimming

LED


Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1360 / 1465 / 1523 / 1554
Nominal Lumen (lm): 1668 / 1797 / 1869 / 1907
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Reflector°: 12
Adjustability: Rotational 360°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380339-

DESCRIPTION
Centriq In 83 - Hypro 40 - Surface - Spot Insert - 83mm / 3 1/4" - 36W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflector: 12° - Lens Pack

GENERAL
Series: Centriq
Subseries: Centriq In
Brand: Prolicht
Division: Architectural
Subcategory: Spots

PHYSICAL
Shape: Cylinder
Diameter (mm): 83
Diameter (in): 3 1/4
Length (mm): 375
Length (in): 14 3/4
Height (mm): 190
Height (in): 7 1/2
Light Distribution: Adjustable / Direct
Diffuser: Lens Pack - No Lens / Opal / Linear Spread Lens / Honeycomb / Spread Lens
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum


ELECTRICAL
Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26
Total Output Wattage (W): 23.7
Dimming: Non-Dimmable
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Upon Request: 0 - 10V Dimming

LED
Delivered Lumen Range: 2000 - 3999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2923 / 3044 / 3261 / 3328
Nominal Lumen (lm): 3471 / 3615 / 3873 / 3952
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL
Reflector°: 12
Adjustability: Rotational 360°; Tilt 90°

RATINGS AND CERTIFICATIONS
Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380378-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 150mm / 5 7/8" -LED 7W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 33° / 66°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 404 / 427 / 454 / 463
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Optic°: 22 / 33 / 66

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380379-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 150mm / 5 7/8" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380380-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 300mm / 11 13/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 33° / 66°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 404 / 427 / 454 / 463
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 22 / 33 / 66

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380381-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 300mm / 11 13/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380382-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 450mm / 17 11/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 33° / 66°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 404 / 427 / 454 / 463
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 22 / 33 / 66

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380383-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø28mm / 1 1/8" x 450mm / 17 11/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380384-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 150mm / 5 7/8" - LED 10W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 44° / 55°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10
Total Output Wattage (W): 9.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 500 - 999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 694 / 726 / 755 / 770
Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 44 / 55

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380385-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 150mm / 5 7/8" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380386-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 300mm / 17 13/16" - LED 10W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 44° / 55°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10
Total Output Wattage (W): 9.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 500 - 999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 694 / 726 / 755 / 770
Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Optic°: 44 / 55

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380387-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 300mm / 11 13/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 300
Height (in): 11 13/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380388-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 450mm / 17 11/16" - LED 10W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 44° / 55°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10
Total Output Wattage (W): 9.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 500 - 999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 694 / 726 / 755 / 770
Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Optic°: 44 / 55

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380389-

DESCRIPTION

Hangover Plug Micro Dot - Insert for Hypro 40 Surface Ø40mm / 1 9/16" x 450mm / 17 11/16" - LED 6W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Optic: 32° / 58°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40 Micro-Dot
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 40
Diameter (in): 1 9/16
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 310 / 328 / 349 / 356
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380390-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 RecessedØ75mm / 2 15/16" x 150mm / 5 7/8" - LED 10W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 44° / 55°

GENERAL

Series: Hangover
Subseries: Hangover Plug 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 75
Diameter (in): 2 15/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 10
Total Output Wattage (W): 9.1
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 500 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 857 / 896 / 932 / 951
Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 22 / 44 / 55

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380391-

DESCRIPTION

Hangover Plug - Insert for Hypro 40 Surface Ø75mm / 2 15/16" x 150mm / 5 7/8" - Direct / Indirect - LED 20W Max. - 2700K / 3000K / 3500K / 4000K - CRI90 - Non-Dimming - Shine Ring, Optic: 22° / 44° / 55°

GENERAL

Series: Hangover
Subseries: Hangover Plug 75
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Cylinder
Diameter (mm): 75
Diameter (in): 2 15/16
Height (mm): 150
Height (in): 5 7/8
Light Distribution: Direct / Indirect
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 20
Total Output Wattage (W): 18.2
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 1000 - 2999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1696 / 1771 / 1796 / 1833
Nominal Lumen (lm): 2370 / 2476 / 2510 / 2561
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 22 / 44 / 55

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380421-

DESCRIPTION

Snooker - Insert for Hypro 40 Surface - 6.4W LED - 2700K / 3000K / 3500K / 4000K, CRI90, Shine Ring - Optic: 32° / 58°

GENERAL

Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Sphere
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 71
Height (in): 2 13/16
Weight (kg): 0.26
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Glass / Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (MA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 284 / 300 / 319 / 325
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380425-

DESCRIPTION

Snooker Metal - Insert for Hypro 40 Surface - 6.4W LED - 2700K / 3000K / 3500K / 4000K, CRI90, Chrome - Optic: 32° / 58°

GENERAL

Series: Snooker
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Sphere
Diameter (mm): 72
Diameter (in): 2 13/16
Height (mm): 71
Height (in): 2 13/16
Weight (kg): 0.26
Fixture Finish: CHR
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6
Total Output Wattage (W): 5.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (mA): 500

LED

Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 284 / 300 / 319 / 325
Nominal Lumen (lm): 461 / 487 / 517 / 528
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 32 / 58

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380434-

DESCRIPTION

Hypline - 40 Rico - Hypro 40 Linear Insert 705mm for HYPRO 40
Surface: 17W LED - 2700K / 3000K / 3500K / 4000K - CRI 90 -
Dimmable

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 705
Length (in): 27 3/4
Width (mm): 29
Width (in): 1 1/8
Height (mm): 50
Height (in): 1 15/16
Fixture Material: Aluminum

ELECTRICAL


Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 25.8
Total Output Wattage (W): 23.5
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1383 / 1437 / 1500 / 1531
Nominal Lumen (lm): 2028 / 2107 / 2199 / 2244
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380442-

DESCRIPTION

Hypline - 40 Rico - Hypro 40 Linear Insert 1128mm/ 44 7/16" for
HYPRO 40 Surface: 26.4W LED - 2700K / 3000K / 3500K / 4000K -
CRI 90 - Dimmable

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 1128
Length (in): 44 7/16
Width (mm): 39
Width (in): 1 9/16
Height (mm): 50
Height (in): 1 15/16
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 25.8
Total Output Wattage (W): 23.5
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277


LED

Delivered Lumen Range: 2000 - 2999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2213 / 2299 / 2400 / 2449
Nominal Lumen (lm): 3245 / 3371 / 3519 / 3591
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380450-

DESCRIPTION

Hypline - 40 Rico - Hypro 40 Linear Insert 1408mm / 55 7/16" for
HYPRO 40 Surface: 33W LED - 2700K / 3000K / 3500K / 4000K -
CRI 90 - Dimmable

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Rectangle
Length (mm): 1408
Length (in): 55 7/16
Width (mm): 39
Width (in): 1 9/16
Height (mm): 50
Height (in): 1 15/16
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 32.2
Total Output Wattage (W): 29.3
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 2000 - 3999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2767 / 2874 / 3000 / 3061
Nominal Lumen (lm): 4057 / 4214 / 4399 / 4489
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 62

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A380487-

DESCRIPTION

Magiq 4 - Hypro 40 Profile Surface Insert - 13.3W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflectors 8° / 14° / 34°

GENERAL

Series: Magiq
Subseries: Magiq 4 Cell
Brand: Prolicht
Division: Architectural
Mounting Type: Track
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 510
Length (in): 20 1⁄16
Width (mm): 35
Width (in): 1 3⁄8
Height (mm): 72
Height (in): 2 13⁄16
Light Distribution: Downlight
Weight (kg): 0.577
Weight (lbs): 1.27
Fixture Finish: BLK / WHI
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 13.3
Total Output Wattage (W): 12.1
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED


Delivered Lumen Range: 500 - 999 lm
Number of LEDs: 4
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 781 / 843 / 860 / 878
Nominal Lumen (lm): 880 / 954 / 970 / 990
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Reflector°: 8 / 14 / 34

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A380491-

DESCRIPTION

Magiq 4 Korona - Hypro 40 Profile Surface Insert - 13.3W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflectors 8° / 14° / 34°

GENERAL

Series: Magiq
Subseries: Magiq 4 Cell Korona
Brand: Prolicht
Division: Architectural
Mounting Type: Track
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 510
Length (in): 20 1⁄16
Width (mm): 35
Width (in): 1 3⁄8
Height (mm): 72
Height (in): 2 13⁄16
Light Distribution: Downlight
Weight (kg): 0.577
Weight (lbs): 1.27
Fixture Finish: BLK
Accent Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 13.3
Total Output Wattage (W): 12.1
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 1050

LED


Delivered Lumen Range: 500 - 999 lm
Number of LEDs: 4
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 781 / 843 / 860 / 878
Nominal Lumen (lm): 880 / 954 / 970 / 990
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Reflector°: 8 / 14 / 34

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS TRACK

A380493-

DESCRIPTION

Magiq 4 Micro Dot - Hypro 40 Profile Surface Insert - 13.3W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Lens 22° / 38°

GENERAL

Series: Magiq Micro Dot
Subseries: Magiq 4 Cell Micro-Dot
Brand: Prolicht
Division: Architectural
Mounting Type: Track
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 510
Length (in): 20 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.577
Weight (lbs): 1.27
Fixture Finish: BLK
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 13.3
Total Output Wattage (W): 12.1
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 500 - 999 lm
Number of LEDs: 4
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 640 / 691 / 706 / 720
Nominal Lumen (lm): 880 / 954 / 970 / 990
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 22 / 38

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380500-

DESCRIPTION

Magiq 4 + 4 Korona - Hypro 40 Profile Surface Insert - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflectors 8° / 14° / 34°

GENERAL

Series: Magiq
Subseries: Magiq 4+4 Korona
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 910
Length (in): 35 13/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.923
Weight (lbs): 2.035
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Holder Finish: WHI / BLK
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.6
Total Output Wattage (W): 24.2
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1561 / 1685 / 1809 / 1756
Nominal Lumen (lm): 1761 / 1908 / 1940 / 1980
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 8 / 14 / 34

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380503-

DESCRIPTION

Magiq 4 + 4 Micro Dot - Hypro 40 Profile Surface Insert - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Reflectors 11° / 22° / 33°

GENERAL

Series: Magiq Micro Dot
Subseries: Magiq 4+4 Micro Dot
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 910
Length (in): 35 13/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.923
Weight (lbs): 2.035
Fixture Finish: BLK
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.6
Total Output Wattage (W): 24.2
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1280 / 1382 / 1411 / 1440
Nominal Lumen (lm): 1761 / 1908 / 1940 / 1980
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 11 / 22 / 33

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380507-

DESCRIPTION

Magiq 8 - Hypro 40 Profile Surface Insert - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Reflectors 8° / 18° / 34°

GENERAL

Series: Magiq
Subseries: Magiq 8 Cell
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 840
Length (in): 33 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.923
Weight (lbs): 2.035
Fixture Finish: BLK
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.6
Total Output Wattage (W): 24.2
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 1050

LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1561 / 1685 / 1809 / 1756
Nominal Lumen (lm): 1761 / 1908 / 1940 / 1980
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 8 / 14 / 34

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380510-

DESCRIPTION

Magiq 8 Korona - Hypro 40 Profile Surface Insert - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Reflectors 11° / 22° / 33°

GENERAL

Series: Magiq
Subseries: Magiq 8 Cell Korona
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 840
Length (in): 33 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 1.131
Weight (lbs): 2.49
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.6
Total Output Wattage (W): 24.2
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1561 / 1685 / 1809 / 1756
Nominal Lumen (lm): 1761 / 1908 / 1940 / 1980
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 11 / 22 / 33

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A380512-

DESCRIPTION

Magiq 8 Micro Dot - Hypro 40 Profile Surface Insert - 650mm / 25 9/16" - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Optics 21° / 38°

GENERAL

Series: Magiq Micro Dot
Subseries: Magiq 8 Cell Micro-Dot
Brand: Prolicht
Division: Architectural
Mounting Type: Track

PHYSICAL

Shape: Rectangle
Length (mm): 840
Length (in): 33 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Fixture Finish: BLK
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.6
Total Output Wattage (W): 24.2
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED


Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1280 / 1384 / 1411 / 1440
CRI: >80 CRI
Lamp Life (hrs): 50000

OPTICAL

Optic°: 21 / 38

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380516-

DESCRIPTION

Magiq 8 + 8 - Hypro 40 Profile Surface Insert - 53.2W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Reflectors 11° / 22° / 33°

GENERAL

Series: Magiq
Subseries: Magiq 8 + 8 Cell
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 1170
Length (in): 46 1⁄16
Width (mm): 35
Width (in): 1 3⁄8
Height (mm): 72
Height (in): 2 13⁄16
Light Distribution: Downlight
Weight (kg): 1.73
Weight (lbs): 3.81
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 53.2
Total Output Wattage (W): 48.4
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 2000 - 3999 lm
Number of LEDs: 16
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3312 / 3371 / 3443 / 3513
Nominal Lumen (lm): 3521 / 3816 / 3882 / 3961
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 11 / 22 / 33

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380518-

DESCRIPTION

Magiq 8 + 8 Korona - Hypro 40 Profile Surface Insert - 53.2W LED (Zhaga Standard) - Black - 2700K / 3000K / 3500K / 4000K - Reflectors 11° / 22° / 33°

GENERAL

Series: Magiq
Subseries: Magiq 8 + 8 Cell Korona
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 1170
Length (in): 46 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 1.769
Weight (lbs): 3.9
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 53.2
Total Output Wattage (W): 48.4
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 2000 - 2999 lm
Number of LEDs: 16
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3312 / 3371 / 3443 / 3513
Nominal Lumen (lm): 3521 / 3816 / 3882 / 3961
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 10 / 20 / 40

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380522-

DESCRIPTION

Magiq 8 + 8 Micro Dot - Hypro 40 Profile Surface Insert - 53.2W LED (Zhaga Standard) - Black - 2700K / 3000K / 3500K / 4000K - Optics: 21° / 38°

GENERAL

Series: Magiq Micro Dot
Subseries: Magiq 8 + 8 Cell Micro Dot
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 1170
Length (in): 46 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 1.769
Weight (lbs): 3.9
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 53.2
Total Output Wattage (W): 48.4
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 1050

LED

Delivered Lumen Range: 2000 - 2999 lm
Number of LEDs: 16
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2560 / 2763 / 2822 / 2880
Nominal Lumen (lm): 3521 / 3816 / 3882 / 3961
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Optic°: 21 / 38

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380526-

DESCRIPTION

Magiq Hollow Wallwash - Hypro 40 Profile Surface Insert - 18.7W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black

GENERAL

Series: Magiq Hollow Wallwash
Subseries: Magiq Hollow Wallwash
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 660
Length (in): 26
Width (mm): 35
Width (in): 1 3/8
Height (mm): 75
Height (in): 2 15/16
Light Distribution: Downlight
Weight (kg): 0.848
Weight (lbs): 1.87
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 18.7
Total Output Wattage (W): 17.0
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 700


LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1270 / 1270 / 1513 / 1544
Nominal Lumen (lm): 1328 / 1405 / 1574 / 1606
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380529-

DESCRIPTION

Magiq Hollow Wallwash Korona - Hypro 40 Profile Surface Insert
- 18.7W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K -
Black

GENERAL

Series: Magiq Hollow Wallwash
Subseries: Magiq Hollow Wallwash Korona
Brand: Prolicht
Division: Architectural
Subcategory: Wallwash

PHYSICAL

Shape: Rectangle
Length (mm): 660
Length (in): 26
Width (mm): 35
Width (in): 1 3⁄8
Height (mm): 75
Height (in): 2 15⁄16
Light Distribution: Asymmetric
Weight (kg): 0.848
Weight (lbs): 1.87
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 18.7
Total Output Wattage (W): 17.0
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac
only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 700


LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1270 / 1270 / 1513 / 1544
Nominal Lumen (lm): 1328 / 1405 / 1574 / 1606
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380535-

DESCRIPTION

Sign Diva Tube - Insert Ø400mm / 15 3/4" for Hypro 40 Surface:
17 Watt LED - 2700K / 3000K / 3500K / 4000K - CRI 90 - Dimmable
- Shine Ring: No Ring / Opal / Yellow / Orange / Red / Blue /
Green - Diffuser: Opal / Micro-Prism / Sparkling Secret / Vintage
Industrial

GENERAL

Series: Sign Diva Tube
Subseries: Sign Diva Tube
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 395
Diameter (in): 15 9/16
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Direct
Diffuser: PMMA - Opal / Micro-Prism / Sparkling Secret / Vintage
Industrial
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: NOR / OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Extruded Aluminum / Steel

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 17
Total Output Wattage (W): 15.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350
Upon Request: Phase Dimming (Trailing/Leading Edge)


LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1807 / 1943 / 1951 / 1991
Nominal Lumen (lm): 2250 / 2420 / 2430 / 2480
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380539-

DESCRIPTION

Sign Diva Tube Korona - Insert Ø400mm / 15 3/4" for Hypro 40
Surface: 17 Watt LED - 2700K / 3000K / 3500K / 4000K - CRI 90 -
Dimmable - Diffuser: Opal / Micro-Prism / Sparkling Secret /
Vintage Industrial

GENERAL

Series: Sign Diva Tube
Subseries: Sign Diva Tube Korona
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 395
Diameter (in): 15 9/16
Height (mm): 86
Height (in): 3 3/8
Light Distribution: Direct
Diffuser: PMMA - Opal / Micro-Prism / Sparkling Secret / Vintage Industrial
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 17
Total Output Wattage (W): 15.4
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350
Upon Request: Phase Dimming (Trailing/Leading Edge)


LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1807 / 1943 / 1951 / 1991
Nominal Lumen (lm): 2250 / 2420 / 2430 / 2480
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380543-

DESCRIPTION

Sign Diva Tube - Insert Ø570mm / 22 7/16" for Hypro 40 Surface:
49 Watt LED - 2700K / 3000K / 3500K / 4000K - CRI 90 - Dimmable
- Shine Ring: No Ring / Opal / Yellow / Orange / Red / Blue /
Green - Diffuser: Opal / Micro-Prism / Sparkling Secret / Vintage
Industrial

GENERAL

Series: Sign Diva Tube
Subseries: Sign Diva Tube
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Diameter (mm): 570
Diameter (in): 22 7/16
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Direct
Diffuser: PMMA - Opal / Micro-Prism / Sparkling Secret / Vintage
Industrial
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Accent Finish: NOR / OPL / YEL / ORA / RED / BLU / GRN
Fixture Material: Extruded Aluminum / Steel

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 49
Total Output Wattage (W): 44.6
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 350
Upon Request: Phase Dimming (Trailing/Leading Edge)

LED

Delivered Lumen Range: 5000 - 9999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 4978 / 5337 / 5384 / 5494
Nominal Lumen (lm): 6199 / 6646 / 6705 / 6842
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 110

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380551-

DESCRIPTION

Hadi-M Suspended - Insert 1242mm / 48 7/8" x 240mm / 9 7/16"
for Hypro 40 Surface - Direct - 37W LED - 3000K / 3500K / 4000K -
CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-M Suspended
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1242
Length (in): 48 7/8
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 37
Total Output Wattage (W): 33.6
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac
only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 900

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 4269 / 4265 / 4352
Nominal Lumen (lm): 4796 / 4971 / 5072
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380555-

DESCRIPTION

Hadi-M Suspended - Insert 1242mm / 48 7/8" x 240mm / 9 7/16"
for Hypro 40 Surface - Direct / Indirect - 78W LED - 3000K / 3500K
/ 4000K - CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-M Suspended
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1242
Length (in): 48 7/8
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 78
Total Output Wattage (W): 70.9
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 5000 - 9999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 5998 / 5997 / 6119
Nominal Lumen (lm): 9801 / 9799 / 9999
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380559-

DESCRIPTION

Hadi Q Suspended - Insert 1403mm / 55 1/4" x 240mm / 9 7/16" for Hypro 40 Surface - Direct - 37W LED - 3000K / 3500K / 4000K - CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-Q Suspended
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1403
Length (in): 55 1/4
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 37
Total Output Wattage (W): 33.6
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 900

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3911 / 3907 / 3987
Nominal Lumen (lm): 4976 / 4971 / 5072
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380563-

DESCRIPTION

Hadi Q Suspended - Insert 1403mm / 55 1/4" x 240mm / 9 7/16" for Hypro 40 Surface - Direct / Indirect - 78W LED - 3000K / 3500K / 4000K - CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-Q Suspended
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1403
Length (in): 55 1/4
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 78
Total Output Wattage (W): 70.9
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3911 / 3907 / 3987
Nominal Lumen (lm): 4976 / 4971 / 5072
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380567-

DESCRIPTION

Hadi-M Surface - Insert 1242mm / 48 7/8" x 240mm / 9 7/16" for
Hypro 40 Surface - Direct - 37W LED - 3000K / 3500K / 4000K - CRI
90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-M Surface
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1242
Length (in): 48 7/8
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 37
Total Output Wattage (W): 33.6
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac
only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 900

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 4269 / 4265 / 4352
Nominal Lumen (lm): 4796 / 4971 / 5072
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380571-

DESCRIPTION

Hadi-M Surface - Insert 1242mm / 48 7/8" x 240mm / 9 7/16" for
Hypro 40 Surface - Direct / Indirect - 78W LED - 3000K / 3500K /
4000K - CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-M Surface
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1242
Length (in): 48 7/8
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 78
Total Output Wattage (W): 70.9
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 5000 - 9999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 5998 / 5997 / 6119
Nominal Lumen (lm): 9801 / 9799 / 9999
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A380575-

DESCRIPTION

Hadi Q Surface - Insert 1403mm / 55 1/4" x 240mm / 9 7/16" for
Hypro 40 Surface - Direct - 37W LED - 3000K / 3500K / 4000K - CRI
90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-Q Surface
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1403
Length (in): 55 1/4
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 37
Total Output Wattage (W): 33.6
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac
only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 900

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3911 / 3907 / 3987
Nominal Lumen (lm): 4976 / 4971 / 5072
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A380579-

DESCRIPTION

Hadi Q Surface - Insert 1403mm / 55 1/4" x 240mm / 9 7/16" for
Hypro 40 Surface - Direct / Indirect - 78W LED - 3000K / 3500K /
4000K - CRI 90 - Non-Dimming

GENERAL

Series: Hadi
Subseries: Hadi-Q Surface
Brand: Prolicht
Division: Architectural

PHYSICAL

Shape: Round
Length (mm): 1403
Length (in): 55 1/4
Width (mm): 240
Width (in): 9 7/16
Height (mm): 48
Height (in): 1 7/8
Light Distribution: Direct
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Extruded Aluminum / Steel
Cable Details: 2,000mm or 6,000mm Transparent Cable

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 78
Total Output Wattage (W): 70.9
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

LED

Delivered Lumen Range: 5000 - 9999 lm
Color Temperature (°K): 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 5783 / 5781 / 5899
Nominal Lumen (lm): 9801 / 9799 / 9999
CRI: >90 CRI
Lamp Life (hrs): 50000



OPTICAL

Beam Angle: 90
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

PROJECT
TYPE
NOTES
QUANTITY
DATE

A38063-

DESCRIPTION

HYPRO 40 - Insert with PLUG-Cable in 2/4M 500mA max22W - Non - Dimming / 0-10V Dimming

GENERAL

Series: Hypro
Subseries: Hypro 40-X
Brand: Prolicht
Division: Architectural

PHYSICAL


Length (mm): 375
Length (in): 14 3/4
Width (mm): 36
Width (in): 1 7/16
Height (mm): 35
Height (in): 1 3/8
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A380639-

DESCRIPTION

Rico LED (Zhaga Standard) - 1128mm / 44 7/16" Hypro 40 Profile
Insert - 35W LED (Zhaga Standard) - 2700K / 3000K / 3500K /
4000K - Beam Angle: 46° / 62°

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Length (mm): 1288
Length (in): 44 7/16
Width (mm): 29
Width (in): 1 1/10
Height (mm): 50
Height (in): 2
Light Distribution: Direct
Weight (kg): 1.191
Weight (lbs): 2.63
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 25
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 1
Input Voltage (V): 120
Constant Current (mA): 350

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2213 / 2299 / 2400 / 2449
Nominal Lumen (lm): 3245 / 3371 / 3519 / 3591
CRI: >80 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 46 / 62

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38870

DESCRIPTION

Idaho / Hypro 40 Recessed System Linear Coupler

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 150
Length (in): 5 7/8
Width (mm): 35
Width (in): 1 3/8
Height (mm): 33
Height (in): 1 5/16
Weight (kg): 0.167
Weight (lbs): 0.37
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38876

DESCRIPTION

Idaho / Hypro 40 Recessed System Central Feed

GENERAL

Brand: Prolicht
Division: Architectural



PHYSICAL

Length (mm): 31
Length (in): 1 ¼
Width (mm): 27
Width (in): 1 ⅛
Height (mm): 45
Height (in): 1 ¾
Weight (kg): 0.046
Weight (lbs): 0.10
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38877

DESCRIPTION

Idaho / Hypro 40 Recessed System - Cable Holder

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Length (mm): 25
Length (in): 1
Width (mm): 36
Width (in): 1 7/16
Height (mm): 22
Height (in): 7/8
Weight (kg): 0.004
Weight (lbs): 0.008
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38880

DESCRIPTION

Idaho 40 / Hypro 40 - System - 705mm Opal Diffuser

GENERAL

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Rectangle

Length (mm): 705

Length (in): 27 3/4

Width (mm): 35

Width (in): 1 3/8

Height (mm): 28

Height (in): 1 1/8

Weight (kg): 0.138

Weight (lbs): 0.3


Diffuser: PMMA - Opal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



(l+30mm) x 43mm
(l+ 1 3/16") x 1 11/16"



100mm
3 15/16"



10mm | 25mm
3/8" | 1"



A3HY40-SUR-SYS COMPONENTS

A38881

DESCRIPTION

Idaho / Hypro 40 System - 1408mm Opal Diffuser

GENERAL

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Rectangle

Length (mm): 1408

Length (in): 55 7/16

Width (mm): 35

Width (in): 1 3/8

Height (mm): 28

Height (in): 1 1/8


Weight (kg): 0.276

Weight (lbs): 0.61

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



(l+30mm) x 43mm
(l+ 1 3/16") x 1 11/16"



100mm
3 15/16"



10mm | 25mm
3/8" | 1"



A

A3HY40-SUR-SYS COMPONENTS

A38882

DESCRIPTION

Idaho 40 / Hypro 40 - System - 2113mm Opal Diffuser

GENERAL

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Rectangle

Length (mm): 2113

Length (in): 83 3/16

Width (mm): 35

Width (in): 1 3/8

Height (mm): 28

Height (in): 1 1/8

Weight (kg): 0.41


Weight (lbs): 0.9

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



(l+30mm) x 43mm
(l+ 1 3/16") x 1 11/16"



100mm
3 15/16"



10mm | 25mm
3/8" | 1"



A

A3HY40-SUR-SYS COMPONENTS

A38883

DESCRIPTION

Idaho 40 / Hypro 40 - System - 2815mm Opal Diffuser

GENERAL

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Rectangle

Length (mm): 2815

Length (in): 110 13/16

Width (mm): 35

Width (in): 1 3/8

Height (mm): 28

Height (in): 1 1/8


Weight (kg): 0.551

Weight (lbs): 1.215

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



(1+30mm) x 43mm
(1+ 1 3/16") x 1 11/16"



100mm
3 15/16"



10mm | 25mm
3/8" | 1"



A3HY40-SUR-SYS COMPONENTS

A38884

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 705mm Micro Prism Diffuser

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 705
Length (in): 27 3/4
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.2
Weight (lbs): 0.44
Diffuser: PMMA - Micro-Prism

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38885

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 1408mm Micro Prism Diffuser

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 1408
Length (in): 55 7/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.4
Weight (lbs): 0.88
Diffuser: PMMA - Micro-Prism

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38886

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 2113mm Micro Prism Diffuser

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 2113
Length (in): 38 3/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.599
Weight (lbs): 1 5/16
Diffuser: PMMA - Micro-Prism

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38887

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 2815mm Micro Prism Diffuser

GENERAL

Brand: Prolicht
Division: Architectural


PHYSICAL

Length (mm): 2815
Length (in): 110 13/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.798
Weight (lbs): 1.76
Diffuser: PMMA - Micro-Prism

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38888

DESCRIPTION

Hypro 40 - Recessed System - Rico Cover - 705mm - Transparent / Black

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural



PHYSICAL

Shape: Rectangle
Length (mm): 705
Length (in): 27 3/4
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.138
Weight (lbs): 0.304
Diffuser: PMMA - Transparent / Black

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38889

DESCRIPTION

Idaho 40 / Hypro 40 - Rico LED (Zhaga Standard) Cover - 1408mm - Transparent

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural



PHYSICAL

Shape: Rectangle
Length (mm): 1408
Length (in): 55 7/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.276
Weight (lbs): 0.608
Diffuser: PMMA - Transparent

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38890

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 2113mm Clear Cover

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural



PHYSICAL

Shape: Rectangle
Length (mm): 2113
Length (in): 83 3/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.414
Weight (lbs): 0.913

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38891

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - 2815mm Clear Cover

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural



PHYSICAL

Shape: Rectangle
Length (mm): 2815
Length (in): 110 13/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.551
Weight (lbs): 1.215
Diffuser: PMMA - Transparent

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38892

DESCRIPTION

Idaho / Hypro 40 Recessed System - 1000mm Black Cover

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 1000
Length (in): 39 3/8
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.194
Weight (lbs): 0.428
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38893

DESCRIPTION

Idaho / Hypro 40 Recessed System - 2000mm Black Cover

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 2000
Length (in): 78 3/4
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.392
Weight (lbs): 0.86
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38894

DESCRIPTION

Idaho / Hypro 40 Recessed System - 3000mm Black Cover

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural


PHYSICAL

Shape: Rectangle
Length (mm): 3000
Length (in): 118 1/8
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.588
Weight (lbs): 1.3
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS RECESSED

A38895-

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - Aluminum Profile per meter - Max 3000mm / 118 1/8"

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural
Mounting Type: Recessed
Mounting Location: Ceiling
Subcategory: Profile


PHYSICAL

Shape: Rectangle
Length (mm): Max. 3000
Length (in): 118 1/8
Width (mm): 35.2
Width (in): 1 3/8
Height (mm): 27.4
Height (in): 1 1/16
Weight (kg): 0.237
Weight (lbs): 0.52
Fixture Finish: ANA / SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



Max. 3000mm 118 1/8"



A3HY40-SUR-SYS COMPONENTS

A38896-

DESCRIPTION

Idaho 40 / Hypro 40 - Recessed System - End Plate Corona - 1 pair

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural



PHYSICAL

Shape: Rectangle
Length (mm): 1
Length (in): 1/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 28
Height (in): 1 1/8
Weight (kg): 0.015
Weight (lbs): 0.033
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38909-

DESCRIPTION

Magiq 4 + 4 - Hypro 40 Profile Surface Insert - 26.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black - Reflectors 11° / 22° / 33°

GENERAL

Series: Magiq
Subseries: Magiq 4 + 4 Cell
Brand: Prolicht
Division: Architectural
Subcategory: Downlight

PHYSICAL

Shape: Rectangle
Length (mm): 710
Length (in): 27 15/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 72
Height (in): 2 13/16
Light Distribution: Downlight
Weight (kg): 0.923
Weight (lbs): 2.035
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 26.9
Total Output Wattage (W): 24.2
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (mA): 1050

LED

Delivered Lumen Range: 1000 - 1999 lm
Number of LEDs: 8
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1561 / 1685 / 1809 / 1756
Nominal Lumen (lm): 1761 / 1908 / 1940 / 1980
CRI: >90 CRI
Lamp Life (hrs): 50000


OPTICAL

Reflector°: 11 / 22 / 33

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A38917-

DESCRIPTION

Magiq Wallwash - Hypro 40 Profile Surface Insert - 31.6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Black

GENERAL

Series: Magiq Wallwash
Subseries: Magiq Wallwash
Brand: Prolicht
Division: Architectural
Subcategory: Wallwash

PHYSICAL

Shape: Rectangle
Length (mm): 760
Length (in): 29 15/16
Width (mm): 35
Width (in): 1 3/8
Height (mm): 85
Height (in): 3 3/8
Light Distribution: Asymmetric
Weight (kg): 1.221
Weight (lbs): 2.69
Fixture Material: Aluminum Die Cast

ELECTRICAL


Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 32
Total Output Wattage (W): 29.5
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 1
Input Voltage (V): 120 - 277
Constant Current (mA): 500

LED

Delivered Lumen Range: 2000 - 2999 lm
Number of LEDs: 5
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 2125 / 2260 / 2513 / 2564
Nominal Lumen (lm): 2550 / 2793 / 2877 / 2936
CRI: >90 CRI
Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3HY40-SUR-SYS COMPONENTS

A38919-

DESCRIPTION

Rico LED (Zhaga Standard) - Hypro 40 Profile Insert - 16.5W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Beam Angle: 46° / 62°

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Length (mm): 705
Length (in): 27 3/4
Width (mm): 29
Width (in): 1 1/10
Height (mm): 50
Height (in): 2
Light Distribution: Direct
Weight (kg): 0.668
Weight (lbs): 1.47
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 10 - 19 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 16.5
Total Output Wattage (W): 15
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (mA): 350

LED

Delivered Lumen Range: 1000 - 1999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 1760 / 1880 / 1920 / 1960
Nominal Lumen (lm): 2250 / 2400 / 2450 / 2500
CRI: >80 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 46 / 62

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38920-

DESCRIPTION

Rico LED (Zhaga Standard) - Hypro 40 Profile Insert - 33.W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Beam Angle: 46° / 62°

GENERAL

Series: Hypro
Subseries: Hypro 40
Brand: Prolicht
Division: Architectural

PHYSICAL

Length (mm): 1408
Length (in): 55 7/16
Width (mm): 29
Width (in): 1 1/10
Height (mm): 50
Height (in): 2
Light Distribution: Direct
Weight (kg): 1.191
Weight (lbs): 2.63
Fixture Material: Metal

ELECTRICAL

Input Wattage Range: 30 - 49 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 33.3
Total Output Wattage (W): 30
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 1
Input Voltage (V): 120
Constant Current (mA): 350

LED

Delivered Lumen Range: 3000 - 4999 lm
Color Temperature (°K): 2700 / 3000 / 3500 / 4000
Max. Delivered Lumen (lm): 3520 / 3760 / 3243 / 3920
Nominal Lumen (lm): 4500 / 4800 / 4900 / 5000
CRI: >80 CRI
Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 46 / 62

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38937-



DESCRIPTION
Idaho 40 / Hypro 40 - Suspension End Cap

GENERAL
Brand: Prolicht
Division: Architectural

PHYSICAL
Shape: Rectangle
Length (mm): 38
Length (in): 1 ½
Width (mm): 12
Width (in): 1/2
Height (mm): 76
Height (in): 3
Weight (kg): 0.046
Weight (lbs): .10
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS
Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38939-

DESCRIPTION

Idaho 40 / Hypro 40 - Surface/Suspension L-Coupler

GENERAL

Brand: Prolicht
Division: Architectural



PHYSICAL

Length (mm): 70
Length (in): 2 ¾
Width (mm): 70
Width (in): 2 ¾
Height (mm): 76
Height (in): 3
Weight (kg): 0.247
Weight (lbs): 0.54
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38940-

DESCRIPTION

Idaho 40 / Hypro 40 - Surface/Suspension T-Coupler

GENERAL

Brand: Prolicht
Division: Architectural



PHYSICAL

Length (mm): 100
Length (in): 3 15/16
Width (mm): 70
Width (in): 2 3/4
Height (mm): 76
Height (in): 3
Weight (kg): 0.524
Weight (lbs): 1.16
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38941-

DESCRIPTION

Idaho 40 / Hypro 40 - Surface/Suspension X-Coupler

GENERAL

Brand: Prolicht
Division: Architectural



PHYSICAL

Length (mm): 100
Length (in): 3 15/16
Width (mm): 100
Width (in): 3 15/16
Height (mm): 76
Height (in): 3
Weight (kg): 0.675
Weight (lbs): 1.49
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS

A38942-

DESCRIPTION

Idaho 40 / Hypro 40 - Surface/Suspension Ceiling-Wall Coupler

GENERAL

Brand: Prolicht
Division: Architectural



PHYSICAL

Length (mm): 49
Length (in): 1 15/16
Width (mm): 49
Width (in): 1 15/16
Height (mm): 210
Height (in): 8 1/4
Weight (kg): 0.587
Weight (lbs): 1.29
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3HY40-SUR-SYS COMPONENTS

A38943



DESCRIPTION
Idaho 40 / Hypro 40 - Surface Installation Clip

GENERAL
Brand: Prolicht
Division: Architectural

PHYSICAL
Length (mm): 30
Length (in): 1 3/16
Width (mm): 30
Width (in): 1 7/16
Height (mm): 12
Height (in): 1/2
Weight (kg): 0.004
Weight (lbs): 1/8
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS
Certified By: Certified for North American Standards
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3HY40-SUR-SYS COMPONENTS SURFACE

PROJECT
TYPE
NOTES
QUANTITY
DATE

A3D117-

DESCRIPTION

Idaho 40 / Hypro 40 - Surface System Profile per meter - Max 3000mm / 118 1/8"

GENERAL



Brand: Prolicht
Division: Architectural
Mounting Type: Surface
Mounting Location: Ceiling
Subcategory: Profile

PHYSICAL

Shape: Rectangle
Length (mm): 1000
Length (in): 39 3/8
Width (mm): 38
Width (in): 1 1/2
Height (mm): 76
Height (in): 3
Weight (kg): 0.959
Weight (lbs): 2.11
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)