

A3MINTRK-SUR-SYS COMPONENTS

A380203-

DESCRIPTION

Minimal Track - Disq Round Aura Cover

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Round

Diameter (mm): 135

Diameter (in): 5 ⁵/₁₆

Height (mm): 5

Height (in): 3/16

Weight (kg): 0.023

Weight (lbs): 0.051



Fixture Finish: YEL / ORA / RED / BLU / GRN

Fixture Material: Plastic

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS



A380204-

DESCRIPTION
 Minimal Track - Disq Square Aura Cover

GENERAL
 Series: Minimal Track
 Brand: Prolicht
 Division: Architectural

PHYSICAL
 Shape: Square
 Length (mm): 144
 Length (in): 5 ¹¹/₁₆
 Width (mm): 58
 Width (in): 2 ⁵/₁₆
 Height (mm): 5
 Height (in): 3/16
 Weight (kg): 0.023
 Weight (lbs): 0.051
 Fixture Finish: YEL / ORA / RED / BLU / GRN
 Fixture Material: Plastic

RATINGS AND CERTIFICATIONS
 Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380205-

DESCRIPTION

Snooker Insert for Minimal Track - 6.5W LED (Zhaga Standard) - 455lm, 48Vdc, CRI90 (DALI Dimming Only) - Optic: 32°/58° - Cable Options

GENERAL

Series: Snooker
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Round
 Diameter (mm): 72
 Diameter (in): 2 ¹³/₁₆
 Height (mm): 71
 Height (in): 2 ¹³/₁₆
 Light Distribution: Direct
 Weight (kg): 0.26
 Weight (lbs): 0.04
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Total Output Wattage (W): 6
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 310 / 328 / 347 / 356
 Nominal Lumen (lm): 460 / 487 / 514 / 528
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 32 / 58
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380206-

DESCRIPTION

Hangover Plug Ø28 - 150mm LED (Zhaga Standard) 6.5W Max. 446lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 28
 Diameter (in): 1 1/8
 Height (mm): 150
 Height (in): 5 7/8
 Light Distribution: Direct
 Weight (kg): 0.124
 Weight (lbs): 0.273
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI/0-10V Dimming with bridge

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 4000
 Max. Delivered Lumen (lm): 377-389 / 400-412 / 433-446
 Nominal Lumen (lm): 455
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66
 Beam Angle: 26 / 56
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380207-

DESCRIPTION

Hangover Plug Ø28 - 300mm LED (Zhaga Standard) 6.5W Max. 446lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 28
 Diameter (in): 1 1/8
 Height (mm): 300
 Height (in): 11 13/16
 Light Distribution: Direct
 Weight (kg): 0.24
 Weight (lbs): 0.529
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 4000
 Max. Delivered Lumen (lm): 377-389 / 400-412 / 433-446
 Nominal Lumen (lm): 455 / 482 / 522
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66
 Beam Angle: 26 / 56
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380208-

DESCRIPTION

Hangover Plug Ø28 - 450mm LED (Zhaga Standard) 6.5W Max.
446lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Shape: Cylinder

Diameter (mm): 28

Diameter (in): 1 1/8

Height (mm): 450

Height (in): 17 11/16

Light Distribution: Direct

Weight (kg): 0.355

Weight (lbs): 0.783

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG /
MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH /
GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Accent Finish: OPL / YEL / ORA / RED / BLU / GRN

Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 6.5

Dimming: Non-Dimmable

Driver Included: No

Driver Location: Remote

Driver Type: Constant Voltage - 120/277Vac

Driver Class: Class 2

Input Voltage (V): 48

Constant Current (MA): 500

Upon Request: DALI

LED

Delivered Lumen Range: 100 - 499 lm

Color Temperature (°K): 2700 / 3000 / 4000

Max. Delivered Lumen (lm): 377-389 / 400-412 / 433-446

Nominal Lumen (lm): 455 / 482 / 522

CRI: >90 CRI

Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66


Beam Angle: 26 / 56

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380209-

DESCRIPTION

Hangover Plug Ø28 Micro Dot - 150mm LED (Zhaga Standard)
6.5W Max. 352lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 28
 Diameter (in): 1 1/8
 Height (mm): 150
 Height (in): 5 7/8
 Light Distribution: Direct
 Weight (kg): 0.124
 Weight (lbs): 0.273
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED

Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 4000
 Max. Delivered Lumen (lm): 280-307 / 297-325 / 322 - 352
 Nominal Lumen (lm): 455.22 / 482 / 522.17
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66
 Beam Angle: 32 / 58
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380210-

DESCRIPTION

Hangover Plug Ø28 Micro Dot - 300mm LED (Zhaga Standard)
6.5W Max. 352lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 28
 Diameter (in): 1 1/8
 Height (mm): 300
 Height (in): 11 13/16
 Light Distribution: Direct
 Weight (kg): 0.24
 Weight (lbs): 0.529
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED



Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 4000
 Max. Delivered Lumen (lm): 280-307 / 297-325 / 322 - 352
 Nominal Lumen (lm): 455.22 / 482 / 522.17
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66
 Beam Angle: 26 / 56
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380211-

DESCRIPTION

Hangover Plug Ø28 Micro Dot - 450mm LED (Zhaga Standard)
6.5W Max. 352lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track
Brand: Prolicht
Division: Architectural
Mounting Type: Track
Mounting Location: Ceiling
Subcategory: Modular

PHYSICAL

Shape: Cylinder
Diameter (mm): 28
Diameter (in): 1 1/8
Height (mm): 450
Height (in): 17 11/16
Light Distribution: Direct
Weight (kg): 0.355
Weight (lbs): 0.783
Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 6.5
Dimming: Non-Dimmable
Driver Included: No
Driver Location: Remote
Driver Type: Constant Voltage - 120/277Vac
Driver Class: Class 2
Input Voltage (V): 48
Constant Current (MA): 500
Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700 / 3000 / 4000
Max. Delivered Lumen (lm): 280-307 / 297-325 / 322 - 352
Nominal Lumen (lm): 455.22 / 482 / 522.17
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Optic°: 33 / 66
Beam Angle: 26 / 56
Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



28mm 1 1/8"



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380212-

DESCRIPTION

Hangover Plug Ø40 - 150mm LED (Zhaga Standard) 9W Max.
 868lm, 48Vdc, CRI90

GENERAL

Series: Minimal Track _____
 Brand: Prolicht _____
 Division: Architectural _____
 Mounting Type: Track _____
 Mounting Location: Ceiling _____
 Subcategory: Modular _____

PHYSICAL

Shape: Cylinder _____
 Diameter (mm): 40 _____
 Diameter (in): 1 9/16 _____
 Height (mm): 150 _____
 Height (in): 5 7/8 _____
 Light Distribution: Direct _____
 Weight (kg): 0.293 _____
 Weight (lbs): 0.646 _____
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR _____
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN _____
 Fixture Material: Aluminum _____

ELECTRICAL

Input Wattage Range: 1 - 9 W _____
 Lamp Type: LED (Zhaga Standard) _____
 Input Wattage (W): 9 _____
 Dimming: Non-Dimmable _____
 Driver Included: No _____
 Driver Location: Remote _____
 Driver Type: Constant Voltage - 120/277Vac _____
 Driver Class: Class 2 _____
 Input Voltage (V): 48 _____
 Constant Current (MA): 500 _____
 Upon Request: DALI _____

LED


Delivered Lumen Range: 500 - 999 lm _____
 Color Temperature (°K): 2700 / 3000 / 4000 _____
 Max. Delivered Lumen (lm): 752 - 782 / 787 - 818 / 834 - 868 _____
 Nominal Lumen (lm): 969.41 / 1014 / 1075.27 _____
 CRI: >90 CRI _____
 Lamp Life (hrs): 50000 _____

OPTICAL

Optic°: 44 / 55 _____
 Beam Angle: 40 / 52 _____
 Adjustability: Fixed _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380214-

DESCRIPTION

Plug Connector - 2000mm or 4000mm Cable

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Length (mm): 151

Length (in): 5 ¹⁵/₁₆

Width (mm): 19

Width (in): 3/4

Height (mm): 52

Height (in): 2 ¹/₁₆

Max. Overall Height (mm): 2052 / 4052

Max. Overall Height (in): 80 ¹³/₁₆

Weight (kg): 0.112

Weight (lbs): 0.247

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Accent Finish: BLK / WHI / ORA / RED / GRN

Fixture Material: Aluminum

Cable Details: 2000mm / 78 3/4" or 4000 / 157 1/2" Cable


OPTICAL

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380215-


DESCRIPTION
 Plug Connector - 10000mm Cable

GENERAL
 Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL
 Length (mm): 151
 Length (in): 5 ¹⁵/₁₆
 Width (mm): 19
 Width (in): 3/4
 Height (mm): 52
 Height (in): 2 ¹/₁₆
 Max. Overall Height (mm): 10052
 Max. Overall Height (in): 395 ³/₄
 Weight (kg): 0.112
 Weight (lbs): 0.247
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum
 Cable Details: 10,000mm / 393 11/16" Cable - Black

OPTICAL
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS
 Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380216-


DESCRIPTION
 Plug Connector - 1100mm Cable

GENERAL
 Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL
 Length (mm): 151
 Length (in): 5 ¹⁵/₁₆
 Width (mm): 19
 Width (in): 3/4
 Height (mm): 52
 Height (in): 2 ¹/₁₆
 Max. Overall Height (mm): 1152
 Max. Overall Height (in): 45 ³/₈
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum
 Cable Details: 1100mm / 43 5/16" Cable - Black

OPTICAL
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS
 Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS SURFACE

A380596-

DESCRIPTION

Microline Insert L=672mm, LED 8W, max. 429lm, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Surface
 Mounting Location: Wall / Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Rectangle
 Length (mm): 674
 Length (in): 26 ⁹/₁₆
 Width (mm): 11
 Width (in): 7/16
 Height (mm): 7
 Height (in): 1/4
 Light Distribution: Direct
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 9.79
 Total Output Wattage (W): 7.26
 Dimming: Non-Dimmable
 Driver Included: Yes
 Driver Location: Integrated
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 120 - 277
 Output Voltage (V): 48
 Upon Request: Dali/ 0-10V Dimming

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000
 Max. Delivered Lumen (lm): 386
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 116

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS SURFACE

A380597-

DESCRIPTION

Microline Insert for Minimal Track Surface - L=1170mm / 46 1/16", LED 15.8W, max. 772lm, CRI90

GENERAL

Series: Microline _____
 Brand: Prolicht _____
 Division: Architectural _____
 Mounting Type: Surface _____
 Mounting Location: Wall / Ceiling _____
 Subcategory: Modular _____

PHYSICAL

Shape: Rectangle _____
 Length (mm): 1174 _____
 Length (in): 46 1/4 _____
 Width (mm): 11 _____
 Width (in): 7/16 _____
 Height (mm): 7 _____
 Height (in): 1/4 _____
 Light Distribution: Direct _____
 Fixture Material: Aluminum _____

ELECTRICAL

Input Wattage Range: 10 - 19 W _____
 Lamp Type: LED (Zhaga Standard) _____
 Input Wattage (W): 15.8 _____
 Total Output Wattage (W): 14.4 _____
 Dimming: Non-Dimmable _____
 Driver Included: Yes _____
 Driver Location: Integrated _____
 Driver Type: Constant Voltage - Universal _____
 Driver Class: Class 2 _____
 Input Voltage (V): 120 - 277 _____
 Output Voltage (V): 48 _____
 Upon Request: Dali/ 0-10V Dimming _____

LED


Delivered Lumen Range: 500 - 999 lm _____
 Color Temperature (°K): 2700 / 3000 _____
 Max. Delivered Lumen (lm): 772 _____
 CRI: >90 CRI _____
 Lamp Life (hrs): 50000 _____

OPTICAL

Beam Angle: 116 _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS SURFACE

A380598-

DESCRIPTION

Microline Insert for Minimal Track Surface L=1670mm / 65 3/4", LED 24W, max. 1158lm, CRI90

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Surface
 Mounting Location: Wall / Ceiling
 Subcategory: Profile

PHYSICAL

Shape: Rectangle
 Length (mm): 1674
 Length (in): 65 7/8
 Width (mm): 11
 Width (in): 7/16
 Height (mm): 7
 Height (in): 1/4
 Light Distribution: Direct
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 20 - 29 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 24
 Total Output Wattage (W): 21.8
 Dimming: Non-Dimmable
 Driver Included: Yes
 Driver Location: Integrated
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 120 - 277
 Output Voltage (V): 48
 Upon Request: Dali/ 0-10V Dimming

LED


Delivered Lumen Range: 1000 - 1999 lm
 Color Temperature (°K): 2700 / 3000
 Max. Delivered Lumen (lm): 1158
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 116

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380601-

DESCRIPTION

Hangover Plug Ø40 - 450mm LED (Zhaga Standard) 9W Max.
868lm, 48Vdc, CRI90

GENERAL

Series: Hangover Plug
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 40
 Diameter (in): 1 9/16
 Height (mm): 450
 Height (in): 17 11/16
 Light Distribution: Direct
 Weight (kg): 0.481
 Weight (lbs): 1.06
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 9
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED

Delivered Lumen Range: 500 - 999 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 695 / 726 / 755 / 770
 Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 40 / 52
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380602-

DESCRIPTION

Hangover Plug Ø75 - 150mm LED 9.8W Max. 951lm, 2700K / 3000K / 3500K / 4000K - 48Vdc, CRI90 - Shine Ring - Optics: 18° / 36° / 56°

GENERAL

Series: Hangover Plug
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 75
 Diameter (in): 2 15/16
 Height (mm): 150
 Height (in): 5 7/8
 Light Distribution: Direct
 Weight (kg): 0.481
 Weight (lbs): 1.06
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 9.8
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (mA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 500 - 999 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 857 / 896 / 932 / 951
 Nominal Lumen (lm): 969 / 1014 / 1054 / 1075
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 18 / 36 / 56
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380603-

DESCRIPTION

Hangover Plug Suspension Direct/Indirect Ø75 - 150mm LED
 9.8W Max. 1829lm, 2700K / 3000K / 3500K / 4000K - 48Vdc, CRI90
 - Shine Ring - Optics: 18° / 36° / 56° (Plug Connector not included
 - See Components)

GENERAL

Series: Hangover Plug
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 75
 Diameter (in): 2 15/16
 Height (mm): 150
 Height (in): 5 7/8
 Light Distribution: Direct / Indirect
 Weight (kg): 0.481
 Weight (lbs): 1.06
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG /
 MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH /
 GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 19.5
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (mA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 500 - 999 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 1757 / 1789 / 1796 / 1833
 Nominal Lumen (lm): 2370 / 2476 / 2510 / 2561
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Optic°: 18 / 36 / 56
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380604-

DESCRIPTION

Magiq Micro for Minimal TracK - 5.5W LED (Zhaga Standard) - 2700K / 3000K / 3500K Max. 365lm, Beam Angle 54

GENERAL

Series: Magiq Micro _____
 Brand: Prolicht _____
 Division: Architectural _____
 Mounting Type: Track _____

PHYSICAL

Shape: Rectangle _____
 Length (mm): 300 _____
 Length (in): 11 ¹³/₁₆ _____
 Width (mm): 11 _____
 Width (in): 7/16 _____
 Height (mm): 7 _____
 Height (in): 1/4 _____
 Light Distribution: Direct _____
 Fixture Finish: BLK / WHI _____
 Fixture Material: Aluminum Die Cast _____

ELECTRICAL

Input Wattage Range: 1 - 9 W _____
 Lamp Type: LED _____
 Input Wattage (W): 7.5 _____
 Total Output Wattage (W): 5 _____
 Dimming: Non-Dimmable _____
 Driver Included: Yes _____
 Driver Location: Integrated _____
 Driver Type: Constant Current - Universal _____
 Driver Class: Class 2 _____
 Input Voltage (V): 120 - 277 _____
 Output Voltage (V): 48 _____
 Upon Request: Dali/ 0-10V Dimming _____

LED


Color Temperature (°K): 2700 / 3000 / 3500 _____
 Max. Delivered Lumen (lm): 338 / 365 _____
 Nominal Lumen (lm): 400 _____
 CRI: >90 CRI _____
 Lamp Life (hrs): 50000 _____

OPTICAL

Beam Angle: 54 _____

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards _____
 IP rating: IP20 _____



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380605-

DESCRIPTION

Minimal Track Surface Snooker - 6.5W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - 48Vdc - Chrome - CRI90 (DALI Dimming Only) - Optic: 32°/58°

GENERAL

Series: Snooker Metal
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Round
 Diameter (mm): 72
 Diameter (in): 2 13/16
 Height (mm): 71
 Height (in): 2 13/16
 Light Distribution: Direct
 Weight (kg): 0.26
 Weight (lbs): 0.04
 Fixture Finish: CHR
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Total Output Wattage (W): 6
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (MA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 283 / 328 / 349 / 356
 Nominal Lumen (lm): 460 / 487 / 517 / 528
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 32 / 58
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380606-

DESCRIPTION

Snooker Insert for Minimal Track Surface - 6.5W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - 48Vdc - Chrome - CRI90 (DALI Dimming Only) - Shine Ring - Optic: 32°/58°

GENERAL

Series: Snooker Metal
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Round
 Diameter (mm): 72
 Diameter (in): 2 13/16
 Height (mm): 71
 Height (in): 2 13/16
 Light Distribution: Direct
 Weight (kg): 0.26
 Weight (lbs): 0.04
 Fixture Finish: CHR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.5
 Total Output Wattage (W): 6
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (mA): 500
 Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 283 / 328 / 349 / 356
 Nominal Lumen (lm): 460 / 487 / 517 / 528
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 32 / 58
 Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380655-

DESCRIPTION

Bilo Insert for Minimal Track System Surface - Ø120mm - 6.4W LED, 48V, CRI:90, Beam 180

GENERAL

Series: Bilo
 Subseries: Bilo
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Sphere
 Diameter (mm): 120
 Diameter (in): 4 ¾
 Height (mm): 120
 Height (in): 4 ¾
 Light Distribution: Omnidirectional
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Accent Finish: OPL / YEL / ORA / RED / BLU / GRN
 Fixture Material: Glass / Metal
 Cable Details: 2000mm/78 ¾" or 4000mm/157 ½" Cable - Color Options: Black / White / Orange / Red / Green

ELECTRICAL



Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6.4
 Dimming: Non-Dimmable / 0-10V Dimming
 Driver Included: No
 Driver Location: Integrated
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (mA): 500
 Upon Request: 0-10V Dimming with Tridonic Bridge

LED

Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 356 / 377 / 398 / 408
 Nominal Lumen (lm): 460 / 487 / 514 / 528
 CRI: >90 CRI
 Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380746-

DESCRIPTION

Imagine Micro Insert for Minimal Track Surface - 23mm / 7/8" x 66mm / 2 5/8" - 4.4W LED, 2700K / 3000K / 3500K / 4000K - 48 - Non-Dimming / Dali Dim - Adjustable - CRI:90 - Beam: 26° / 28° / 38° / 46° / 64°

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 23
 Diameter (in): 7/8
 Height (mm): 66
 Height (in): 2 5/8
 Light Distribution: Direct
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Holder Finish: WHI / BLK
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 4.4
 Dimming: Dali Dimming
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 48

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 252 / 271 / 315 / 290
 Nominal Lumen (lm): 295 / 317 / 368 / 339
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 26, 28, 38, 46, 64
 Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380758-

DESCRIPTION

Disq Round for Minimal Track Surface, LED (Zhaga Standard):
 5.1W LED (Zhaga Standard) - 2700K - 400lm - 48V (DALI Dimming
 Only) - Dibond Cover

GENERAL

Series: Disq Round
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Round
 Diameter (mm): 206
 Diameter (in): 8 1/8
 Height (mm): 19
 Height (in): 3/4
 Light Distribution: Indirect
 Weight (kg): 0.3
 Weight (lbs): 0.66
 Fixture Finish: COP / MIR / SST
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 5.1
 Total Output Wattage (W): 4.6
 Dimming: Non-Dimmable
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - 120/277Vac
 Driver Class: Class 2
 Input Voltage (V): 48
 Constant Current (mA): 96
 Upon Request: DALI

LED



Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700
 Max. Delivered Lumen (lm): 400
 Nominal Lumen (lm): 400
 CRI: >90 CRI
 Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 180

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380759-

DESCRIPTION

Disq Round for Minimal Round, LED (Zhaga Standard): 5.1W LED (Zhaga Standard) - 2700K - 400lm - 48V (DALI DIM Only) - Powder Coat Colors

GENERAL

Series: Disq Round

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Shape: Round

Diameter (mm): 206

Diameter (in): 8 1/8"

Height (mm): 17

Height (in): 11/16"

Light Distribution: Indirect

Weight (kg): 0.3

Weight (lbs): 0.66

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W

Lamp Type: LED (Zhaga Standard)

Input Wattage (W): 5.1

Total Output Wattage (W): 4.6

Dimming: Non-Dimmable

Driver Included: No

Driver Location: Remote

Driver Type: Constant Voltage - 120/277Vac

Driver Class: Class 2

Input Voltage (V): 48

Constant Current (mA): 96

Upon Request: DALI

LED

Delivered Lumen Range: 100 - 499 lm

Color Temperature (°K): 2700

Max. Delivered Lumen (lm): 400

Nominal Lumen (lm): 400

CRI: >90 CRI

Lamp Life (hrs): 50000


OPTICAL

Beam Angle: 180

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A380760-

DESCRIPTION

Disq Square for Minimal Track Surface, LED (Zhaga Standard):
 5.1W LED (Zhaga Standard) - 2700K - 400lm - 48V (DALI DIM
 Only) - DiBond Cover

GENERAL

Series: Disq Square _____
 Brand: Prolight _____
 Division: Architectural _____
 Mounting Type: Track _____
 Mounting Location: Ceiling _____
 Subcategory: Modular _____

PHYSICAL

Shape: Round _____
 Length (mm): 216 _____
 Length (in): 8 ½ _____
 Width (mm): 216 _____
 Width (in): 8 ½ _____
 Height (mm): 17 _____
 Height (in): 11/16 _____
 Light Distribution: Indirect _____
 Weight (kg): 0.307 _____
 Weight (lbs): 0.677 _____
 Fixture Finish: COP / MIR / SST _____
 Fixture Material: Aluminum _____

ELECTRICAL

Input Wattage Range: 1 - 9 W _____
 Lamp Type: LED (Zhaga Standard) _____
 Input Wattage (W): 5.1 _____
 Total Output Wattage (W): 4.6 _____
 Dimming: Non-Dimmable _____
 Driver Included: No _____
 Driver Location: Remote _____
 Driver Type: Constant Voltage - 120/277Vac _____
 Driver Class: Class 2 _____
 Input Voltage (V): 48 _____
 Constant Current (MA): 96 _____
 Upon Request: DALI _____

LED



Delivered Lumen Range: 100 - 499 lm _____
 Color Temperature (°K): 2700 _____
 Max. Delivered Lumen (lm): 400 _____
 Nominal Lumen (lm): 400 _____
 CRI: >90 CRI _____
 Lamp Life (hrs): 50000 _____

OPTICAL

Beam Angle: 180 _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A380761-

DESCRIPTION

Disq Square for Minimal Track Surface, LED (Zhaga Standard):
5.1W LED (Zhaga Standard) - 2700K - 400lm - 48V (DALI DIM Only) - Powder Coat Colors

GENERAL

Series: Disq Square
Brand: Prolicht
Division: Architectural
Mounting Type: Track
Mounting Location: Ceiling
Subcategory: Modular

PHYSICAL

Shape: Round
Length (mm): 216
Length (in): 8 1/2
Width (mm): 216
Width (in): 8 1/2
Height (mm): 17
Height (in): 11/16
Light Distribution: Indirect
Weight (kg): 0.4
Weight (lbs): 0.88
Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
Lamp Type: LED (Zhaga Standard)
Input Wattage (W): 5.1
Total Output Wattage (W): 4.6
Dimming: Non-Dimmable
Driver Included: No
Driver Location: Remote
Driver Type: Constant Voltage - 120/277Vac
Driver Class: Class 2
Input Voltage (V): 48
Constant Current (MA): 96
Upon Request: DALI

LED


Delivered Lumen Range: 100 - 499 lm
Color Temperature (°K): 2700
Max. Delivered Lumen (lm): 400
Nominal Lumen (lm): 400
CRI: >90 CRI
Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 180

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS SURFACE

A3T141-

DESCRIPTION

Minimal Track - Profile - 1000mm / 2000mm / 3000mm -
 Aluminum Profile - Black or White

GENERAL


Series: Minimal Track _____
 Brand: Prolicht _____
 Division: Architectural _____
 Mounting Type: Surface _____
 Mounting Location: Wall / Ceiling _____
 Subcategory: Profile _____

PHYSICAL

Shape: Rectangle _____
 Length (mm): 1000 / 2000 / 3000 _____
 Length (in): 39 ³/₈ _____
 Width (mm): 19 _____
 Width (in): 3/4 _____
 Height (mm): 10 _____
 Height (in): 3/8 _____
 Fixture Finish: BLK / WHI _____
 Fixture Material: Aluminum _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T142-

DESCRIPTION

Minimal Track Wall / Ceiling Cable Loop

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Diameter (mm): 17

Diameter (in): 11/16

Height (mm): 30

Height (in): 1 3/16

Weight (kg): 0.01

Weight (lbs): 0.022

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum


OPTICAL

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T143-

DESCRIPTION

Minimal Track Suspended Cable Roller

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Diameter (mm): 17

Diameter (in): 11/16

Height (mm): 75

Height (in): 2 ¹⁵/₁₆

Weight (kg): 0.02

Weight (lbs): 0.044

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum


OPTICAL

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



75mm 2 ¹⁵/₁₆"

Ø17mm 1 ¹/₁₆"



A3MINTRK-SUR-SYS COMPONENTS

A3T151-

DESCRIPTION

Minimal Track - Driver Box for End Feed - 48Vdc - Max 96W - Non-dimming - 120/277Vac

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

PHYSICAL

Shape: Rectangle

Length (mm): 240

Length (in): 9 ⁷/₁₆

Width (mm): 70

Width (in): 2 ³/₄

Height (mm): 32

Height (in): 1 ¹/₄

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED (Zhaga Standard)

Total Output Wattage (W): 96

Dimming: Non-Dimmable

Driver Included: Yes

Driver Type: Constant Voltage - Universal

Driver Class: Class 2



Input Voltage (V): 120 - 277

Output Voltage (V): 48

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS

A3T152-

DESCRIPTION

Minimal Track - Driver Box for Central Feed - 48Vdc - Max 96W - Non-dimming - 120/277Vac

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural

PHYSICAL



Shape: Rectangle
 Length (mm): 240
 Length (in): 9 7/16
 Width (mm): 70
 Width (in): 2 3/4
 Height (mm): 32
 Height (in): 1 1/4
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED (Zhaga Standard)
 Total Output Wattage (W): 96
 Dimming: Non-Dimmable
 Driver Included: Yes
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 120 - 277
 Output Voltage (V): 48

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS

A3T153

DESCRIPTION

Minimal Track - Remote InstalLED (Zhaga Standard) Dali-Driver - 48Vdc - max 96W

GENERAL

Series: Minimal Track
 Brand: Prolicht
 Division: Architectural

PHYSICAL

Length (mm): 252
 Length (in): 9 ¹⁵/₁₆
 Width (mm): 28
 Width (in): 1 ¹/₈
 Height (mm): 20
 Height (in): 13/16
 Fixture Material: Aluminum

ELECTRICAL



Lamp Type: LED (Zhaga Standard)
 Total Output Wattage (W): 96
 Dimming: Dali Dimming
 Driver Included: Yes
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 120 - 277
 Output Voltage (V): 48

LED

Lamp Life (hrs): 50000

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T188-

DESCRIPTION

Minimal Track / Code System - Curved Track Ø=800mm / 45° - Black

GENERAL



Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling

PHYSICAL

Shape: Curves
 Diameter (mm): 800
 Diameter (in): 31 1/2
 Length (mm): 285
 Length (in): 11 1/4
 Width (mm): 130
 Width (in): 5 1/8
 Height (mm): 10
 Height (in): 3/8
 Weight (kg): 0.141
 Weight (lbs): 0.022
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T189-

DESCRIPTION

Minimal Track / Code System - Curved Track Ø=1600mm / 45°

GENERAL


Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling

PHYSICAL

Shape: Curves
 Diameter (mm): 1600
 Diameter (in): 63
 Length (mm): 740
 Length (in): 29 1/8
 Width (mm): 320
 Width (in): 12 5/8
 Height (mm): 10
 Height (in): 3/8
 Weight (kg): 0.237
 Weight (lbs): 0.037
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T190-

DESCRIPTION

Minimal Track / Code System - Curved Track Connector -
 Ø=400mm / 15 3/4" - 90°

GENERAL


Series: Minimal Track _____
 Brand: Prolicht _____
 Division: Architectural _____
 Mounting Type: Track _____
 Mounting Location: Ceiling _____

PHYSICAL

Shape: Curves _____
 Diameter (mm): 400 _____
 Diameter (in): 15 3/4 _____
 Length (mm): 200 _____
 Length (in): 7 7/8 _____
 Width (mm): 200 _____
 Width (in): 7 7/8 _____
 Height (mm): 10 _____
 Height (in): 3/8 _____
 Weight (kg): 0.135 _____
 Weight (lbs): 0.021 _____
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG /
 MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH /
 GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR _____
 Fixture Material: Aluminum _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



PROJECT
TYPE
NOTES
QUANTITY
DATE

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T191-

DESCRIPTION

Minimal Track - Curved Track Ø=1600mm / 90°

GENERAL


Series: Minimal Track
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling

PHYSICAL

Shape: Curves
 Diameter (mm): 1600
 Diameter (in): 63
 Length (mm): 100
 Length (in): 3 ¹⁵/₁₆
 Width (mm): 100
 Width (in): 3 ¹⁵/₁₆
 Height (mm): 10
 Height (in): 3/8
 Weight (kg): 0.332
 Weight (lbs): 0.052
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T192-

DESCRIPTION

Minimal Track - Curved Track Ø=1600mm / 180°

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

PHYSICAL

Shape: Curves

Diameter (mm): 1600

Diameter (in): 63

Length (mm): 1600

Length (in): 63

Width (mm): 900

Width (in): 35 ⁷/₁₆

Height (mm): 10

Height (in): 3/8

Weight (kg): 0.522

Weight (lbs): 0.082


Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T193-

DESCRIPTION

Minimal Track - X-Connector

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

PHYSICAL

Length (mm): 160

Length (in): 6 ⁵/₁₆

Width (mm): 160

Width (in): 6 ⁵/₁₆

Height (mm): 10

Height (in): 3/8

Weight (kg): 0.15

Weight (lbs): 0.33


Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T194-

DESCRIPTION

Minimal Track - T-Connector

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

PHYSICAL

Length (mm): 160

Length (in): 6 ⁵/₁₆

Width (mm): 89

Width (in): 3 ¹/₂

Height (mm): 10

Height (in): 3/8

Weight (kg): 0.1

Weight (lbs): 0.22


Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS

A3T256-

DESCRIPTION

Minimal Track - Driver Box for End Feed - 48Vdc - Max 96W - Dali dimming - 120/277Vac

GENERAL

Series: Minimal Track _____
 Brand: Prolicht _____
 Division: Architectural _____

PHYSICAL



Shape: Rectangle _____
 Length (mm): 240 _____
 Length (in): 9 ⁷/₁₆ _____
 Width (mm): 70 _____
 Width (in): 2 ³/₄ _____
 Height (mm): 32 _____
 Height (in): 1 ¹/₄ _____
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR _____
 Fixture Material: Aluminum _____

ELECTRICAL

Lamp Type: LED (Zhaga Standard) _____
 Total Output Wattage (W): 96 _____
 Dimming: Non-Dimmable _____
 Driver Included: Yes _____
 Driver Type: Constant Voltage - Universal _____
 Driver Class: Class 2 _____
 Input Voltage (V): 120 - 277 _____
 Output Voltage (V): 48 _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
 IP rating: IP20 _____



PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

A3MINTRK-SUR-SYS COMPONENTS

A3T257-

DESCRIPTION

Minimal Track - Driver Box for Central Feed - 48Vdc - Max 96W -
Dali dimming - 120/277Vac

GENERAL

Series: Minimal Track _____
Brand: Prolicht _____
Division: Architectural _____

PHYSICAL



Shape: Rectangle _____
Length (mm): 240 _____
Length (in): 9 ⁷/₁₆ _____
Width (mm): 70 _____
Width (in): 2 ³/₄ _____
Height (mm): 32 _____
Height (in): 1 ¹/₄ _____
Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG /
MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH /
GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR _____
Fixture Material: Aluminum _____

ELECTRICAL

Lamp Type: LED (Zhaga Standard) _____
Total Output Wattage (W): 96 _____
Dimming: Dali Dimming _____
Driver Included: Yes _____
Driver Type: Constant Voltage - Universal _____
Driver Class: Class 2 _____
Input Voltage (V): 120 - 277 _____
Output Voltage (V): 48 _____

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards _____
IP rating: IP20 _____



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T288-

DESCRIPTION

Imagine Micro Track Spot for Minimal Track / The Code System - Ø23mm / 7/8" - 6W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Optics: 18° / 22° - Dimmable

GENERAL

Series: Imagine
 Brand: Prolicht
 Division: Architectural
 Mounting Type: Track
 Mounting Location: Ceiling
 Subcategory: Modular

PHYSICAL

Shape: Cylinder
 Diameter (mm): 35
 Diameter (in): 1 3/8
 Height (mm): 105
 Height (in): 4 1/8
 Light Distribution: Adjustable / Direct
 Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
 Holder Finish: WHI / BLK
 Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 1 - 9 W
 Lamp Type: LED (Zhaga Standard)
 Input Wattage (W): 6
 Total Output Wattage (W): 5.4
 Dimming: 0-10V / DALI Dimming
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 48

LED


Delivered Lumen Range: 100 - 499 lm
 Color Temperature (°K): 2700 / 3000 / 3500 / 4000
 Max. Delivered Lumen (lm): 110 / 119 / 124 / 127
 Nominal Lumen (lm): 372 / 399 / 418 / 427
 CRI: >90 CRI
 Lamp Life (hrs): 80000

OPTICAL

Optic°: 14
 Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T323-

DESCRIPTION

Minimal Track cable loop

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Diameter (mm): 17

Diameter (in): 11/16

Height (mm): 25

Height (in): 1

Weight (kg): 0.011

Weight (lbs): 0.024

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum


OPTICAL

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T324-

DESCRIPTION

Minimal Track Cable Roller

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

Subcategory: Modular

PHYSICAL

Diameter (mm): 17

Diameter (in): 11/16

Height (mm): 77

Height (in): 3 1/16

Weight (kg): 0.029

Weight (lbs): 0.064

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

OPTICAL

Adjustability: Fixed

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



77mm 3 1/16"

Ø17mm 1 1/16"



A3MINTRK-SUR-SYS COMPONENTS TRACK

A3T325-

DESCRIPTION

Minimal Track - Suspended Cable Roller

GENERAL

Series: Minimal Track

Brand: Prolicht

Division: Architectural

Mounting Type: Track

Mounting Location: Ceiling

PHYSICAL

Diameter (mm): 17

Diameter (in): 11/16

Height (mm): 80

Height (in): 3 1/8

Weight (kg): 0.032

Weight (lbs): 0.005


Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards











IP rating: IP20



LEGEND

 floor-mounted	 pivotable	 special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
 wall and ceiling: recessed and surface mounted	 rotating	 warm dim / natural dimming LED
 ceiling-mounted and wall-mounted	 illuminate tilted	 rechargeable battery powered
 wall-mounted	 color of suspension cable	 fixture with natural vivid LED (upon request)
 omni-directional light distribution	 length of suspension cable	 color rendering index
 direct light distribution	 reflector degree selection	 color temperature
 direct/indirect light distribution	 super spot	 lumen (luminous flux)
 indirect light distribution	 lens	 efficacy (lumens per watt)
 asymmetric light distribution	 lens pack	 Unified Glare Rating (UGR) range from 5-40
 aura light distribution	 shine ring	 marine grade (AISI 316 stainless steel)
 round wall or ceiling cut-out	 integrated shine ring with diffuser	 walk on
 square wall or ceiling cut-out	 free individual colors 01-29	 drive on
 the supplied jig specifies the cutout dimensions	 individual colors: 00 (free of charge), 01-25 (extra charge)	 Dark Sky Compliance
 minimum distance (meters) lamp - object	 luminaire part to be colored (F1)	 Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
 recessed depth	 luminaire part to be colored (F2)	 lamp protected against explosion
 ceiling thickness in mm	 luminaire part to be colored (F3)	 blown glass using traditional methods by master glass blower
 ceiling thickness selection	 luminaire part to be colored (F4)	 acoustic material
 dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)	 luminaire part to be colored (F5)	 protection class I, protection insulation
 included or excluded LED driver/transformer/control gear	 color of 3-circuit adaptor	 protection class II, protection insulation
 separately switchable	 indirect diffuser	 ETL Certified to UL and CSA Standards
 sensor	 direct diffuser	 UL Certified to UL and CSA Standards
 remote control	 ball-proof (upon request)	 CSA Certified to UL and CSA Standards
 available upon request	 accessory	 Certified for North American Standards

IP RATING

 IP20	protected against ingress of solid bodies greater than 12.5mm (finger)
 IP33	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
 IP40	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
 IP43	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
 IP44	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
 IP54	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
 IP65	protected against ingress of dust protected against jets of water
 IP66	protected against ingress of dust protected against powerful jets of water or heavy seas
 IP67	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
 IP68	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

 IK01	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
 IK02	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
 IK03	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
 IK04	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
 IK05	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
 IK06	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
 IK07	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
 IK08	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
 IK09	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
 IK10	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)