

A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR1110-

DESCRIPTION

Track - End Feed (Right) 2-Circuit

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Length (mm): 148

Length (in): 5 13/16

Width (mm): 32

Width (in): 1 1/4

Height (mm): 38

Height (in): 1 1/2


Fixture Finish: WHI / BLK

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR121-

DESCRIPTION

Track - End Feed (Left) 2-Circuit

GENERAL


Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 148
Length (in): 5 13/16
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR141-

DESCRIPTION

Track - Central Feed 2-Circuit

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 254
Length (in): 10
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 5/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR2100-

DESCRIPTION

Track - Straight Connector

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 115
Length (in): 4 1/2
Width (mm): 26
Width (in): 1
Height (mm): 33
Height (in): 1 5/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

STR2300-

DESCRIPTION

Track - Flexible Connector 2-Circuit

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Length (mm): 370

Length (in): 14 9/16"

Width (mm): 32

Width (in): 1 1/4"

Height (mm): 38

Height (in): 1 5/16"

Fixture Finish: WHI / BLK



Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR3400-

DESCRIPTION

Track - L-Connector 2-Circuit , Outside Corner (Feedable)

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 143
Length (in): 5 5/8
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR3500-

DESCRIPTION

Track - L-Connector 2-Circuit , Inside Corner (Feedable)

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 143
Length (in): 5 5/8
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR380-

DESCRIPTION

Track - X-Connector 2-Circuit (Feedable)

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 148
Length (in): 5 13/16
Width (mm): 148
Width (in): 5 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR3900-

DESCRIPTION

Track - T-Connector (Left) 2-Circuit , Outside Corner (Feedable)

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 254
Length (in): 10
Width (mm): 143
Width (in): 5 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR40001-

DESCRIPTION

Track - T-Connector (Right) 2-Circuit , Outside Corner (Feedable)

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 254
Length (in): 10
Width (mm): 143
Width (in): 5 5/8
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

STR510-

DESCRIPTION

Track - Suspension Cable Kit 1 - Screw gripper + steel cable (diameter 1,5 mm) + clamp with automatic gripper

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR512-

DESCRIPTION

Track - Ceiling Mounting Bracket

GENERAL


Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 40
Length (in): 1 9/16
Width (mm): 24
Width (in): 15/16
Height (mm): 14
Height (in): 9/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

STR521-

DESCRIPTION

Track - Stem and canopy kit 1000mm

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Fixture Finish: WHI / BLK


Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3T048- COMPONENTS TRACK

STR9001R-

DESCRIPTION

Track - End Feed Cover

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Length (mm): 95

Length (in): 3 3/4

Width (mm): 52

Width (in): 2 1/16

Height (mm): 34

Height (in): 1 5/16



Fixture Finish: WHI / BLK

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR9010R-

DESCRIPTION


Track - Central Feed Cover

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 148
Length (in): 5 13/16
Width (mm): 52
Width (in): 2 1/16
Height (mm): 34
Height (in): 1 5/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum



A3T048- COMPONENTS TRACK

STR9011R-

DESCRIPTION

Track - L-Connector Cover

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Length (mm): 100

Length (in): 3 15/16

Width (mm): 100

Width (in): 3 15/16


Height (mm): 34

Height (in): 1 5/16

Fixture Finish: WHI / BLK

Fixture Material: Aluminum

PROJECT
TYPE
NOTES
QUANTITY
DATE



A3T048- COMPONENTS TRACK

STR9013R-

DESCRIPTION



Track - T-Connector Cover

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 148
Length (in): 5 13/16
Width (mm): 100
Width (in): 3 15/16
Height (mm): 34
Height (in): 1 5/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STR9017R-

DESCRIPTION



Track - Cover Cross Connector

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Length (mm): 148
Length (in): 5 13/16
Width (mm): 148
Width (in): 5 13/16
Height (mm): 34
Height (in): 1 5/16
Fixture Finish: WHI / BLK
Fixture Material: Aluminum



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STRR4100-

DESCRIPTION

Track - Recessed - End Cap

GENERAL



Partner: Prolicht
Division: Architectural
Installation: Surface

PHYSICAL

Length (mm): 32
Length (in): 1 ¼
Width (mm): 32
Width (in): 1 ¼
Height (mm): 38
Height (in): 1 ½
Fixture Finish: WHI / BLK / GRY
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STRR4400-

DESCRIPTION

Track - 4' Recessed Track 3-Circuit - 120V

GENERAL

Partner: Prolight

Division: Architectural

Installation: Track

PHYSICAL

Shape: Rectangle

Length (mm): 1219

Length (in): 48

Width (mm): 32

Width (in): 1 1/4

Height (mm): 38

Height (in): 1 1/2


Fixture Finish: WHI / BLK / GRY

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STRR4800-

DESCRIPTION

Track - 8' Recessed Track 3-Circuit - 120V

GENERAL


Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL

Shape: Rectangle
Length (mm): 2438
Length (in): 96
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / GRY
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS SURFACE

STRS4100-

DESCRIPTION

Track - Surface - End Cap

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Surface

PHYSICAL

Length (mm): 32

Length (in): 1 1/4

Width (mm): 32

Width (in): 1 1/4

Height (mm): 38

Height (in): 1 1/2

Fixture Finish: WHI / BLK / GRY



Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A3T048- COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STRS4400-

DESCRIPTION

Track - 4' Surface Mount 3-Circuit Track - 120V

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL


Shape: Rectangle
Length (mm): 1219
Length (in): 48
Width (mm): 32
Width (in): 1 1/4
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / GRY
Fixture Material: Aluminum

ELECTRICAL

Driver Included: No

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A3T048- COMPONENTS TRACK

PROJECT
TYPE
NOTES
QUANTITY
DATE

STRS4800-

DESCRIPTION

Track - 8' Surface Mount 3-Circuit Track - 120V

GENERAL

Partner: Prolicht
Division: Architectural
Installation: Track

PHYSICAL


Shape: Rectangle
Length (mm): 2438
Length (in): 96"
Width (mm): 32
Width (in): 1 1/4"
Height (mm): 38
Height (in): 1 1/2"
Fixture Finish: WHI / BLK / GRY
Fixture Material: Aluminum

ELECTRICAL

Driver Included: No

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

STRV120

DESCRIPTION

Cutting Tool for Track Conductors

GENERAL

Partner: Prolicht

Division: Architectural

Installation: Track

PHYSICAL

Length (mm): 245

Length (in): 9 5/8

Height (mm): 58

Height (in): 2 5/16

Fixture Material: Aluminum


ELECTRICAL

Driver Included: No

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)