

## A7LEVEL-MOD-SYS COMPONENTS

### A7900052-

#### DESCRIPTION

Level LED Strip - 5.000mm / 196 7/8" - 65W - 2700K / 3000K - 48V

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Width (mm): 10  
 Width (in): 3/8  
 Weight (kg): 0.95  
 Weight (lbs): 2.09  
 Fixture Material: Aluminum

#### ELECTRICAL


Total Output Wattage (W): 65W (13W/m)

#### LED

Color Temperature (°K): 2700 / 3000  
 Nominal Lumen (lm): 7150 / 7550 (1430/m / 1510/m)

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS

### A7900053-

#### DESCRIPTION

Level LED Strip - 10.000mm / 393 11/16" - 130W - 2700K / 3000K - 48V

#### GENERAL

Series: Level \_\_\_\_\_  
 Brand: Letroh \_\_\_\_\_  
 Division: Architectural \_\_\_\_\_  
 Subcategory: Profile \_\_\_\_\_

#### PHYSICAL

Shape: Rectangle \_\_\_\_\_  
 Length (mm): 10000 \_\_\_\_\_  
 Length (in): 393 11/16 \_\_\_\_\_  
 Width (mm): 10 \_\_\_\_\_  
 Width (in): 3/8 \_\_\_\_\_  
 Weight (kg): 0.75 \_\_\_\_\_  
 Weight (lbs): 1.65 \_\_\_\_\_  
 Fixture Material: Aluminum \_\_\_\_\_

#### ELECTRICAL


Total Output Wattage (W): 130W (13W/m) \_\_\_\_\_

#### LED

Color Temperature (°K): 2700 / 3000 \_\_\_\_\_  
 Nominal Lumen (lm): 14300 / 15100 (1430/m / 1510/m) \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_  
 IP rating: IP20 \_\_\_\_\_



## A7LEVEL-MOD-SYS COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	


### A7900054-

**DESCRIPTION**  
Level - Power feed - 2500mm

**GENERAL**  
Series: Level  
Brand: Letroh  
Division: Architectural  
Subcategory: Profile

**PHYSICAL**  
Shape: Rectangle  
Diameter (mm): 100  
Diameter (in): 3 <sup>15</sup>/<sub>16</sub>  
Height (mm): 33  
Height (in): 1 <sup>3</sup>/<sub>16</sub>  
Max. Overall Height (mm): 2533  
Max. Overall Height (in): 99 <sup>3</sup>/<sub>4</sub>  
Fixture Finish: WHI / BLK  
Fixture Material: Aluminum

**RATINGS AND CERTIFICATIONS**  
Certified By: Certified for North American Standards  
IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS

### A7900055-

#### DESCRIPTION

Level - Cube Wall fixing

#### GENERAL


Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 80  
 Length (in): 3 1/8  
 Width (mm): 242  
 Width (in): 9 1/2  
 Height (mm): 80  
 Height (in): 3 1/8  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS

### A7900056-

#### DESCRIPTION

Level - Cube ceiling fixing

#### GENERAL


Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 80  
 Length (in): 3 1/8"  
 Width (mm): 242  
 Width (in): 9 1/2"  
 Height (mm): 80  
 Height (in): 3 1/8"  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A7LEVEL-MOD-SYS COMPONENTS

### A7900057-

#### DESCRIPTION

Level - Ceiling Spacer

#### GENERAL


Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 80  
 Length (in): 3 1/8  
 Width (mm): 80  
 Width (in): 3 1/8  
 Height (mm): 263  
 Height (in): 10 3/8  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS

### A7900058-

#### DESCRIPTION

Level - Mini - Lens - 20° / 40° / 60°

#### GENERAL

Series: Level

Brand: Letroh

Division: Architectural

#### OPTICAL

Optic°: 20 / 40 / 60

Adjustability: Fixed

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS SURFACE


### A7T00027-

**DESCRIPTION**  
 Level Cable - 5000mm / 196 7/8"

**GENERAL**  
 Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Surface  
 Mounting Location: Wall / Ceiling  
 Subcategory: Profile

**PHYSICAL**  
 Shape: Rectangle  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Width (mm): 33  
 Width (in): 1 5/16  
 Height (mm): 4  
 Height (in): 3/16  
 Light Distribution: Downlight  
 Weight (kg): 0.95  
 Weight (lbs): 2.09  
 Fixture Finish: TRA / BLK / WHI  
 Fixture Material: Aluminum

**RATINGS AND CERTIFICATIONS**  
 Certified By: Certified for North American Standards  
 IP rating: IP20





## A7LEVEL-MOD-SYS COMPONENTS SURFACE

### A7T00028-

#### DESCRIPTION

Level Cable - 10,000mm / 393 11/16"

#### GENERAL


Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Surface  
 Mounting Location: Wall / Ceiling  
 Subcategory: Profile

#### PHYSICAL

Shape: Rectangle  
 Length (mm): 10000  
 Length (in): 393 11/16  
 Width (mm): 33  
 Width (in): 1 5/16  
 Height (mm): 4  
 Height (in): 3/16  
 Light Distribution: Downlight  
 Weight (kg): 0.19  
 Weight (lbs): 0.42  
 Fixture Finish: TRA / BLK / WHI  
 Fixture Material: Aluminum

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00029-

#### DESCRIPTION

Level - Zoom - Adjustable Spot, 16.5W, 48V, 350mA, CRI 97, Dimmable Converter Included

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Profile

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 85  
 Diameter (in): 3 3/8  
 Height (mm): 130  
 Height (in): 5 1/8  
 Light Distribution: Downlight  
 Weight (kg): 0.33  
 Weight (lbs): 0.73  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED  
 Input Wattage (W): 16.5  
 Total Output Wattage (W): 12.8  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Housing: ENCP50  
 Input Voltage (V): 120 - 277  
 Output Voltage (V): 48  
 Constant Current (MA): 350  
 Upon Request: Dali Dimming

#### LED


Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000  
 Max. Delivered Lumen (lm): 831 / 878  
 Nominal Lumen (lm): 1010 / 1068  
 CRI: >97 CRI  
 Lamp Life (hrs): 50000

#### OPTICAL

Optic°: 12 - 46  
 Adjustability: Tilting and rotating

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00030-

#### DESCRIPTION

Level - Zoom - Fixed Spot, 16.5W, 48V, 350mA, CRI 97, Dimmable Converter Included

#### GENERAL

Series: Level \_\_\_\_\_  
 Brand: Letroh \_\_\_\_\_  
 Division: Architectural \_\_\_\_\_  
 Mounting Type: Track \_\_\_\_\_  
 Mounting Location: Ceiling \_\_\_\_\_  
 Subcategory: Profile \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_  
 Diameter (mm): 85 \_\_\_\_\_  
 Diameter (in): 3 3/8 \_\_\_\_\_  
 Height (mm): 90 \_\_\_\_\_  
 Height (in): 3 9/16 \_\_\_\_\_  
 Light Distribution: Downlight \_\_\_\_\_  
 Weight (kg): 0.33 \_\_\_\_\_  
 Weight (lbs): 0.73 \_\_\_\_\_  
 Fixture Finish: WHI / BLK \_\_\_\_\_  
 Fixture Material: Aluminum \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 10 - 19 W \_\_\_\_\_  
 Lamp Type: LED \_\_\_\_\_  
 Input Wattage (W): 16.5 \_\_\_\_\_  
 Total Output Wattage (W): 12.8 \_\_\_\_\_  
 Dimming: Non-Dimmable / 0-10V Dimming \_\_\_\_\_  
 Driver Included: No \_\_\_\_\_  
 Driver Location: Remote \_\_\_\_\_  
 Driver Type: Constant Voltage - Universal \_\_\_\_\_  
 Driver Class: Class 2 \_\_\_\_\_  
 Housing: ENCP50 \_\_\_\_\_  
 Input Voltage (V): 120 - 277 \_\_\_\_\_  
 Output Voltage (V): 48 \_\_\_\_\_  
 Upon Request: Dali Dimming \_\_\_\_\_

#### LED


Delivered Lumen Range: 500 - 1999 lm \_\_\_\_\_  
 Color Temperature (°K): 2700 / 3000 \_\_\_\_\_  
 Max. Delivered Lumen (lm): 831 / 878 \_\_\_\_\_  
 Nominal Lumen (lm): 1010 / 1068 \_\_\_\_\_  
 CRI: >97 CRI \_\_\_\_\_  
 Lamp Life (hrs): 50000 \_\_\_\_\_

#### OPTICAL

Optic°: 12 - 46 \_\_\_\_\_  
 Adjustability: Fixed \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_  
 IP rating: IP20 \_\_\_\_\_



## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00031-

#### DESCRIPTION

Level - Zoom - Suspension, 16.5W, 48V, 350mA, CRI 97,  
 Dimmable Converted Included

#### GENERAL

Series: Level \_\_\_\_\_  
 Brand: Letroh \_\_\_\_\_  
 Division: Architectural \_\_\_\_\_  
 Mounting Type: Track \_\_\_\_\_  
 Mounting Location: Ceiling \_\_\_\_\_  
 Subcategory: Spots \_\_\_\_\_

#### PHYSICAL

Shape: Cylinder \_\_\_\_\_  
 Diameter (mm): 85 \_\_\_\_\_  
 Diameter (in): 3 3/8 \_\_\_\_\_  
 Height (mm): 75 \_\_\_\_\_  
 Height (in): 2 15/16 \_\_\_\_\_  
 Max. Overall Height (mm): 2075 \_\_\_\_\_  
 Max. Overall Height (in): 81 11/16 \_\_\_\_\_  
 Light Distribution: Downlight \_\_\_\_\_  
 Weight (kg): 0.42 \_\_\_\_\_  
 Weight (lbs): 0.93 \_\_\_\_\_  
 Fixture Finish: WHI / BLK \_\_\_\_\_  
 Fixture Material: Aluminum \_\_\_\_\_

#### ELECTRICAL

Input Wattage Range: 10 - 19 W \_\_\_\_\_  
 Lamp Type: LED \_\_\_\_\_  
 Input Wattage (W): 16.5 \_\_\_\_\_  
 Total Output Wattage (W): 12.8 \_\_\_\_\_  
 Dimming: Non-Dimmable / 0-10V Dimming \_\_\_\_\_  
 Driver Included: No \_\_\_\_\_  
 Driver Location: Remote \_\_\_\_\_  
 Driver Type: Constant Voltage - Universal \_\_\_\_\_  
 Driver Class: Class 2 \_\_\_\_\_  
 Housing: ENCP50 \_\_\_\_\_  
 Input Voltage (V): 120 - 277 \_\_\_\_\_  
 Output Voltage (V): 48 \_\_\_\_\_  
 Upon Request: Dali Dimming \_\_\_\_\_

#### LED


Delivered Lumen Range: 500 - 1999 lm \_\_\_\_\_  
 Color Temperature (°K): 2700 / 3000 \_\_\_\_\_  
 Max. Delivered Lumen (lm): 831 / 878 \_\_\_\_\_  
 Nominal Lumen (lm): 1010 / 1068 \_\_\_\_\_  
 CRI: >97 CRI \_\_\_\_\_  
 Lamp Life (hrs): 50000 \_\_\_\_\_

#### OPTICAL

Optic°: 12 - 46 \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_  
 IP rating: IP20 \_\_\_\_\_



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00032-

#### DESCRIPTION

Level - Mini - Adjustable Spot 11.2W, 48V, 250mA, CRI 97

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Spots

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 45  
 Diameter (in): 1 3/4  
 Height (mm): 109  
 Height (in): 4 5/16  
 Light Distribution: Downlight  
 Weight (kg): 0.12  
 Weight (lbs): 0.26  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### ELECTRICAL


Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 11.2  
 Bulb Included: Bulb Included  
 Total Output Wattage (W): 7.8  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Housing: ENCP50  
 Input Voltage (V): 120 - 277  
 Output Voltage (V): 48  
 Upon Request: Dali Dimming

#### LED

Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000  
 Max. Delivered Lumen (lm): 728 / 770  
 CRI: >97 CRI  
 Lamp Life (hrs): 50000

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00033-

#### DESCRIPTION

Level - Mini - Fixed Spot 11.2W, 48V, 250mA, CRI 97

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Spots

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 45  
 Diameter (in): 1 3/4  
 Height (mm): 69  
 Height (in): 2 11/16  
 Light Distribution: Downlight  
 Weight (kg): 0.12  
 Weight (lbs): 0.26  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### ELECTRICAL

Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 11.2  
 Total Output Wattage (W): 7.8  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Housing: ENCP50  
 Input Voltage (V): 120 - 277  
 Output Voltage (V): 48  
 Upon Request: Dali Dimming

#### LED


Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000  
 Max. Delivered Lumen (lm): 728 / 770  
 CRI: >97 CRI  
 Lamp Life (hrs): 50000

#### OPTICAL

Adjustability: Fixed

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## A7LEVEL-MOD-SYS COMPONENTS TRACK

### A7T00034-

#### DESCRIPTION

Level - Mini - Fixed Spot Diffuser - 11.2W, 48V, 250mA, CRI 97

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Spots

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 45  
 Diameter (in): 1 3/4  
 Height (mm): 69  
 Height (in): 2 11/16  
 Light Distribution: Downlight  
 Weight (kg): 0.11  
 Weight (lbs): 0.24  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### ELECTRICAL


Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 11.2  
 Total Output Wattage (W): 7.8  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Housing: ENCP50  
 Input Voltage (V): 120 - 277  
 Output Voltage (V): 48  
 Upon Request: Dali Dimming

#### LED

Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000  
 Max. Delivered Lumen (lm): 728 / 770  
 CRI: >97 CRI  
 Lamp Life (hrs): 50000

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20



## A7LEVEL-MOD-SYS COMPONENTS TRACK

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### A7T00035-

#### DESCRIPTION

Level - Mini - Suspension Spot - 11.2W, 48V, 250mA, CRI 97

#### GENERAL

Series: Level  
 Brand: Letroh  
 Division: Architectural  
 Mounting Type: Track  
 Mounting Location: Ceiling  
 Subcategory: Spots

#### PHYSICAL

Shape: Cylinder  
 Diameter (mm): 45  
 Diameter (in): 1 3/4  
 Height (mm): 69  
 Height (in): 2 11/16  
 Max. Overall Height (mm): 2069  
 Max. Overall Height (in): 81 7/16  
 Light Distribution: Downlight  
 Weight (kg): 0.23  
 Weight (lbs): 0.51  
 Fixture Finish: WHI / BLK  
 Fixture Material: Aluminum

#### ELECTRICAL


Input Wattage Range: 10 - 19 W  
 Lamp Type: LED (Zhaga Standard)  
 Input Wattage (W): 11.2  
 Total Output Wattage (W): 7.8  
 Dimming: Non-Dimmable / 0-10V Dimming  
 Driver Included: No  
 Driver Location: Remote  
 Driver Type: Constant Voltage - Universal  
 Driver Class: Class 2  
 Housing: ENCP50  
 Input Voltage (V): 120 - 277  
 Output Voltage (V): 48  
 Upon Request: Dali Dimming

#### LED

Delivered Lumen Range: 500 - 1999 lm  
 Color Temperature (°K): 2700 / 3000  
 Max. Delivered Lumen (lm): 728 / 770  
 CRI: >97 CRI  
 Lamp Life (hrs): 50000

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP20





## A7LEVEL-MOD-SYS COMPONENTS

### DND1000048TLC

#### DESCRIPTION

Tridonic - LC 48V 100W DC-STR UNV FO Ip - 120-277Vac - 48Vdc - 96W - Non-dimming driver -Used with ENCP7 -Available with IP68 – Outdoor Rated – Enclosure TBD

#### GENERAL

Division: Architectural : Components

#### PHYSICAL

Length (mm): 425

Length (in): 16 <sup>3</sup>/<sub>4</sub>

Width (mm): 30

Width (in): 1 <sup>1</sup>/<sub>16</sub>

Height (mm): 21

Height (in): 13/16

Weight (kg): 0.756

Fixture Material: Metal

#### ELECTRICAL

Lamp Type: LED

Input Wattage (W): Max. 106

Total Output Wattage (W): 100

Dimming: Non-Dimmable

Driver Type: Constant Voltage - Universal


Driver Class: Class 2

Input Voltage (V): 120 - 277

Constant Voltage (V): 48Vdc

#### RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards



PROJECT
TYPE
NOTES
QUANTITY
DATE

## A7LEVEL-MOD-SYS COMPONENTS


### ENCP50

**DESCRIPTION**  
Empty Metal Enclosure for Driver - IP20 - Indoor Rated

**GENERAL**  
Division: Architectural : Components

**PHYSICAL**  
Shape: Rectangle  
Length (mm): 670  
Length (in): 26 <sup>3</sup>/<sub>8</sub>  
Width (mm): 44  
Width (in): 1 <sup>3</sup>/<sub>4</sub>  
Height (mm): 38  
Height (in): 1 <sup>1</sup>/<sub>2</sub>  
Gasket: 1554JGASKET  
Fixture Material: Metal

**RATINGS AND CERTIFICATIONS**  
IP rating: IP20



### LEGEND

 floor-mounted	 pivotable	 special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
 wall and ceiling: recessed and surface mounted	 rotating	 warm dim / natural dimming LED
 ceiling-mounted and wall-mounted	 illuminate tilted	 rechargeable battery powered
 wall-mounted	 color of suspension cable	 fixture with natural vivid LED (upon request)
 omni-directional light distribution	 length of suspension cable	 color rendering index
 direct light distribution	 reflector degree selection	 color temperature
 direct/indirect light distribution	 super spot	 lumen (luminous flux)
 indirect light distribution	 lens	 efficacy (lumens per watt)
 asymmetric light distribution	 lens pack	 Unified Glare Rating (UGR) range from 5-40
 aura light distribution	 shine ring	 marine grade (AISI 316 stainless steel)
 round wall or ceiling cut-out	 integrated shine ring with diffuser	 walk on
 square wall or ceiling cut-out	 free individual colors 01-29	 drive on
 the supplied jig specifies the cutout dimensions	 individual colors: 00 (free of charge), 01-25 (extra charge)	 Dark Sky Compliance
 minimum distance (meters) lamp - object	 luminaire part to be colored (F1)	 Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
 recessed depth	 luminaire part to be colored (F2)	 lamp protected against explosion
 ceiling thickness in mm	 luminaire part to be colored (F3)	 blown glass using traditional methods by master glass blower
 ceiling thickness selection	 luminaire part to be colored (F4)	 acoustic material
 dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)	 luminaire part to be colored (F5)	 protection class I, protection insulation
 included or excluded LED driver/transformer/control gear	 color of 3-circuit adaptor	 protection class II, protection insulation
 separately switchable	 indirect diffuser	 ETL Certified to UL and CSA Standards
 sensor	 direct diffuser	 UL Certified to UL and CSA Standards
 remote control	 ball-proof (upon request)	 CSA Certified to UL and CSA Standards
 available upon request	 accessory	 Certified for North American Standards

### IP RATING

 IP20	protected against ingress of solid bodies greater than 12.5mm (finger)
 IP33	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
 IP40	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
 IP43	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
 IP44	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
 IP54	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
 IP65	protected against ingress of dust protected against jets of water
 IP66	protected against ingress of dust protected against powerful jets of water or heavy seas
 IP67	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
 IP68	protected against ingress of dust protected against immersion of water under pressure for long periods

### IK RATING

 IK01	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
 IK02	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
 IK03	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
 IK04	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
 IK05	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
 IK06	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
 IK07	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
 IK08	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
 IK09	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
 IK10	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)