

PROJECT
TYPE
NOTES
QUANTITY
DATE

D113034-

DESCRIPTION

Kit Pop-Up - Surface - Wall Holder with fixed 200mm / 7 7/8" arm  
(Shade sold separately)

GENERAL

Series: Kit Pop-Up  
Brand: Ole  
Division: Design  
Mounting Type: Surface  
Mounting Location: Wall

PHYSICAL

Shape: Abstract  
Diameter (mm): 120  
Diameter (in): 4 3/4  
Length (mm): 200  
Length (in): 7 7/8  
Max. Overall Height (mm): 1200  
Max. Overall Height (in): 47 1/4  
Light Distribution: Direct  
Fixture Finish: WHI / MBK  
Fixture Material: Metal

ELECTRICAL


Number of Lamps: 1  
Lamp Type: LED Retrofit  
Lamp Shape: A19  
Bulb Included: Bulb Not Included  
Max. Wattage Per Lamp (W): 15  
Lamp Base: E26  
Input Voltage (V): 120  
Upon Request: 277Vac / GU24

OPTICAL

Adjustability: Rotational 120°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



D11KITPOP-SUR-SYS COMPONENTS SURFACE

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

D113035-

DESCRIPTION

Kit Pop-Up - Surface - Wall Holder with fixed 500mm / 19 11/16" arm (Shade sold separately)

GENERAL

Series: Kit Pop-Up  
Brand: Ole  
Division: Design  
Mounting Type: Surface  
Mounting Location: Wall

PHYSICAL

Shape: Abstract  
Diameter (mm): 140  
Diameter (in): 5 1/2  
Length (mm): 500  
Length (in): 19 11/16  
Max. Overall Height (mm): 1200  
Max. Overall Height (in): 47 1/4  
Light Distribution: Direct  
Fixture Finish: WHI / MBK  
Fixture Material: Metal

ELECTRICAL



Number of Lamps: 1  
Lamp Type: LED Retrofit  
Lamp Shape: A19  
Bulb Included: Bulb Not Included  
Max. Wattage Per Lamp (W): 15  
Lamp Base: E26  
Input Voltage (V): 120  
Upon Request: 277Vac / GU24

OPTICAL

Adjustability: Rotational 120°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



D11KITPOP-SUR-SYS COMPONENTS SURFACE

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

D113036-

DESCRIPTION

Kit Pop-Up - Surface - Wall Holder with fixed 800mm / 31 1/2" arm (Shade sold separately)

GENERAL

Series: Kit Pop-Up  
Brand: Ole  
Division: Design  
Mounting Type: Surface  
Mounting Location: Wall

PHYSICAL

Shape: Abstract  
Diameter (mm): 140  
Diameter (in): 5 1/2  
Length (mm): 800  
Length (in): 31 1/2  
Max. Overall Height (mm): 1200  
Max. Overall Height (in): 47 1/4  
Light Distribution: Direct  
Fixture Finish: WHI / MBK  
Fixture Material: Metal

ELECTRICAL




Number of Lamps: 1  
Lamp Type: LED Retrofit  
Lamp Shape: A19  
Bulb Included: Bulb Not Included  
Max. Wattage Per Lamp (W): 15  
Lamp Base: E26  
Input Voltage (V): 120  
Upon Request: 277Vac / GU24

OPTICAL

Adjustability: Rotational 120°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



D11KITPOP-SUR-SYS COMPONENTS

D119000-

DESCRIPTION

Banyo Shade - 300mm - 80mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 300

Diameter (in): 11 13/16

Height (mm): 200

Height (in): 7 7/8

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI


Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D11KITPOP-SUR-SYS COMPONENTS

D119001-

DESCRIPTION

Drum Shade - 180mm - 80mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 180

Diameter (in): 7 1/16

Height (mm): 250

Height (in): 9 13/16

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI


Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D11KITPOP-SUR-SYS COMPONENTS

D119002-

DESCRIPTION

Drum Shade - 300mm - 50mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 300

Diameter (in): 11 13/16

Height (mm): 200

Height (in): 7 7/8

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI

Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20


PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



Ø270mm 10 5/8"



200mm 7 7/8"



Ø300mm 11 13/16"

D11KITPOP-SUR-SYS COMPONENTS

D119003-

DESCRIPTION

Ukelele Shade - 260mm - 75mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 260

Diameter (in): 10 ¼

Height (mm): 380

Height (in): 14 15/16

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI


Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



D11KITPOP-SUR-SYS COMPONENTS

D119004-

DESCRIPTION

Ukelele Shade - 350mm - 60mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 350

Diameter (in): 13 3/4

Height (mm): 200

Height (in): 7 7/8

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI



Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	





D11KITPOP-SUR-SYS COMPONENTS

D119005-

DESCRIPTION

Kora Shade - 240mm - 55mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 240

Diameter (in): 9 7/16

Height (mm): 380

Height (in): 14 15/16

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI


Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D11KITPOP-SUR-SYS COMPONENTS

D119006-

DESCRIPTION

Kora Shade - 350mm - 60mm Cord

GENERAL

Series: Kit Pop-Up

Brand: Ole

Division: Design

PHYSICAL

Shape: Abstract

Diameter (mm): 350

Diameter (in): 13 3/4

Height (mm): 220

Height (in): 8 11/16

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI


Fixture Material: Fabric Cord / Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



PROJECT
TYPE
NOTES
QUANTITY
DATE

LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)