ZANEEN®

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141207-

DESCRIPTION

Aeron - Suspension - 130mm / 5 1/8" - 1 x Max. W LED Retrofit - E12 - without Canopy

GENERAL

Series: Aeron
Subseries: Aeron Modular System
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 130
Diameter (in): 5 $\frac{1}{8}$
Height (mm): 280
Height (in): 11
Max. Overall Height (mm): 1780
Max. Overall Height (in): 70 $\frac{1}{16}$
Light Distribution: Omnidirectional
Weight (kg): 0.860
Weight (lbs): 1.90
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: Black Rubber Cable

ELECTRICAL

Number of Lamps: 1
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 4
Lamp Base: E12
Input Voltage (V): 120

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

max. 1500mm 59 $\frac{1}{16}$"

280mm 11"

Ø80mm
3 $\frac{1}{8}$"

Ø130mm
5 $\frac{1}{8}$"

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141208-

DESCRIPTION

Aeron - Suspension - 150mm / 13 3/8" - 1 x Max.W LED Retrofit -
E26 - Without Canopy

GENERAL

Series: Aeron
Subseries: Aeron Modular System
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 150
Diameter (in): 5 $\frac{7}{8}$
Height (mm): 340
Height (in): 13 $\frac{3}{8}$
Max. Overall Height (mm): 1830
Max. Overall Height (in): 72 $\frac{1}{16}$
Light Distribution: Omnidirectional
Weight (kg): 1.356
Weight (lbs): 2.99
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: Black Rubber Cable

ELECTRICAL

Number of Lamps: 1
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 8
Lamp Base: E26
Input Voltage (V): 120
Upon Request: GU24 / 277Vac

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

max. 1500mm 59 $\frac{1}{16}$"

340mm 13 $\frac{3}{8}$"

Ø100mm
3 $\frac{15}{16}$"

Ø150mm 5 $\frac{7}{8}$"

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141209-

DESCRIPTION

Aeron - Suspension - 210mm / 8 1/4" - 1 x Max. W LED Retrofit - E26 - With Canopy

GENERAL

Series: Aeron
Subseries: Aeron Modular System
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 210
Diameter (in): 8 $\frac{1}{4}$
Height (mm): 480
Height (in): 18 $\frac{7}{8}$
Max. Overall Height (mm): 1980
Max. Overall Height (in): 77 $\frac{15}{16}$
Light Distribution: Omnidirectional
Weight (kg): 2.800
Weight (lbs): 6.17
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: 1,500mm / 59 1/16" - Black Rubber Cable

ELECTRICAL

Number of Lamps: 1
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 8
Lamp Base: E26
Input Voltage (V): 120
Upon Request: GU24 / 277Vac

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

max. 1500mm 59 1/16"

480mm 18 7/8"

Ø150mm 5 7/8"

Ø210mm 8 1/4"

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141210-

DESCRIPTION

Aeron - Suspension - 280mm / 11" - 1 x Max. W LED Retrofit - E26 - Without Canopy

GENERAL

Series: Aeron
Subseries: Aeron Modular System
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 280
Diameter (in): 11
Height (mm): 550
Height (in): 21 $\frac{5}{8}$
Max. Overall Height (mm): 2050
Max. Overall Height (in): 80 $\frac{11}{16}$
Light Distribution: Omnidirectional
Weight (kg): 3.570
Weight (lbs): 7.87
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: 1,500mm / 59 1/16" - Black Rubber Cable

ELECTRICAL

Number of Lamps: 1
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 8
Lamp Base: E26
Input Voltage (V): 120
Upon Request: GU24 / 277Vac

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

max. 1500mm 59 ⅛"

550mm 21 ⅝"

Ø200mm 7 ⅞"

Ø280mm 11"

(D)

ZANEEN®

PROJECT

TYPE

NOTES

QUANTITY

DATE

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141211-

GENERAL

Series: Aeron
Subseries: Aeron 3 Light Linear
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 130
Diameter (in): 5 $\frac{1}{8}$
Length (mm): 1200
Length (in): 47 $\frac{1}{4}$
Height (mm): 130
Height (in): 5 $\frac{1}{8}$
Max. Overall Height (mm): 1630
Max. Overall Height (in): 63 $\frac{3}{16}$
Light Distribution: Omnidirectional
Weight (kg): 2.800
Weight (lbs): 6.18
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: 1,500mm / 59 1/16" - Black Rubber Cable

ELECTRICAL

Number of Lamps: 3
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 4
Lamp Base: E12
Input Voltage (V): 120

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

Ø125mm 4 $\frac{15}{16}$"

Round cover plate

1200mm 47 $\frac{1}{4}$"

40mm 1 $\frac{9}{16}$"

max. 1500mm 59 $\frac{1}{16}$"

280mm 11"

Ø130mm 5 $\frac{1}{8}$"

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS SUSPENSION

D141212-

GENERAL

Series: Aeron
Subseries: Aeron 3 Light Cluster
Brand: Cangini & Tucci
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Ambient

PHYSICAL

Shape: Cylinder
Diameter (mm): 540
Diameter (in): 21 $\frac{1}{4}$
Height (mm): 210
Height (in): 8 $\frac{1}{4}$
Max. Overall Height (mm): 1710
Max. Overall Height (in): 67 $\frac{5}{16}$
Light Distribution: Omnidirectional
Weight (kg): 6.830
Weight (lbs): 15.06
Fixture Finish: AMB / GRN / PNK / RUB / SKB / SMK / TOB / TRA
Holder Finish: CHR / SGD / SBK
Fixture Material: Glass / Metal
Cable Details: 1,500mm / 59 1/16" - Black Rubber Cable

ELECTRICAL

Number of Lamps: 2 + 1
Lamp Type: LED Retrofit
Bulb Included: Bulb Not Included
Max. Wattage Per Lamp (W): 8 + 4
Lamp Base: E26 + E12
Input Voltage (V): 120

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149000-

<table>
<tr><td>**DESCRIPTION**</td></tr>
<tr><td>Standard Single 120mm - Round Canopy</td></tr>
</table>

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 $\frac{3}{4}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

1 $\frac{3}{16}$" 30mm

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149001-

DESCRIPTION

Component - Single 120mm - Round Canopy

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 $\frac{3}{4}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

1 ³⁄₁₆" 30mm

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149006-

DESCRIPTION

Component - Round Canopy - 95mm - 3 Holes

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 ¾

Height (mm): 25

Height (in): 1

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

1" 25mm

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149007-

DESCRIPTION

Component - Round Canopy - 120mm - 5 Holes

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 ¾

Height (mm): 25

Height (in): 1

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

1" 25mm

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149008-

DESCRIPTION

Component - Single 120mm - Round Cone Canopy - 2 External Holes + 1 Central Hole

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 ¾

Height (mm): 70

Height (in): 2 ¾

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

70mm 2 ¾"

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149009-

DESCRIPTION

Component - Single 120mm - Round Cone Canopy - 4 External
Holes + 1 Central Hole

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 120

Diameter (in): 4 $\frac{3}{4}$

Height (mm): 90

Height (in): 3 $\frac{9}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø120mm 4 ¾"

90mm 3 ⁹⁄₁₆"

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149011-

DESCRIPTION
Flute - Cable Spacer

GENERAL

Series: Flute

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

25mm 1"

15mm ⁹⁄₁₆"   15mm ⁹⁄₁₆"

(D)

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149012-

DESCRIPTION

Accessory - Wall Stud Cable Spacer

GENERAL

Series: Flute

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

20mm ¹³⁄₁₆"

10mm ³⁄₈"   20mm ¹³⁄₁₆"

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149013-

DESCRIPTION

Accessory - Ceiling Cable Spacer

GENERAL

Series: Flute

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

30mm 1 ³⁄₁₆"

30mm 1 ³⁄₁₆"

10mm ³⁄₈"

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149014-

DESCRIPTION

Component - Round Canopy - 270mm - for 3 - 5 - 6 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 270

Diameter (in): 10 $\frac{5}{8}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

D

Zaneen Group Inc. © 2024, T 1800-388-3382, F 416-247-9319, www.zaneen.com

Availble for International specifications by adding 'INT' at the end of the existing Model #. For assistance on 'custom' specifications, contact zteam@zaneen.com.
In a constant effort to supply the best product, we reserve the right to change specifications or materials without notice. The most recent specification sheets are found at zaneen.com

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149015-

DESCRIPTION

Component - Round Canopy - 430mm - for 3 - 5 - 6 - 7 - 8 - 9 - 10 -11 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 430

Diameter (in): 16 $\frac{15}{16}$

Height (mm): 40

Height (in): 1 $\frac{9}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

5 $\frac{1}{8}$"
130mm

6 $\frac{5}{16}$"
160mm

9 $\frac{1}{16}$"
230mm

220mm
8 $\frac{11}{16}$"

Ø370mm 14 $\frac{9}{16}$"

1 $\frac{9}{16}$"
40mm

Ø430mm 16 $\frac{15}{16}$"

130mm
5 $\frac{1}{8}$"

D

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149016-

DESCRIPTION

Component - Round Canopy - 500mm - for 3 - 4 - 5 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Round

Diameter (mm): 500

Diameter (in): 19 $\frac{11}{16}$

Height (mm): 40

Height (in): 1 $\frac{9}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

360mm 14 $\frac{3}{16}$ "

8 $\frac{1}{4}$ "
210mm

300mm 11 $\frac{13}{16}$ "

Ø460mm 18 $\frac{1}{8}$ "

40mm 1 $\frac{9}{16}$ "

Ø500mm 19 $\frac{11}{16}$ "

D

October 12, 2024, 1:47 am

ZANEEN®

## D14AERON-MOD-SYS COMPONENTS

D149017-

DESCRIPTION

Component - Square Canopy - 300mm - for 5 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Square

Length (mm): 300

Length (in): 11 $\frac{13}{16}$

Width (mm): 300

Width (in): 11 $\frac{13}{16}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

300mm 11 $\frac{13}{16}$"

220mm 8 $\frac{11}{16}$"

80mm 3 $\frac{1}{8}$"

300mm 11 $\frac{13}{16}$"

220mm 8 $\frac{11}{16}$"

120mm 4 $\frac{3}{4}$"

1 $\frac{3}{16}$"

30mm

D

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149018-

DESCRIPTION

Component - Square Canopy - 400mm - for 5 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Square

Length (mm): 400

Length (in): 15 ¾

Width (mm): 400

Width (in): 15 ¾

Height (mm): 30

Height (in): 1 ³⁄₁₆

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

400mm 15 ¾"

300mm 11 ¹³⁄₁₆"

130mm 5 ⅛"

400mm 15 ¾"

300mm 11 ¹³⁄₁₆"

180mm 7 ¹⁄₁₆"

1 ³⁄₁₆"

30mm

(D)

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149019-

DESCRIPTION

Component - Slim Linear Canopy - 300mm - 2 lights

GENERAL

Brand: Cangini & Tucci
Division: Design

PHYSICAL

Shape: Rectangle
Length (mm): 300
Length (in): 11 $\frac{13}{16}$
Width (mm): 30
Width (in): 1 $\frac{3}{16}$
Height (mm): 30
Height (in): 1 $\frac{3}{16}$
Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF
Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

Ø125mm 4 $\frac{15}{16}$"

1 $\frac{3}{16}$" 30mm

300mm 11 $\frac{13}{16}$"

1 $\frac{3}{16}$" 30mm

50mm 1 $\frac{15}{16}$"

50mm 1 $\frac{15}{16}$"

30mm 1 $\frac{3}{16}$"

200mm 7 $\frac{7}{8}$"

(D)

October 12, 2024, 1:47 am

ZANEEN®

D14AERON-MOD-SYS COMPONENTS

D149020-

DESCRIPTION

Component - Slim Linear Canopy - 500mm - 3 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Rectangle

Length (mm): 500

Length (in): 19 $\frac{11}{16}$

Width (mm): 30

Width (in): 1 $\frac{3}{16}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø125mm 4 $\frac{15}{16}$"

1 $\frac{3}{16}$"
30mm

500mm 19 $\frac{11}{16}$"

1 $\frac{3}{16}$"
30mm

200mm 7 $\frac{7}{8}$"

50mm 30mm

1 $\frac{15}{16}$" 1 $\frac{3}{16}$"

D

October 12, 2024, 1:47 am

ZANEEN®

## D14AERON-MOD-SYS COMPONENTS

D149021-

DESCRIPTION

Component - Slim Linear Canopy - 1000mm - 3-5 lights

GENERAL

Brand: Cangini & Tucci

Division: Design

PHYSICAL

Shape: Rectangle

Length (mm): 1000

Length (in): 39 $\frac{3}{8}$

Width (mm): 30

Width (in): 1 $\frac{3}{16}$

Height (mm): 30

Height (in): 1 $\frac{3}{16}$

Fixture Finish: CHR / WHI / BLK / BST / SLF / GLF

Fixture Material: Metal

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Ø125mm 4 $\frac{15}{16}$"

1 $\frac{3}{16}$" 30mm

1000mm 39 $\frac{3}{8}$"

1 $\frac{3}{16}$" 30mm

150mm 5 $\frac{7}{8}$"   350mm 13 $\frac{3}{4}$"   30mm 1 $\frac{3}{16}$"

Ø125mm 4 $\frac{15}{16}$"

1 $\frac{3}{16}$" 30mm

1000mm 39 $\frac{3}{8}$"

1 $\frac{3}{16}$" 30mm

100mm 3 $\frac{15}{16}$"   200mm 7 $\frac{7}{8}$"   30mm 1 $\frac{3}{16}$"

(D)

October 12, 2024, 1:47 am

ZANEEN

D14AERON-MOD-SYS COMPONENTS

LEGEND

Symbol	Description	Symbol	Description	Symbol	Description
↓	floor-mounted		pivotable		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
↗	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
↑	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
→	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable	CRI	color rendering index
	direct light distribution		reflector degree selection	°K	color temperature
	direct/indirect light distribution	s|s	super spot	LM	lumen (luminous flux)
	indirect light distribution		lens	LM/W	efficacy (lumens per watt)
	asymmetric light distribution		lens pack	UGR	Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out	⊙	integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions	c	individual colors: 00 (free of charge), 01-25 (extra charge)	DSC	Dark Sky Compliance
	minimum distance (meters) lamp - object	◆	luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth	▲	luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm	●	luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection	■	luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)	⬠	luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear	▪	color of 3-circuit adaptor	□	protection class II, protection insulation
	separately switchable	⊙	indirect diffuser	ETL	ETL Certified to UL and CSA Standards
	sensor	D	direct diffuser	UL	UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)	CSA	CSA Certified to UL and CSA Standards
	available upon request		accessory	Z	Certified for North American Standards

IP RATING

IP20	protected against ingress of solid bodies greater than 12.5mm (finger)
IP33	protected against ingress of solid bodies greater than 2.5mm / protected against sprays of water up to 60 degrees from the vertical (rain)
IP40	protected against ingress of solid bodies greater than 1mm (wire) / no protection against the ingress of moisture
IP43	protected against ingress of solid bodies greater than 1mm (wire) / protected against sprays of water up to 60 degrees from the vertical (rain)
IP44	protected against ingress of solid bodies greater than 1mm (wire) / protected against water splashed from all directions
IP54	protected against limited ingress of dust (wet rooms/covered outdoor areas) / protected against water splashed from all directions
IP65	protected against ingress of dust / protected against jets of water
IP66	protected against ingress of dust / protected against powerful jets of water or heavy seas
IP67	protected against ingress of dust / protected against immersion of water between 15cm - 1m for 30 minutes
IP68	protected against ingress of dust / protected against immersion of water under pressure for long periods

IK RATING

IK01	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
IK02	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
IK03	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
IK04	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
IK05	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
IK06	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
IK07	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
IK08	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
IK09	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
IK10	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)

Zaneen Group Inc. © 2024, T 1800-388-3382, F 416-247-9319, www.zaneen.com

Page 24/24

Availble for International specifications by adding 'INT' at the end of the existing Model #. For assistance on 'custom' specifications, contact zteam@zaneen.com.

In a constant effort to supply the best product, we reserve the right to change specifications or materials without notice. The most recent specification sheets are found at zaneen.com.

October 12, 2024, 1:47 am