

D81630R9- COMPONENTS SUSPENSION

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

D89058-

DESCRIPTION

Zero Round Canopy - Ø206mm / 8 1/8" - For One Suspension - Non-dimming / 0-10Vdc Dimming Driver Included - 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL


Shape: Cylinder
Diameter (mm): 206
Diameter (in): 8 1/8
Height (mm): 41
Height (in): 1 5/16
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum

ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



D81630R9- COMPONENTS SUSPENSION

D89059-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Two
Suspensions - Non-dimming / 0-10Vdc Dimming Driver Included
- 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL

Shape: Cylinder
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum


ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D81630R9- COMPONENTS SUSPENSION

D89060-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Three
Suspensions - Non-dimming / 0-10Vdc Dimming Driver Included
- 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL

Shape: Round
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum


ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D81630R9- COMPONENTS SUSPENSION

PROJECT
TYPE
NOTES
QUANTITY
DATE

D89061-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Four
Suspensions - Non-dimming / 0-10Vdc Dimming Driver Included
- 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL


Shape: Cylinder
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum

ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



D81630R9- COMPONENTS SUSPENSION

D89062-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Two
Suspensions with joined steel cables - Non-dimming / 0-10Vdc
Dimming Driver Included - 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL

Shape: Cylinder
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum


ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D81630R9- COMPONENTS SUSPENSION

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

D89063-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Three Suspensions with joined steel cables - Non-dimming / 0-10Vdc Dimming Driver Included - 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL


Shape: Cylinder
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum

ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



D81630R9- COMPONENTS SUSPENSION

D89064-

DESCRIPTION

Zero Round Canopy - Ø325mm / 12 13/16" - For Four
Suspensions with joined steel cables - Non-dimming / 0-10Vdc
Dimming Driver Included - 120/277Vac

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL

Shape: Cylinder
Diameter (mm): 325
Diameter (in): 12 13/16
Height (mm): 38
Height (in): 1 1/2
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum


ELECTRICAL

Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D81630R9- COMPONENTS SUSPENSION

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

D89103-

DESCRIPTION

Zero Shapes - Canopy for 1 Horizontal Suspension with joined steel cables - including power supply - 0-10V Dimming

GENERAL

Series: Zero Round
Brand: Panzeri
Division: Design
Mounting Type: Suspension
Mounting Location: Ceiling
Subcategory: Pendant

PHYSICAL



Shape: Cylinder
Diameter (mm): 206
Diameter (in): 8 2⁄16
Height (mm): 41
Height (in): 1 5⁄16
Fixture Finish: WHI / BLK / BRZ / MBR / TIM
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 50 - 79 W
Lamp Type: LED
Input Wattage (W): 75
Total Output Wattage (W): 60
Dimming: 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



Ø206mm 8 1⁄8"



PROJECT
TYPE
NOTES
QUANTITY
DATE

LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/ control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)