

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

## E15G0006- COMPONENTS

### E15A004

#### DESCRIPTION

Glowline, On/Off leader cable and cap - 2,000mm/78 3/4", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline \_\_\_\_\_  
 Partner: Diamante \_\_\_\_\_  
 Division: Exterior \_\_\_\_\_

#### PHYSICAL

Diameter (mm): 23 \_\_\_\_\_  
 Diameter (in): 7/8 \_\_\_\_\_  
 Length (mm): 2000 \_\_\_\_\_  
 Length (in): 78 3/4 \_\_\_\_\_  
 Weight (kg): 0.28 \_\_\_\_\_

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards \_\_\_\_\_  
 IP rating: IP66 \_\_\_\_\_  
 IK Rating: IK08 \_\_\_\_\_



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## E15G0006- COMPONENTS

### E15A005

#### DESCRIPTION

Glowline, On/Off leader cable and cap - 5,000mm/196 7/8", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Weight (kg): 0.66

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A006

#### DESCRIPTION

Glowline, On/Off leader cable and cap - 10,000mm/393 11/16", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 10000  
 Length (in): 393 11/16  
 Weight (kg): 1.3

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

## E15G0006- COMPONENTS

### E15A007

#### DESCRIPTION

Glowline, On/Off leader cable and cap - 20,000mm/787 3/8", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 20000  
 Length (in): 787 3/8  
 Weight (kg): 2.59

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A008

#### DESCRIPTION

Glowline, On/Off Jumper cable - 500mm/19 11/16", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 500  
 Length (in): 19 11/16  
 Weight (kg): 0.1

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66  
 IK Rating: IK08



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A009

#### DESCRIPTION

Glowline, On/Off Jumper cable - 1,000mm/39 3/8", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 1000  
 Length (in): 39 3/8  
 Weight (kg): 0.17

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A010

#### DESCRIPTION

Glowline, On/Off Jumper cable - 2,000mm/78 3/4", 4 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 2000  
 Length (in): 78 3/4  
 Weight (kg): .3

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	


### E15A011

**DESCRIPTION**  
 Glowline, On/Off Jumper cable - 5,000mm/196 7/8", 4 Pole, Max Power 1500W, 1200Vac

**GENERAL**  
 Series: Glowline  
 Partner: Diamante  
 Division: Exterior

**PHYSICAL**  
 Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Weight (kg): .68

**RATINGS AND CERTIFICATIONS**  
 Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A012

#### DESCRIPTION

Glowline, Dali leader cable and cap - 2,000mm/78 3/4", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 2000  
 Length (in): 78 3/4  
 Weight (kg): 0.41

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66  
 IK Rating: IK08



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A013

#### DESCRIPTION

Glowline, Dali leader cable and cap - 5,000mm/196 7/8", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Weight (kg): 1

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A014

#### DESCRIPTION

Glowline, Dali leader cable and cap - 10,000mm/393 11/16", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 10000  
 Length (in): 393 11/16  
 Weight (kg): 2

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	


### E15A015

**DESCRIPTION**  
 Glowline, Dali leader cable and cap - 20,000mm/787 3/8", 5 Pole, Max Power 1500W, 1200Vac

**GENERAL**  
 Series: Glowline  
 Partner: Diamante  
 Division: Exterior

**PHYSICAL**  
 Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 20000  
 Length (in): 787 3/8  
 Weight (kg): 4

**RATINGS AND CERTIFICATIONS**  
 Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A016

#### DESCRIPTION

Glowline, Dali Jumper cable - 500mm/19 11/16", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 500  
 Length (in): 19 11/16  
 Weight (kg): 0.13

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66  
 IK Rating: IK08



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A017

#### DESCRIPTION

Glowline, Dali Jumper cable - 1,000mm/39 3/8", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 1000  
 Length (in): 39 3/8  
 Weight (kg): 0.23

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A018

#### DESCRIPTION

Glowline, Dali Jumper cable - 2,000mm/78 3/4", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 2000  
 Length (in): 78 3/4  
 Weight (kg): .43

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



## E15G0006- COMPONENTS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

### E15A019

#### DESCRIPTION

Glowline, Dali Jumper cable - 5,000mm/196 7/8", 5 Pole, Max Power 1500W, 1200Vac

#### GENERAL


Series: Glowline  
 Partner: Diamante  
 Division: Exterior

#### PHYSICAL

Diameter (mm): 23  
 Diameter (in): 7/8  
 Length (mm): 5000  
 Length (in): 196 7/8  
 Weight (kg): .1

#### RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
 IP rating: IP66



### LEGEND

floor-mounted	pivotal	special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
wall and ceiling: recessed and surface mounted	rotating	warm dim / natural dimming LED
ceiling-mounted and wall-mounted	illuminate tilted	rechargeable battery powered
wall-mounted	color of suspension cable	fixture with natural vivid LED (upon request)
omni-directional light distribution	length of suspension cable	color rendering index
direct light distribution	reflector degree selection	color temperature
direct/indirect light distribution	super spot	lumen (luminous flux)
indirect light distribution	lens	efficacy (lumens per watt)
asymmetric light distribution	lens pack	Unified Glare Rating (UGR) range from 5-40
aura light distribution	shine ring	marine grade (AISI 316 stainless steel)
round wall or ceiling cut-out	integrated shine ring with diffuser	walk on
square wall or ceiling cut-out	free individual colors 01-29	drive on
the supplied jig specifies the cutout dimensions	individual colors: 00 (free of charge), 01-25 (extra charge)	Dark Sky Compliance
minimum distance (meters) lamp - object	luminaire part to be colored (F1)	Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
recessed depth	luminaire part to be colored (F2)	lamp protected against explosion
ceiling thickness in mm	luminaire part to be colored (F3)	blown glass using traditional methods by master glass blower
ceiling thickness selection	luminaire part to be colored (F4)	acoustic material
dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)	luminaire part to be colored (F5)	protection class I, protection insulation
included or excluded LED driver/transformer/control gear	color of 3-circuit adaptor	protection class II, protection insulation
separately switchable	indirect diffuser	ETL Certified to UL and CSA Standards
sensor	direct diffuser	UL Certified to UL and CSA Standards
remote control	ball-proof (upon request)	CSA Certified to UL and CSA Standards
available upon request	accessory	Certified for North American Standards

### IP RATING

IP20	protected against ingress of solid bodies greater than 12.5mm (finger)
IP33	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
IP40	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
IP43	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
IP44	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
IP54	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
IP65	protected against ingress of dust protected against jets of water
IP66	protected against ingress of dust protected against powerful jets of water or heavy seas
IP67	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
IP68	protected against ingress of dust protected against immersion of water under pressure for long periods

### IK RATING

IK01	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
IK02	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
IK03	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
IK04	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
IK05	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
IK06	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
IK07	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
IK08	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
IK09	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
IK10	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)