

D111090-

base number

Options Options

1.To build a product code in our configurator select the specify button on the base model #

2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Senia Brand: Ole Division: Design

Mounting Type: Suspension

Mounting Location: Ceiling

Subcategory: Ambient

PHYSICAL

Shape: Drum Diameter (mm): 400

Diameter (in): 15 3/4

Height (mm): 200 Height (in): 7 1/8

Max. Overall Height (mm): 2200

Max. Overall Height (in): 86 %

Light Distribution: Direct

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI

Holder Finish: WHI / MBK

Fixture Material: Fabric Cord / Metal

Cable Details: 2000mm Cable

Upon Request: Other fabric cord colors available upon request (see downloadable finish chart)

ELECTRICAL

Number of Lamps: 1

Lamp Type: LED Retrofit

Lamp Shape: A19

Bulb Included: Bulb Not Included

Max. Wattage Per Lamp (W): 15

Lamp Base: E26

Input Voltage (V): 120

Upon Request: 277Vac / GU24


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT TYPE SPECIFIER QUANTITY DATE










D111090-

| PROJECT |
|-----------|
| ГҮРЕ |
| SPECIFIER |
| QUANTITY |
| DATE |







COLOR FINISH CHART


| PROJECT | | |
|-----------|--|--|
| TYPE | | |
| SPECIFIER | | |
| QUANTITY | | |
| DATE | | |

Fixture Finish
































Holder Finish





Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens. **Physical:** When texture is involved, there will be variations in color, character and tone within a product series and between product families.





PROJECT TYPE SPECIFIER QUANTITY DATE



















301







Pant. WHITE 71

Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens. **Physical:** When texture is involved, there will be variations in color, character and tone within a product series and between product families.



| PROJECT | | |
|-----------|--|--|
| TYPE | | |
| SPECIFIER | | |
| QUANTITY | | |
| DATE | | |

129

COMPLETE COLOR FINISH CHART





| PROJECT | | |
|-----------|--|--|
| TYPE | | |
| SPECIFIER | | |
| QUANTITY | | |
| DATE | | |

COMPLETE COLOR FINISH CHART





VERDE BILLAR

Pant. 340C

353



Standard Colors with [S-]

AVELLANA

Pant. 729C

Other fabric cord colors available upon request. Price increase and minimum quantities may apply

152

Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens.



| PROJECT | | |
|-----------|--|--|
| TYPE | | |
| SPECIFIER | | |
| QUANTITY | | |
| DATE | | |

COMPLETE COLOR FINISH CHART





COMPLETE COLOR FINISH CHART













LEGEND

| | | | | | special LED (upon request) PGB_PGBW_tunable |
|-----------------------|--|----------|--|------------|--|
| <u></u> | floor-mounted | ¥ | pivotable | ⊛ | special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+ |
| 7 | wall and ceiling: recessed and surface mounted | C | rotating | 0 | warm dim / natural dimming LED |
| $\overline{\uparrow}$ | ceiling-mounted and wall-mounted | Œ | illuminate tilted | 0 | rechargeable battery powered |
| \rightarrow | wall-mounted | I | color of suspension cable | | fixture with natural vivid LED (upon request) |
| Y | omni-directional light distribution | 1 | length of suspension cable | CRI | color rendering index |
| $\dot{\Delta}$ | direct light distribution | | reflector degree selection | (K) | color temperature |
| X | direct/indirect light distribution | s s | super spot | LM | lumen (luminous flux) |
| Y | indirect light distribution | * | lens | ₩ | efficacy (lumens per watt) |
| | asymmetric light distribution | 8 | lens pack | UGR | Unified Glare Rating (UGR) range from 5-40 |
| | aura light distribution | 0 | shine ring | * | marine grade (AISI 316 stainless steel) |
| R | round wall or ceiling cut-out | 0 | integrated shine ring with diffuser | 3 | walk on |
| Z) | square wall or ceiling cut-out | | free individual colors 01-29 | ② | drive on |
| 4 | the supplied jig specifies the cutout dimensions | Ĉ | individual colors: 00 (free of charge), 01-25 (extra charge) | DSC | Dark Sky Compliance |
| □ ←,→ | minimum distance (meters) lamp - object | ♦ | luminaire part to be colored (F1) | Ġ | Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor) |
| $\hat{\pm}$ | recessed depth | | luminaire part to be colored (F2) | | lamp protected against explosion |
| <u></u> | ceiling thickness in mm | • | luminaire part to be colored (F3) | | blown glass using traditional methods by master glass blower |
| 1 | ceiling thickness selection | | luminaire part to be colored (F4) | ● ® | acoustic material |
| | dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim) | • | luminaire part to be colored (F5) | | protection class I, protection insulation |
| C. CO | included or excluded LED driver/transformer/ control gear | • | color of 3-circuit adaptor | | protection class II, protection insulation |
| 8 | separately switchable | \odot | indirect diffuser | . . | ETL Certified to UL and CSA Standards |
| 9 | sensor | 0 | direct diffuser | շ (Մը) us | UL Certified to UL and CSA Standards |
| | remote control | (1) | ball-proof (upon request) | ® : | CSA Certified to UL and CSA Standards |
| 9 | available upon request | O | accessory | ② | Certified for North American Standards |

IP RATING

| IP20 | protected against ingress of solid bodies greater than 12.5mm (finger) |
|------|---|
| IP33 | protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain) |
| IP40 | protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture |
| IP43 | protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain) |
| IP44 | protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions |
| IP54 | protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions |
| IP65 | protected against ingress of dust protected against jets of water |
| IP66 | protected against ingress of dust protected against powerful jets of water or heavy seas |
| IP67 | protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes |
| IP68 | protected against ingress of dust protected against immersion of water under pressure for long periods |

IK RATING

above the surface)

| IK02 | protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface) |
|-------------|---|
| ІКОЗ | protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface) |
| IK04 | protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface) |
| IK05 | protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface) |
| 1K06 | protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface) |
| IK07 | protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface) $$ |
| IKOB | protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface) |
| IK09 | protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface) |

protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)

protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm