

D111105-

base number

Options Options

 $1. To \ build\ a\ product\ code\ in\ our\ configurator\ select\ the\ specify\ button\ on\ the\ base\ model\ \#$

2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Nela	
Brand: Ole	
Division: Design	
Mounting Type: Suspension	
Mounting Location: Ceiling	
Subcategory: Up/Down Light	

PHYSICAL

	Shape: Abstract
Ī	Diameter (mm): 500
i	Diameter (in): 19 11/16
Ī	Height (mm): 350
i	Height (in): 13 ¾
- 3	

Max. Overall Height (mm): 2350 Max. Overall Height (in): 92 ½ Light Distribution: Omnidirectional

Fixture Finish: BEI / BLK / BLU / COG / DGN / GRY / MRN / MOC / MUS / OLV / SIL / STN / TER / WHI

Holder Finish: MWH / MBK

Fixture Material: Fabric Cord / Metal

Cable Details: 2000mm Cable


Upon Request: Other fabric cord colors available upon request (see downloadable finish chart)

ELE	CTRICAL
Num	nber of Lamps: 1
Lam	p Type: LED Retrofit
Lam	p Shape: A19
Bulb	o Included: Bulb Not Included
Max.	. Wattage Per Lamp (W): 15
Lam	p Base: E26
Inpu	it Voltage (V): 120
Upo	n Request: 277Vac / GU24


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20












D111105-

PROJECT		
TYPE		
SPECIFIER		
QUANTITY		
DATE		








COLOR FINISH CHART


PROJECT
TYPE
SPECIFIER
QUANTITY
DATE

Fixture Finish































Holder Finish





Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens. **Physical:** When texture is involved, there will be variations in color, character and tone within a product series and between product families.





PROJECT TYPE SPECIFIER QUANTITY DATE



























Pant. WHITE 71

Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens. **Physical:** When texture is involved, there will be variations in color, character and tone within a product series and between product families.



PROJECT		
TYPE		
SPECIFIER		
QUANTITY		
DATE		

COMPLETE COLOR FINISH CHART





PROJECT		
TYPE		
SPECIFIER		
QUANTITY		
DATE		

COMPLETE COLOR FINISH CHART





VERDE BILLAR

Pant. 340C

353





PROJECT			
TYPE			
SPECIFIER			
QUANTITY			
DATE			

COMPLETE COLOR FINISH CHART





PROJECT		
TYPE		
SPECIFIER		
QUANTITY		
DATE		

COMPLETE COLOR FINISH CHART















PROJECT		
TYPE		
SPECIFIER		
QUANTITY		
DATE		

LEGEND

T Y	Tues o		A		special LED (upon request) BCP, BCPW tupoble
<u></u>	floor-mounted	¥	pivotable	⊛	special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
7	wall and ceiling: recessed and surface mounted	S	rotating	0	warm dim / natural dimming LED
\uparrow	ceiling-mounted and wall-mounted	Œ	illuminate tilted	0	rechargeable battery powered
\rightarrow	wall-mounted	T	color of suspension cable	THESE	fixture with natural vivid LED (upon request)
Y	omni-directional light distribution	1	length of suspension cable	CRI	color rendering index
	direct light distribution		reflector degree selection	(K)	color temperature
X	direct/indirect light distribution	s s	super spot	(LM)	lumen (luminous flux)
M	indirect light distribution	*	lens	₩)	efficacy (lumens per watt)
	asymmetric light distribution	8	lens pack	UGR	Unified Glare Rating (UGR) range from 5-40
	aura light distribution	0	shine ring	*	marine grade (AISI 316 stainless steel)
R	round wall or ceiling cut-out	0	integrated shine ring with diffuser	3	walk on
Z)	square wall or ceiling cut-out		free individual colors 01-29	②	drive on
4	the supplied jig specifies the cutout dimensions	Ċ	individual colors: 00 (free of charge), 01-25 (extra charge)	DSC	Dark Sky Compliance
d •,→	minimum distance (meters) lamp - object	•	luminaire part to be colored (F1)	Ġ	Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
$\hat{\pm}$	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
1	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
1	ceiling thickness selection		luminaire part to be colored (F4)	()	acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)	•	luminaire part to be colored (F5)		protection class I, protection insulation
- Laco	included or excluded LED driver/transformer/ control gear	•	color of 3-circuit adaptor		protection class II, protection insulation
४	separately switchable	\odot	indirect diffuser	. (1)	ETL Certified to UL and CSA Standards
9	sensor	O	direct diffuser	.(N) us	UL Certified to UL and CSA Standards
	remote control	(3)	ball-proof (upon request)	(I)	CSA Certified to UL and CSA Standards
9	available upon request	0	accessory	Z	Certified for North American Standards

IP RATING

IP20	protected against ingress of solid bodies greater than 12.5mm (finger)
IP33	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
IP40	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
IP43	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
IP44	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
IP54	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
IP65	protected against ingress of dust protected against jets of water
IP66	protected against ingress of dust protected against powerful jets of water or heavy seas
IP67	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
IP68	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

above the surface)

above the surface)

protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface) $$

protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm

protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm