



FELIX 40 SURFACE

L12F0001-

GENERAL

Division: Exterior
 Series: Felix
 Subseries: Felix 40
 Mounting Type: Surface
 Mounting Location: Above Ground
 Subcategory: Flood
 Brand: Unonovesette

PHYSICAL

Shape: Cylinder
 Length (mm): 75
 Length (in): 2 ¹³/₁₆
 Height (mm): 51.5
 Height (in): 2
 Light Distribution: Adjustable / Direct
 Weight (kg): 0.41
 Weight (lbs): 0.90
 Diffuser: Extra clear tempered 4mm
 Fixture Finish: Stainless Steel
 Fixture Material: Metal
 Cable Details: 5000mm NS20N PCP 2x0.5 mm2

ELECTRICAL

Lamp Type: LED
 Input Wattage (W): 2.93
 Total Output Wattage (W): 2
 Dimming: Non-Dimming / Phase Dimming (120Vac only) / 0-10V Dimming
 Driver Included: No
 Driver Location: Remote
 Driver Type: Constant Voltage - Universal
 Driver Class: Class 2
 Input Voltage (V): 120 / 277
 Output Voltage (V): 24

LED

Number of LEDs: 1
 Color Temperature (°K): 2200 / 2700 / 3000 / 4000
 Max. Delivered Lumen (lm): 127
 CRI: >90 CRI
 Lamp Life (hrs): 100000

OPTICAL

Optic°: 10 / 23 / 43 / 10x40
 Beam Angle: Narrow / Medium / Wide / Elliptical

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
 IP rating: IP68
 IK Rating: IK07
 Marine Grade: 304

PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



FELIX 40 SURFACE

L12F0001-



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



FELIX 40 SURFACE COLOR FINISH CHART

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens.
Physical: When texture is involved, there will be variations in color, character and tone within a product series and between product families.

