

CENTRIQ IN SURFACE

A3D332-

|             |                |                      |                       |                        |                       |
|-------------|----------------|----------------------|-----------------------|------------------------|-----------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 160

Height (in): 6 5/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 18.8

Dimming: Non-Dimming / DALI Dimming

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 1941

Nominal Lumen (lm): Max 2339

CRI: >90 CRI

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D333-

|             |                |                      |                       |                        |                       |
|-------------|----------------|----------------------|-----------------------|------------------------|-----------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 2 5/16

Height (mm): 185

Height (in): 7 5/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 36.2

Dimming: Non-Dimming / DALI Dimming

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 900mA

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 3450

Nominal Lumen (lm): Max 3952

CRI: >90 CRI

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D432-

|             |                |                      |                       |                        |
|-------------|----------------|----------------------|-----------------------|------------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) |
|-------------|----------------|----------------------|-----------------------|------------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 160

Height (in): 6 5/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 20.6

Dimming: Non-Dimming / DALI Dimming

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 1554

Nominal Lumen (lm): Max 1907

CRI: >90 CRI

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D436-

|             |                      |                       |                        |                       |
|-------------|----------------------|-----------------------|------------------------|-----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|----------------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 120

Height (in): 4 3/4

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 68mm / 2 11/16"

ELECTRICAL

Input Wattage (W): 23

Dimming: Non-dimmable / MATTER Dimming

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 2291

Nominal Lumen (lm): Max 2761

CRI: >90 CRI

Efficiency (%): 99.6

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



A

CENTRIQ IN SURFACE

A3D437-

base number

Color  
Temperature

Finishes  
(Diamond)

Finishes  
(Triangle)

- 1.To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 120

Height (in): 4 3/4

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 68mm / 2 11/16"

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 20.6

Dimming: Non-Dimming / DALI Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 500mA

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 1566

Nominal Lumen (lm): Max 1922

CRI: >90 CRI

Efficiency (%): 99.6

OPTICAL

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D438-

|             |                       |                        |                       |
|-------------|-----------------------|------------------------|-----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 120

Height (in): 4 3/4

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 68mm / 2 11/16"

ELECTRICAL

Input Wattage (W): 8.2

Dimming: DALI Dimming / MATTER Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 200mA

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 1251

Nominal Lumen (lm): Max 1460

CRI: >90 CRI

Efficiency (%): 99.6

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D439- -

|             |                       |                        |
|-------------|-----------------------|------------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) |
|-------------|-----------------------|------------------------|

- 1.To build a product code in our configurator select the specify button on the base model # product page
- 2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

**GENERAL**

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

**PHYSICAL**

Shape: Cylinder

Diameter (mm): 65

Diameter (in): 2 9/16

Height (mm): 120

Height (in): 4 3/4

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 86mm / 3 3/8"

**ELECTRICAL**

Lamp Type: LED

Input Wattage (W): 14

Dimming: DALI Dimming / MATTER Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 700mA

**LED**

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 564

Nominal Lumen (lm): Max 664

CRI: >90 CRI

Efficiency (%): 99.6

Lamp Life (hrs): 50000

**OPTICAL**

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°


**RATINGS AND CERTIFICATIONS**

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



A

CENTRIQ IN SURFACE

A3D440-

|             |                      |                       |                        |                       |                      |
|-------------|----------------------|-----------------------|------------------------|-----------------------|----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options | Ceiling<br>Thickness |
|-------------|----------------------|-----------------------|------------------------|-----------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                            |
|--------------------------------------------|
| Series: Centriq                            |
| Subseries: Centriq In                      |
| Partner: Prolicht                          |
| Division: Architectural                    |
| Installation: Surface                      |
| Product Type: Spots                        |
| Mounting Location: Ceiling                 |
| Light Distribution: Adjustable / Downlight |

PHYSICAL

|                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shape: Cylinder                                                                                                                                                                 |
| Diameter (mm): 65                                                                                                                                                               |
| Diameter (in): 2 9/16                                                                                                                                                           |
| Height (mm): 120                                                                                                                                                                |
| Height (in): 4 3/4                                                                                                                                                              |
| Ceiling Thickness (mm): 10 / 12.5 / 15 / 25                                                                                                                                     |
| Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1                                                                                                                                 |
| Min. Recessing Depth (mm): 50                                                                                                                                                   |
| Min. Recessing Depth (in): 1 15/16                                                                                                                                              |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR |
| Fixture Material: Aluminum Die Cast                                                                                                                                             |
| Cut-out Measurements: Dia. 86mm / 3 3/8"                                                                                                                                        |

ELECTRICAL

|                                             |
|---------------------------------------------|
| Input Wattage (W): 23                       |
| Dimming: Dali Dimming                       |
| Driver Included: Yes                        |
| Driver Location: Remote                     |
| Driver Type: Constant Current - Universal   |
| Driver Class: Class 2                       |
| Input Voltage (V): 120                      |
| Constant Current (MA): 600mA                |
| Upon Request: 0-10V dimming / Phase Dimming |

LED

|                                                   |
|---------------------------------------------------|
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000 |
| Max. Delivered Lumen (lm): Max 2291               |
| Nominal Lumen (lm): Max 2761                      |
| CRI: >90 CRI                                      |
| Efficiency (%): 99.6                              |
| Lamp Life (hrs): 50000                            |


OPTICAL

|                                          |
|------------------------------------------|
| Beam Angle: 24, 36, 52                   |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |
| Glare Rating: ≤ 16                                   |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D441-

|             |                      |                       |                        |                      |
|-------------|----------------------|-----------------------|------------------------|----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Ceiling<br>Thickness |
|-------------|----------------------|-----------------------|------------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                            |
|--------------------------------------------|
| Series: Centriq                            |
| Subseries: Centriq In                      |
| Partner: Prolicht                          |
| Division: Architectural                    |
| Installation: Surface                      |
| Product Type: Spots                        |
| Mounting Location: Ceiling                 |
| Light Distribution: Adjustable / Downlight |

PHYSICAL

|                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shape: Cylinder                                                                                                                                                                 |
| Diameter (mm): 65                                                                                                                                                               |
| Diameter (in): 2 9/16                                                                                                                                                           |
| Height (mm): 120                                                                                                                                                                |
| Height (in): 4 3/4                                                                                                                                                              |
| Ceiling Thickness (mm): 10 / 12.5 / 15 / 25                                                                                                                                     |
| Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1                                                                                                                                 |
| Min. Recessing Depth (mm): 50                                                                                                                                                   |
| Min. Recessing Depth (in): 1 15/16                                                                                                                                              |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR |
| Fixture Material: Aluminum Die Cast                                                                                                                                             |
| Cut-out Measurements: Dia. 86mm / 3 3/8"                                                                                                                                        |

ELECTRICAL

|                                             |
|---------------------------------------------|
| Lamp Type: LED                              |
| Input Wattage (W): 20.6                     |
| Dimming: Dali Dimming                       |
| Driver Included: Yes                        |
| Driver Location: Remote                     |
| Driver Type: Constant Current - Universal   |
| Driver Class: Class 2                       |
| Input Voltage (V): 120                      |
| Constant Current (MA): 500mA                |
| Upon Request: 0-10V dimming / Phase Dimming |

LED

|                                                   |
|---------------------------------------------------|
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000 |
| Max. Delivered Lumen (lm): Max 1566               |
| Nominal Lumen (lm): Max 1922                      |
| CRI: >90 CRI                                      |
| Efficiency (%): 99.6                              |
| Lamp Life (hrs): 50000                            |


OPTICAL

|                                          |
|------------------------------------------|
| Beam Angle: 12                           |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |
| Glare Rating: ≤ 16                                   |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D442-

|             |                       |                        |                       |                      |
|-------------|-----------------------|------------------------|-----------------------|----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options | Ceiling<br>Thickness |
|-------------|-----------------------|------------------------|-----------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                            |
|--------------------------------------------|
| Series: Centriq                            |
| Subseries: Centriq In                      |
| Partner: Prolicht                          |
| Division: Architectural                    |
| Installation: Surface                      |
| Product Type: Spots                        |
| Mounting Location: Ceiling                 |
| Light Distribution: Adjustable / Downlight |

PHYSICAL

|                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shape: Cylinder                                                                                                                                                                 |
| Diameter (mm): 65                                                                                                                                                               |
| Diameter (in): 2 9/16                                                                                                                                                           |
| Height (mm): 120                                                                                                                                                                |
| Height (in): 4 3/4                                                                                                                                                              |
| Ceiling Thickness (mm): 10 / 12.5 / 15 / 25                                                                                                                                     |
| Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1                                                                                                                                 |
| Min. Recessing Depth (mm): 50                                                                                                                                                   |
| Min. Recessing Depth (in): 1 15/16                                                                                                                                              |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR |
| Fixture Material: Aluminum Die Cast                                                                                                                                             |
| Cut-out Measurements: Dia. 86mm / 3 3/8"                                                                                                                                        |

ELECTRICAL

|                                             |
|---------------------------------------------|
| Input Wattage (W): 14.4                     |
| Dimming: Dali Dimming                       |
| Driver Included: Yes                        |
| Driver Location: Remote                     |
| Driver Type: Constant Current - Universal   |
| Driver Class: Class 2                       |
| Input Voltage (V): 120                      |
| Constant Current (MA): 700mA                |
| Upon Request: 0-10V dimming / Phase Dimming |

LED

|                                                 |
|-------------------------------------------------|
| Color Temperature (°K): 2700-6500 Tunable White |
| Max. Delivered Lumen (lm): Max 1251             |
| Nominal Lumen (lm): Max 1460                    |
| CRI: >90 CRI                                    |
| Efficiency (%): 99.6                            |
| Lamp Life (hrs): 50000                          |


OPTICAL

|                                          |
|------------------------------------------|
| Beam Angle: 24, 36, 52                   |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |
| Glare Rating: ≤ 16                                   |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D443-

|             |                       |                        |                      |
|-------------|-----------------------|------------------------|----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Ceiling<br>Thickness |
|-------------|-----------------------|------------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                            |
|--------------------------------------------|
| Series: Centriq                            |
| Subseries: Centriq In                      |
| Partner: Prolicht                          |
| Division: Architectural                    |
| Installation: Surface                      |
| Product Type: Spots                        |
| Mounting Location: Ceiling                 |
| Light Distribution: Adjustable / Downlight |

PHYSICAL

|                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shape: Cylinder                                                                                                                                                                 |
| Diameter (mm): 65                                                                                                                                                               |
| Diameter (in): 2 9/16                                                                                                                                                           |
| Height (mm): 120                                                                                                                                                                |
| Height (in): 4 3/4                                                                                                                                                              |
| Ceiling Thickness (mm): 10 / 12.5 / 15 / 25                                                                                                                                     |
| Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1                                                                                                                                 |
| Min. Recessing Depth (mm): 50                                                                                                                                                   |
| Min. Recessing Depth (in): 1 15/16                                                                                                                                              |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR |
| Fixture Material: Aluminum Die Cast                                                                                                                                             |
| Cut-out Measurements: Dia. 86mm / 3 3/8"                                                                                                                                        |

ELECTRICAL

|                                           |
|-------------------------------------------|
| Lamp Type: LED                            |
| Input Wattage (W): 8.2                    |
| Dimming: Dali Dimming                     |
| Driver Included: Yes                      |
| Driver Location: Remote                   |
| Driver Type: Constant Current - Universal |
| Driver Class: Class 2                     |
| Input Voltage (V): 120                    |
| Constant Current (MA): 200mA              |

LED

|                                                 |
|-------------------------------------------------|
| Color Temperature (°K): 2700-6500 Tunable White |
| Max. Delivered Lumen (lm): Max 564              |
| Nominal Lumen (lm): Max 664                     |
| CRI: >90 CRI                                    |
| Efficiency (%): 99.6                            |
| Lamp Life (hrs): 50000                          |


OPTICAL

|                                          |
|------------------------------------------|
| Beam Angle: 12                           |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |
| Glare Rating: ≤ 16                                   |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |



CENTRIQ IN SURFACE

A3D444-

|             |                      |                       |                        |                       |
|-------------|----------------------|-----------------------|------------------------|-----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|----------------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 68mm / 2 11/16"

ELECTRICAL

Input Wattage (W): 27.3

Dimming: Dali Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 700mA

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 2768

Nominal Lumen (lm): Max 3170

CRI: >90 CRI

Efficiency (%): 101.3

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D445- -

|             |                       |                        |
|-------------|-----------------------|------------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) |
|-------------|-----------------------|------------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 86mm / 3 3/8"

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 27

Dimming: Dali Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 700mA

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 569

Nominal Lumen (lm): Max 664

CRI: >90 CRI

Efficiency (%): 69.6

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D446-

|             |                       |                        |                       |
|-------------|-----------------------|------------------------|-----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options |
|-------------|-----------------------|------------------------|-----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 68mm / 2 11/16"

ELECTRICAL

Input Wattage (W): 27.4

Dimming: DALI Dimming / MATTER Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 700mA

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 2414

Nominal Lumen (lm): Max 2827

CRI: >90 CRI

Efficiency (%): 88.2

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D448-

|             |                      |                       |                        |                       |                      |
|-------------|----------------------|-----------------------|------------------------|-----------------------|----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options | Ceiling<br>Thickness |
|-------------|----------------------|-----------------------|------------------------|-----------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                            |
|--------------------------------------------|
| Series: Centriq                            |
| Subseries: Centriq In                      |
| Partner: Prolicht                          |
| Division: Architectural                    |
| Installation: Surface                      |
| Product Type: Spots                        |
| Mounting Location: Ceiling                 |
| Light Distribution: Adjustable / Downlight |

PHYSICAL

|                                                                                                                                                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Shape: Cylinder                                                                                                                                                                 |
| Diameter (mm): 83                                                                                                                                                               |
| Diameter (in): 3 1/4                                                                                                                                                            |
| Height (mm): 160                                                                                                                                                                |
| Height (in): 6 5/16                                                                                                                                                             |
| Ceiling Thickness (mm): 10 / 12.5 / 15 / 25                                                                                                                                     |
| Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1                                                                                                                                 |
| Min. Recessing Depth (mm): 50                                                                                                                                                   |
| Min. Recessing Depth (in): 1 15/16                                                                                                                                              |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR |
| Fixture Material: Aluminum Die Cast                                                                                                                                             |
| Cut-out Measurements: Dia. 86mm / 3 3/8"                                                                                                                                        |

ELECTRICAL

|                                             |
|---------------------------------------------|
| Input Wattage (W): 27.3                     |
| Dimming: Non-Dimming / DALI Dimming         |
| Driver Included: Yes                        |
| Driver Location: Remote                     |
| Driver Type: Constant Current - Universal   |
| Driver Class: Class 2                       |
| Input Voltage (V): 120                      |
| Constant Current (MA): 700mA                |
| Upon Request: 0-10V dimming / Phase Dimming |

LED

|                                                   |
|---------------------------------------------------|
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000 |
| Max. Delivered Lumen (lm): Max 2768               |
| Nominal Lumen (lm): Max 3170                      |
| CRI: >90 CRI                                      |
| Efficiency (%): 101.3                             |
| Lamp Life (hrs): 50000                            |


OPTICAL

|                                          |
|------------------------------------------|
| Beam Angle: 24, 36, 52                   |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |
| Glare Rating: ≤ 16                                   |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D449-

|             |                      |                       |                        |                      |
|-------------|----------------------|-----------------------|------------------------|----------------------|
| base number | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Ceiling<br>Thickness |
|-------------|----------------------|-----------------------|------------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Ceiling Thickness (mm): 10 / 12.5 / 15 / 25

Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 86mm / 3 3/8"

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 26.1

Dimming: Non-Dimming / DALI Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 600mA

Upon Request: 0-10V dimming / Phase Dimming

LED

Color Temperature (°K): 2700 / 3000 / 3500 / 4000

Max. Delivered Lumen (lm): Max 1544

Nominal Lumen (lm): Max 1907

CRI: >90 CRI

Efficiency (%): 75.6

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards


IP rating: IP20

Glare Rating: ≤ 16

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D450-

|             |                       |                        |                       |                      |
|-------------|-----------------------|------------------------|-----------------------|----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Beam Angle<br>Options | Ceiling<br>Thickness |
|-------------|-----------------------|------------------------|-----------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Ceiling Thickness (mm): 10 / 12.5 / 15 / 25

Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 86mm / 3 3/8"

ELECTRICAL

Input Wattage (W): 27.4

Dimming: DALI Dimming / MATTER Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 700mA

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 2414

Nominal Lumen (lm): Max 2827

CRI: >90 CRI

Efficiency (%): 88.2

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 24, 36, 52

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN SURFACE

A3D451-

|             |                       |                        |                      |
|-------------|-----------------------|------------------------|----------------------|
| base number | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Ceiling<br>Thickness |
|-------------|-----------------------|------------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: Centriq

Subseries: Centriq In

Partner: Prolicht

Division: Architectural

Installation: Surface

Product Type: Spots

Mounting Location: Ceiling

Light Distribution: Adjustable / Downlight

PHYSICAL

Shape: Cylinder

Diameter (mm): 83

Diameter (in): 3 1/4

Height (mm): 160

Height (in): 6 5/16

Ceiling Thickness (mm): 10 / 12.5 / 15 / 25

Ceiling Thickness (in): 3/8 or 1/2 or 9/16 or 1

Min. Recessing Depth (mm): 50

Min. Recessing Depth (in): 1 15/16

Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR

Fixture Material: Aluminum Die Cast

Cut-out Measurements: Dia. 86mm / 3 3/8"

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 8.2

Dimming: DALI Dimming / MATTER Dimming

Driver Included: Yes

Driver Location: Remote

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120

Constant Current (MA): 200mA

LED

Color Temperature (°K): 2700-6500 Tunable White

Max. Delivered Lumen (lm): Max 569

Nominal Lumen (lm): Max 664

CRI: >90 CRI

Efficiency (%): 99.6

Lamp Life (hrs): 50000

OPTICAL

Beam Angle: 12

Adjustability: Rotational 350°; Tilt 90°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

Glare Rating: ≤ 16


PROJECT

TYPE


SPECIFIER

QUANTITY

DATE



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN TRACK

A3T215-

|             |                |                      |                       |                        |                   |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Finish<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                         |
|-----------------------------------------|
| Series: Centriq                         |
| Subseries: Centriq In                   |
| Partner: Prolicht                       |
| Division: Architectural                 |
| Installation: Track                     |
| Product Type: Track System Line Voltage |
| Mounting Location: Ceiling              |
| Light Distribution: Adjustable          |

PHYSICAL

|                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Aperture Sizes - Downlights: 2"                                                                                                                                                            |
| Shape: Cylinder                                                                                                                                                                            |
| Diameter (mm): 65                                                                                                                                                                          |
| Diameter (in): 2 9/16                                                                                                                                                                      |
| Length (mm): 250                                                                                                                                                                           |
| Length (in): 9 13/16                                                                                                                                                                       |
| Height (mm): 136                                                                                                                                                                           |
| Height (in): 5 3/8                                                                                                                                                                         |
| Weight (kg): 0.6                                                                                                                                                                           |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR            |
| Holder Finish: WHI / BLK                                                                                                                                                                   |
| Accent Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG |
| Fixture Material: Aluminum                                                                                                                                                                 |

ELECTRICAL

|                                        |
|----------------------------------------|
| Lamp Type: LED (Zhaga Standard)        |
| Input Wattage (W): 20                  |
| Total Output Wattage (W): 18.1         |
| Dimming: Non-Dimmable / 0-10V Dimming  |
| Driver Included: Yes                   |
| Driver Location: Integrated            |
| Driver Type: Constant Current - 120Vac |
| Driver Class: Class 2                  |
| Input Voltage (V): 120                 |

LED

|                                                      |
|------------------------------------------------------|
| Number of LEDs: 1                                    |
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000    |
| Max. Delivered Lumen (lm): 1362 / 1467 / 1526 / 1557 |
| Nominal Lumen (lm): 1672 / 1800 / 1872 / 1910        |
| CRI: >90 CRI                                         |
| Lamp Life (hrs): 50000                               |


OPTICAL

|                                                 |
|-------------------------------------------------|
| Beam Angle: 12                                  |
| Adjustability: Rotational 360°; Tilt 90° (±45°) |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN TRACK

A3T216-

|             |                |                      |                       |                        |                   |                      |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|----------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Finish<br>Options | Reflector<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                         |
|-----------------------------------------|
| Series: Centriq                         |
| Subseries: Centriq In                   |
| Partner: Prolicht                       |
| Division: Architectural                 |
| Installation: Track                     |
| Product Type: Track System Line Voltage |
| Mounting Location: Ceiling              |
| Light Distribution: Adjustable          |

PHYSICAL

|                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Aperture Sizes - Downlights: 2"                                                                                                                                                            |
| Shape: Cylinder                                                                                                                                                                            |
| Diameter (mm): 65                                                                                                                                                                          |
| Diameter (in): 2 9/16                                                                                                                                                                      |
| Length (mm): 250                                                                                                                                                                           |
| Length (in): 9 13/16                                                                                                                                                                       |
| Height (mm): 136                                                                                                                                                                           |
| Height (in): 5 3/8                                                                                                                                                                         |
| Weight (kg): 0.6                                                                                                                                                                           |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR            |
| Holder Finish: WHI / BLK                                                                                                                                                                   |
| Accent Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG |
| Fixture Material: Aluminum                                                                                                                                                                 |

ELECTRICAL

|                                        |
|----------------------------------------|
| Lamp Type: LED (Zhaga Standard)        |
| Input Wattage (W): 23                  |
| Total Output Wattage (W): 20.9         |
| Dimming: Non-Dimmable / 0-10V Dimming  |
| Driver Included: Yes                   |
| Driver Location: Integrated            |
| Driver Type: Constant Current - 120Vac |
| Driver Class: Class 2                  |
| Input Voltage (V): 120                 |

LED

|                                                      |
|------------------------------------------------------|
| Number of LEDs: 1                                    |
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000    |
| Max. Delivered Lumen (lm): 1975 / 2056 / 2145 / 2245 |
| Nominal Lumen (lm): 2429 / 2529 / 2638 / 2761        |
| CRI: >90 CRI                                         |
| Lamp Life (hrs): 50000                               |


OPTICAL

|                                          |
|------------------------------------------|
| Reflector°: 24 / 36 / 52                 |
| Adjustability: Rotational 360°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN TRACK

A3T217-

|             |                |                      |                       |                        |                   |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Finish<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                         |
|-----------------------------------------|
| Series: Centriq                         |
| Subseries: Centriq In                   |
| Partner: Prolicht                       |
| Division: Architectural                 |
| Installation: Track                     |
| Product Type: Track System Line Voltage |
| Mounting Location: Ceiling              |
| Light Distribution: Adjustable          |

PHYSICAL

|                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Aperture Sizes - Downlights: 2"                                                                                                                                                            |
| Shape: Cylinder                                                                                                                                                                            |
| Diameter (mm): 83                                                                                                                                                                          |
| Diameter (in): 3 1/4                                                                                                                                                                       |
| Length (mm): 250                                                                                                                                                                           |
| Length (in): 9 13/16                                                                                                                                                                       |
| Height (mm): 166                                                                                                                                                                           |
| Height (in): 6 9/16                                                                                                                                                                        |
| Weight (kg): 0.6                                                                                                                                                                           |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR            |
| Holder Finish: WHI / BLK                                                                                                                                                                   |
| Accent Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG |
| Fixture Material: Aluminum                                                                                                                                                                 |

ELECTRICAL

|                                        |
|----------------------------------------|
| Lamp Type: LED (Zhaga Standard)        |
| Input Wattage (W): 26                  |
| Total Output Wattage (W): 23.7         |
| Dimming: Non-Dimmable / 0-10V Dimming  |
| Driver Included: Yes                   |
| Driver Location: Integrated            |
| Driver Type: Constant Current - 120Vac |
| Driver Class: Class 2                  |
| Input Voltage (V): 120                 |

LED

|                                                      |
|------------------------------------------------------|
| Number of LEDs: 1                                    |
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000    |
| Max. Delivered Lumen (lm): 1975 / 2056 / 2145 / 2245 |
| Nominal Lumen (lm): 2429 / 2529 / 2638 / 2761        |
| CRI: >90 CRI                                         |
| Lamp Life (hrs): 50000                               |


OPTICAL

|                                                 |
|-------------------------------------------------|
| Optic°: 12                                      |
| Adjustability: Rotational 360°; Tilt 90° (±45°) |


RATINGS AND CERTIFICATIONS

|                                                      |
|------------------------------------------------------|
| Certified By: Certified for North American Standards |
| IP rating: IP20                                      |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |



CENTRIQ IN TRACK

A3T218-

|             |                |                      |                       |                        |                   |                      |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|----------------------|
| base number | LED<br>Dimming | Color<br>Temperature | Finishes<br>(Diamond) | Finishes<br>(Triangle) | Finish<br>Options | Reflector<br>Options |
|-------------|----------------|----------------------|-----------------------|------------------------|-------------------|----------------------|

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

|                                         |
|-----------------------------------------|
| Series: Centriq                         |
| Subseries: Centriq In                   |
| Partner: Prolicht                       |
| Division: Architectural                 |
| Installation: Track                     |
| Product Type: Track System Line Voltage |
| Mounting Location: Ceiling              |
| Light Distribution: Adjustable          |

PHYSICAL

|                                                                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Aperture Sizes - Downlights: 2"                                                                                                                                                            |
| Shape: Cylinder                                                                                                                                                                            |
| Diameter (mm): 83                                                                                                                                                                          |
| Diameter (in): 3 1/4                                                                                                                                                                       |
| Length (mm): 250                                                                                                                                                                           |
| Length (in): 9 13/16                                                                                                                                                                       |
| Height (mm): 166                                                                                                                                                                           |
| Height (in): 6 9/16                                                                                                                                                                        |
| Weight (kg): 0.87                                                                                                                                                                          |
| Fixture Finish: SSR / BKV / CWI / CRY / HAB / UFT / ITA / RUA / FTG / MYG / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / CHC / COM / ABZ / JAG / OBR / MOS / ROR            |
| Holder Finish: WHI / BLK                                                                                                                                                                   |
| Accent Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG |
| Fixture Material: Aluminum                                                                                                                                                                 |

ELECTRICAL

|                                        |
|----------------------------------------|
| Lamp Type: LED (Zhaga Standard)        |
| Input Wattage (W): 36.2                |
| Total Output Wattage (W): 32.7         |
| Dimming: Non-Dimmable / 0-10V Dimming  |
| Driver Included: Yes                   |
| Driver Location: Integrated            |
| Driver Type: Constant Current - 120Vac |
| Driver Class: Class 2                  |
| Input Voltage (V): 120                 |

LED

|                                                      |
|------------------------------------------------------|
| Number of LEDs: 1                                    |
| Color Temperature (°K): 2700 / 3000 / 3500 / 4000    |
| Max. Delivered Lumen (lm): 2916 / 3037 / 3166 / 3320 |
| Nominal Lumen (lm): 3471 / 3615 / 3769 / 3952        |
| CRI: >90 CRI                                         |
| Lamp Life (hrs): 50000                               |


OPTICAL

|                                          |
|------------------------------------------|
| Reflector°: 20 / 32 / 54                 |
| Adjustability: Rotational 350°; Tilt 90° |


RATINGS AND CERTIFICATIONS

|                                                     |
|-----------------------------------------------------|
| Certified By: CSA Certified to UL and CSA Standards |
| IP rating: IP20                                     |

|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |










|           |
|-----------|
| PROJECT   |
| TYPE      |
| SPECIFIER |
| QUANTITY  |
| DATE      |




|           |  |
|-----------|--|
| PROJECT   |  |
| TYPE      |  |
| SPECIFIER |  |
| QUANTITY  |  |
| DATE      |  |

Fixture Finish

|                                                                                                                 |                                                                                                                    |                                                                                                                    |                                                                                                                       |                                                                                                                    |                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Sparkling Silver - 01 (SSR)<br> | Black Velvet - 02 (BKV)<br>       | Crystal White - 03 (CWI)<br>      | Creamy - 04 (CRY)<br>               | Hampton Bay - 05 (HAB)<br>      | Urban Forest - 07 (UFT)<br>  |
| In the Army - 08 (ITA)<br>      | Rusty Angel - 09 (RUA)<br>        | Fade to Gray - 12 (FTG)<br>       | Mysterious Gray - 13 (MYG)<br>      | Lost Dream - 15 (LOD)<br>       | Purple Sky - 16 (PUS)<br>    |
| Fresh Oh - 17 (FRO)<br>        | Funky P. - 18 (FUP)<br>          | Kissing Aphrodite - 19 (KIA)<br> | Poseidon's Paradise - 20 (POP)<br> | Blue Sky - 21 (BLS)<br>        | Spring Green - 22 (SPG)<br> |
| Mellow Yellow - 23 (MEY)<br>  | Golden Heart - 24 (GOH)<br>     | Champagne Cream - 26 (CHC)<br>  | Copper Mine - 27 (COM)<br>        | Ancient Bronze - 28 (ABZ)<br> | Jazz Gold - 29 (JAG)<br>   |
| Olive Breeze - 30 (OBR)<br>   | Moonlight Silver - 31 (MOS)<br> | Rosewood Red - 32 (ROR)<br>     |                                                                                                                       |                                                                                                                    |                                                                                                                 |

Holder Finish

|                                                                                                         |                                                                                                           |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| White - WHI (WHI)<br> | Black - BLK (BLK)<br> |
|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|



PROJECT

TYPE

SPECIFIER

QUANTITY

DATE

Accent Finish

Sparkling Silver - 01 (SSR)

Black Velvet - 02 (BKV)

Crystal White - 03 (CWI)

Creamy - 04 (CRY)

Hampton Bay - 05 (HAB)

Lagoon - 06 (LAG)

Urban Forest - 07 (UFT)

In the Army - 08 (ITA)

Rusty Angel - 09 (RUA)

Rusty Rush - 10 (RUR)

Milk and Chocolate - 11 (MIC)

Fade to Gray - 12 (FTG)

Mysterious Gray - 13 (MYG)

Twilight - 14 (TWT)

Lost Dream - 15 (LOD)

Purple Sky - 16 (PUS)

Fresh Oh - 17 (FRO)

Funky P. - 18 (FUP)

Kissing Aphrodite - 19 (KIA)

Poseidon's Paradise - 20 (POP)

Blue Sky - 21 (BLS)

Spring Green - 22 (SPG)

Mellow Yellow - 23 (MEY)

Golden Heart - 24 (GOH)

Gun Metal - 25 (GUM)

Champagne Cream - 26 (CHC)

Copper Mine - 27 (COM)

Ancient Bronze - 28 (ABZ)

Jazz Gold - 29 (JAG)

**Digital:** Not all screens are calibrated the same, and therefore, colors will appear differently between screens.  
**Physical:** When texture is involved, there will be variations in color, character and tone within a product series and between product families.  
**Champagne Cream, Copper Mine, Ancient Bronze + Jazz Gold:** These finishes have slight fading from specific powder coating production. Each luminaire will slightly vary.



### LEGEND

|  |                                                           |  |                                                              |  |                                                                                                |
|--|-----------------------------------------------------------|--|--------------------------------------------------------------|--|------------------------------------------------------------------------------------------------|
|  | floor-mounted                                             |  | pivotal                                                      |  | special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+                    |
|  | wall and ceiling: recessed and surface mounted            |  | rotating                                                     |  | warm dim / natural dimming LED                                                                 |
|  | ceiling-mounted and wall-mounted                          |  | illuminate tilted                                            |  | rechargeable battery powered                                                                   |
|  | wall-mounted                                              |  | color of suspension cable                                    |  | fixture with natural vivid LED (upon request)                                                  |
|  | omni-directional light distribution                       |  | length of suspension cable                                   |  | color rendering index                                                                          |
|  | direct light distribution                                 |  | reflector degree selection                                   |  | color temperature                                                                              |
|  | direct/indirect light distribution                        |  | super spot                                                   |  | lumen (luminous flux)                                                                          |
|  | indirect light distribution                               |  | lens                                                         |  | efficacy (lumens per watt)                                                                     |
|  | asymmetric light distribution                             |  | lens pack                                                    |  | Unified Glare Rating (UGR) range from 5-40                                                     |
|  | aura light distribution                                   |  | shine ring                                                   |  | marine grade (AISI 316 stainless steel)                                                        |
|  | round wall or ceiling cut-out                             |  | integrated shine ring with diffuser                          |  | walk on                                                                                        |
|  | square wall or ceiling cut-out                            |  | free individual colors 01-29                                 |  | drive on                                                                                       |
|  | the supplied jig specifies the cutout dimensions          |  | individual colors: 00 (free of charge), 01-25 (extra charge) |  | Dark Sky Compliance                                                                            |
|  | minimum distance (meters) lamp - object                   |  | luminaire part to be colored (F1)                            |  | Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor) |
|  | recessed depth                                            |  | luminaire part to be colored (F2)                            |  | lamp protected against explosion                                                               |
|  | ceiling thickness in mm                                   |  | luminaire part to be colored (F3)                            |  | blown glass using traditional methods by master glass blower                                   |
|  | ceiling thickness selection                               |  | luminaire part to be colored (F4)                            |  | acoustic material                                                                              |
|  | dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim) |  | luminaire part to be colored (F5)                            |  | protection class I, protection insulation                                                      |
|  | included or excluded LED driver/transformer/control gear  |  | color of 3-circuit adaptor                                   |  | protection class II, protection insulation                                                     |
|  | separately switchable                                     |  | indirect diffuser                                            |  | ETL Certified to UL and CSA Standards                                                          |
|  | sensor                                                    |  | direct diffuser                                              |  | UL Certified to UL and CSA Standards                                                           |
|  | remote control                                            |  | ball-proof (upon request)                                    |  | CSA Certified to UL and CSA Standards                                                          |
|  | available upon request                                    |  | accessory                                                    |  | Certified for North American Standards                                                         |

### IP RATING

|  |                                                                                                                                                  |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------|
|  | protected against ingress of solid bodies greater than 12.5mm (finger)                                                                           |
|  | protected against ingress of solid bodies greater than 2.5mm<br>protected against sprays of water up to 60 degrees from the vertical (rain)      |
|  | protected against ingress of solid bodies greater than 1mm (wire)<br>no protection against the ingress of moisture                               |
|  | protected against ingress of solid bodies greater than 1mm (wire)<br>protected against sprays of water up to 60 degrees from the vertical (rain) |
|  | protected against ingress of solid bodies greater than 1mm (wire)<br>protected against water splashed from all directions                        |
|  | protected against limited ingress of dust (wet rooms/covered outdoor areas)<br>protected against water splashed from all directions              |
|  | protected against ingress of dust<br>protected against jets of water                                                                             |
|  | protected against ingress of dust<br>protected against powerful jets of water or heavy seas                                                      |
|  | protected against ingress of dust<br>protected against immersion of water between 15cm - 1m for 30 minutes                                       |
|  | protected against ingress of dust<br>protected against immersion of water under pressure for long periods                                        |

### IK RATING

|  |                                                                                                       |
|--|-------------------------------------------------------------------------------------------------------|
|  | protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)  |
|  | protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)   |
|  | protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface) |
|  | protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)  |
|  | protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)  |
|  | protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)    |
|  | protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)     |
|  | protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)     |
|  | protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)    |
|  | protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)    |