

LINEARI 65 RECESSED

E12I0000-

base number Color Lens
Temperature Options

- 1. To build a product code in our configurator select the specify button on the base model # product page
- 2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: LinearI 65
Partner: Zaneen
Division: Exterior
Installation: Recessed
Product Type: Wall Grazer
Mounting Location: In-Ground
Light Distribution: Uplight

PHYSICAL

Shape: Rectangle
Length (mm): 305
Length (in): 12
Width (mm): 65
Width (in): 2 9/16
Height (mm): 102
Height (in): 4
Weight (kg): 2
Weight (lbs): 4.4
Load Resistance (kg): 2500
Load Resistance (lbs): 5511
Diffuser: Extra clear tempered 6mm
Fixture Finish: BLK
Fixture Material: Extruded Aluminum
Cable Details: IP67 30cm Cable with Easy Lock system

ELECTRICAL

Lamp Type: LED
Input Wattage (W): 20.89
Total Output Wattage (W): 18.48
Dimming: 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED

Color Temperature (°K): 2700 / 3000 / 4000
Nominal Lumen (lm): 1960
CRI: >82 CRI
Lamp Life (hrs): 100000


OPTICAL

Optic°: 10 / 28 / 40 / 12x32
Adjustability: Tilt ±20°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP67
IK Rating: IK09

PROJECT
TYPE
SPECIFIER
QUANTITY
DATE



LINEARI 65 RECESSED

E12I0001- -

base number

Color

Lens

Temperature

Options

1. To build a product code in our configurator select the specify button on the base model # product page
2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: LinearI 65

Partner: Zaneen

Division: Exterior

Installation: Recessed

Product Type: Wall Grazer

Mounting Location: In-Ground

Light Distribution: Uplight

PHYSICAL

Shape: Rectangle

Length (mm): 592

Length (in): 23 5⁄16

Width (mm): 65

Width (in): 2 5⁄16

Height (mm): 102

Height (in): 4

Weight (kg): 4

Weight (lbs): 8.8

Load Resistance (kg): 2500

Load Resistance (lbs): 5511

Diffuser: Extra clear tempered 6mm

Fixture Finish: BLK

Fixture Material: Extruded Aluminum

Cable Details: IP67 30cm Cable with Easy Lock system

ELECTRICAL

Lamp Type: LED

Input Wattage (W): 40.6

Total Output Wattage (W): 36.8

Dimming: 0-10V Dimming

Driver Included: Yes

Driver Location: Integrated

Driver Type: Constant Current - Universal

Driver Class: Class 2

Input Voltage (V): 120 - 277

Constant Current (MA): 500

LED

Color Temperature (°K): 2700 / 3000 / 4000

Nominal Lumen (lm): 3920

CRI: >82 CRI

Lamp Life (hrs): 100000

OPTICAL

Optic°: 10 / 28 / 40 / 12x32

Adjustability: Tilt ±20°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP67

IK Rating: IK09


PROJECT

TYPE

SPECIFIER

QUANTITY

DATE



LINEARI 65 RECESSED

E12I0002-

base number Color Lens
Temperature Options

- 1. To build a product code in our configurator select the specify button on the base model # product page
- 2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: LinearI 65
Partner: Zaneen
Division: Exterior
Installation: Recessed
Product Type: Wall Grazer
Mounting Location: In-Ground
Light Distribution: Uplight

PHYSICAL

Shape: Rectangle
Length (mm): 879
Length (in): 34 7/8
Width (mm): 65
Width (in): 2 9/16
Height (mm): 102
Height (in): 4
Weight (kg): 6
Weight (lbs): 13.2
Load Resistance (kg): 2500
Load Resistance (lbs): 5511
Diffuser: Extra clear tempered 6mm
Fixture Finish: BLK
Fixture Material: Extruded Aluminum
Cable Details: IP67 30cm Cable with Easy Lock system

ELECTRICAL

Lamp Type: LED
Input Wattage (W): 63
Total Output Wattage (W): 55.3
Dimming: 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED

Color Temperature (°K): 2700 / 3000 / 4000
Nominal Lumen (lm): 5883
CRI: >82 CRI
Lamp Life (hrs): 100000


OPTICAL

Optic°: 10 / 28 / 40 / 12x32
Adjustability: Tilt ±20°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP67
IK Rating: IK09

PROJECT
TYPE
SPECIFIER
QUANTITY
DATE



LINEARI 65 RECESSED

E12I0003-

base number Color Lens
Temperature Options

- 1. To build a product code in our configurator select the specify button on the base model # product page
- 2. To build a manual product code on this datasheet choose from the options listed below in blue font and add the suffix to the base model #

GENERAL

Series: LinearI 65
Partner: Zaneen
Division: Exterior
Installation: Recessed
Product Type: Wall Grazer
Mounting Location: In-Ground
Light Distribution: Uplight

PHYSICAL

Shape: Rectangle
Length (mm): 1166
Length (in): 45 7/8
Width (mm): 65
Width (in): 2 9/16
Height (mm): 102
Height (in): 4
Weight (kg): 8
Weight (lbs): 17.64
Load Resistance (kg): 2500
Load Resistance (lbs): 5511
Diffuser: Extra clear tempered 6mm
Fixture Finish: BLK
Fixture Material: Extruded Aluminum
Cable Details: IP67 30cm Cable with Easy Lock system

ELECTRICAL

Lamp Type: LED
Input Wattage (W): 84
Total Output Wattage (W): 73.7
Dimming: 0-10V Dimming
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Constant Current (MA): 500

LED

Color Temperature (°K): 2700 / 3000 / 4000
Nominal Lumen (lm): 7840
CRI: >82 CRI
Lamp Life (hrs): 100000


OPTICAL

Optic°: 10 / 28 / 40 / 12x32
Adjustability: Tilt ±20°

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP67
IK Rating: IK09

PROJECT
TYPE
SPECIFIER
QUANTITY
DATE



LINEARI 65
COLOR FINISH CHART

PROJECT
TYPE
SPECIFIER
QUANTITY
DATE

Fixture Finish

Black - BLK



Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens.
Physical: When texture is involved, there will be variations in color, character and tone within a product series and between product families.



LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)