

PROJECT
TYPE
NOTES
QUANTITY
DATE

GENERAL

Series: Dau

Brand: Milan

Division: Design

Mounting Type: Surface

Mounting Location: Ceiling

Subcategory: Pendant

PHYSICAL

Shape: Abstract

Length (mm): 520

Length (in): 20 1/2

Width (mm): 110

Width (in): 4 3/16

Height (mm): 254

Height (in): 10

Weight (kg): 1.4

Weight (lbs): 3

Fixture Material: Aluminum

ELECTRICAL

Number of Lamps: 3

Lamp Type: LED Retrofit

Lamp Shape: MR16

Bulb Included: Bulb Not Included

Total Output Wattage (W): 15

Max. Wattage Per Lamp (W): 5

Lamp Base: GU10

Input Voltage (V): 120

LED


Delivered Lumen Range: 500 - 999 lm

OPTICAL

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

GENERAL

Series: Dau

Brand: Milan

Division: Design

Mounting Type: Surface

Mounting Location: Ceiling

Subcategory: Pendant

PHYSICAL

Shape: Abstract

Length (mm): 750

Length (in): 29 1/2

Width (mm): 110

Width (in): 4 3/16

Height (mm): 254

Height (in): 10

Weight (kg): 2.04

Weight (lbs): 4.5

Fixture Material: Aluminum

ELECTRICAL

Number of Lamps: 4

Lamp Type: LED Retrofit

Lamp Shape: MR16

Bulb Included: Bulb Not Included

Total Output Wattage (W): 20

Max. Wattage Per Lamp (W): 5

Lamp Base: GU10

Input Voltage (V): 120

LED


Delivered Lumen Range: 1000 - 1999 lm

OPTICAL

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

GENERAL

Series: Dau

Brand: Milan

Division: Design

Mounting Type: Surface

Mounting Location: Ceiling

Subcategory: Pendant

PHYSICAL

Shape: Square

Length (mm): 300

Length (in): 11 ¾

Width (mm): 300

Width (in): 11 ¾

Height (mm): 254

Height (in): 10

Weight (kg): 3.27

Weight (lbs): 7.2

Fixture Material: Aluminum

ELECTRICAL

Number of Lamps: 4

Lamp Type: LED Retrofit

Lamp Shape: MR16

Bulb Included: Bulb Not Included

Total Output Wattage (W): 20

Max. Wattage Per Lamp (W): 5

Lamp Base: GU10

Input Voltage (V): 120

LED


Delivered Lumen Range: 1000 - 1999 lm

OPTICAL

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards

IP rating: IP20



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

GENERAL

Series: Dau

Brand: Milan

Division: Design

Mounting Type: Surface

Mounting Location: Ceiling

Subcategory: Spots

PHYSICAL

Shape: Square

Length (mm): 110

Length (in): 4 5/16

Width (mm): 110

Width (in): 4 5/16

Height (mm): 254

Height (in): 10

Weight (kg): 0.9

Weight (lbs): 2

Fixture Material: Metal

ELECTRICAL

Number of Lamps: 1

Lamp Type: LED Retrofit / Halogen

Lamp Shape: MR16

Bulb Included: Bulb Not Included

Total Output Wattage (W): 5

Max. Wattage Per Lamp (W): 5

Lamp Base: GU10

Input Voltage (V): 120

LED


Delivered Lumen Range: 100 - 499 lm

OPTICAL

RATINGS AND CERTIFICATIONS

Certified By: CSA Certified to UL and CSA Standards

IP rating: IP20



DAU SINGLE SURFACE

D92128

GENERAL
Series: Dau
Subseries: Dau Single
Brand: Milan
Division: Design
Mounting Type: Surface
Mounting Location: Ceiling
Subcategory: Downlight

PHYSICAL
Shape: Cube
Length (mm): 80
Length (in): 3 1/8"
Width (mm): 80
Width (in): 3 1/8"
Height (mm): 90
Height (in): 3 9/16"
Light Distribution: Direct
Weight (kg): 0.6
Weight (lbs): 1.2999
Fixture Material: Extruded Aluminum

ELECTRICAL
Input Wattage Range: 10 - 19 W
Lamp Type: LED
Input Wattage (W): 10
Total Output Wattage (W): 9.3
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)
Driver Included: Yes
Driver Location: Integrated
Driver Type: Constant Current - 120Vac
Driver Class: Class 2
Input Voltage (V): 120
Constant Current (mA): 350
Upon Request: (Not included: see components) Remote: 0-10Vdc dimming / Phase dimming @120Vac / 277Vac / Lutron Pro

LED
Delivered Lumen Range: 500 - 999 lm
Number of LEDs: 1
Color Temperature (°K): 2700
Max. Delivered Lumen (lm): 829.93
CRI: >80 CRI
Lamp Life (hrs): 50000


OPTICAL
Reflector°: 50

RATINGS AND CERTIFICATIONS
Certified By: CSA Certified to UL and CSA Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE




108mm 4 1/4"



108mm 4 1/4"

J-Box cover plate
Included

80mm 3 1/8"



80mm 3 1/8"



88mm 3 7/16"




90mm 3 9/16"

D93146

GENERAL	
Series: Dau	
Brand: Milan	
Division: Design	
Mounting Type: Surface	
Mounting Location: Wall	
PHYSICAL	
Shape: Cube	
Length (mm): 110	
Length (in): 4 5⁄16	
Height (mm): 110	
Height (in): 4 5⁄16	
Extension (mm): 101	
Extension (in): 4.0	
Weight (kg): 0.91	
Weight (lbs): 2	
Fixture Finish: SST	
Fixture Material: Metal	
ELECTRICAL	
Number of Lamps: 1	
Lamp Type: LED	
Max. Wattage Per Lamp (W): 4	
Dimming: Electronic Low Voltage Dimming	
Input Voltage (V): 120	
LED	
Number of LEDs: 1	
Color Temperature (°K): 2700 / 2900	
Nominal Lumen (lm): 300	
CRI: >80 CRI	
OPTICAL	
RATINGS AND CERTIFICATIONS	
Certified By: CSA Certified to UL and CSA Standards	
IP rating: IP20	


PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



D93148


GENERAL	
Series: Dau	
Brand: Milan	
Division: Design	
Mounting Type: Surface	
Mounting Location: Wall	
Subcategory: Up/Down Light	
PHYSICAL	
Shape: Cube	
Length (mm): 110	
Length (in): 4 5⁄16	
Height (mm): 110	
Height (in): 4 5⁄16	
Extension (mm): 101	
Extension (in): 4.0	
Weight (kg): 0.91	
Weight (lbs): 2	
Fixture Finish: SST	
Fixture Material: Metal	
ELECTRICAL	
Number of Lamps: 2	
Lamp Type: LED	
Total Output Wattage (W): 8	
Max. Wattage Per Lamp (W): 4	
Dimming: Electronic Low Voltage Dimming	
Driver Type: operates without a driver	
Input Voltage (V): 120	
LED	
Delivered Lumen Range: 100 - 499 lm	
Number of LEDs: 2	
Color Temperature (°K): 2700 / 2900	
Max. Delivered Lumen (lm): 339.01	
Nominal Lumen (lm): 600	
CRI: >80 CRI	
OPTICAL	
RATINGS AND CERTIFICATIONS	
Certified By: CSA Certified to UL and CSA Standards	
IP rating: IP44	

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	




GENERAL	
Series: Dau	
Brand: Milan	
Division: Design	
Mounting Type: Surface	
Mounting Location: Wall	
Subcategory: Up/Down Light	
PHYSICAL	
Length (mm): 110	
Length (in): 4 ⁵ / ₁₆	
Height (mm): 170	
Height (in): 6 ¹¹ / ₁₆	
Extension (mm): 101	
Extension (in): 4.0	
Weight (kg): 0.9	
Weight (lbs): 2	
ELECTRICAL	
Lamp Type: LED	
Total Output Wattage (W): 8	
Max. Wattage Per Lamp (W): 4	
Dimming: Electronic Low Voltage Dimming	
Input Voltage (V): 120	
LED	
Number of LEDs: 2	
Color Temperature (°K): 2700 / 2900	
Nominal Lumen (lm): 600	
CRI: >80 CRI	
Lamp Life (hrs): 50000	
OPTICAL	
RATINGS AND CERTIFICATIONS	
Certified By: CSA Certified to UL and CSA Standards	
IP rating: IP44	

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	




108mm 4 1/4"




108mm 4 1/4"

J-Box cover plate
Included


80mm 3 1/8"



101mm 4"



170mm 6 11/16"



D93189

GENERAL
Series: Dau
Brand: Milan
Division: Design
Mounting Type: Surface
Mounting Location: Wall
Subcategory: Up/Down Light

PHYSICAL
Shape: Cube
Length (mm): 80
Length (in): 3 1/8
Height (mm): 101
Height (in): 4
Extension (mm): 114
Extension (in): 4 5/16
Light Distribution: Direct
Weight (kg): 4.5
Weight (lbs): 10


ELECTRICAL
Lamp Type: LED
Max. Wattage Per Lamp (W): 10
Dimming: Non-Dimmable
Driver Included: Yes
Driver Type: Constant Current
Driver Class: Class 2
Input Voltage (V): 120

LED
Delivered Lumen Range: 500 - 999 lm
Number of LEDs: 1
Color Temperature (°K): 2700
Max. Delivered Lumen (lm): 829.93
Nominal Lumen (lm): 1010
CRI: >80 CRI

OPTICAL
Reflector°: 50° (avaible in 24° and 32° upon request)

RATINGS AND CERTIFICATIONS
Certified By: CSA Certified to UL and CSA Standards
IP rating: IP44

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	




108mm 4 1/4"




108mm 4 1/4"

J-Box cover plate
Included


80mm 3 1/8"



101mm 4"






110mm 4 5/16"



D

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

GENERAL	
Series: Dau	
Brand: Milan	
Division: Design	
Mounting Type: Surface	
Mounting Location: Wall	
Subcategory: Up/Down Light	
PHYSICAL	
Shape: Rectangle	
Length (mm): 80	
Length (in): 3 1/8	
Height (mm): 200	
Height (in): 7 7/8	
Extension (mm): 101	
Extension (in): 4	
Light Distribution: Direct / Indirect	
Weight (kg): 4.5	
Weight (lbs): 10	
Fixture Finish: WHI	
Fixture Material: Metal	
ELECTRICAL	
Lamp Type: LED	
Total Output Wattage (W): 20W	
Max. Wattage Per Lamp (W): 10W	
Dimming: Electronic Low Voltage Dimming	
Driver Type: 120V DIRECT LINE (operates without a driver)	
Input Voltage (V): 120	
LED	
Number of LEDs: 2	
Color Temperature (°K): 2700	
Nominal Lumen (lm): 2 x 1010	
CRI: >80 CRI	
OPTICAL	
Reflector°: 50	
RATINGS AND CERTIFICATIONS	
Certified By: CSA Certified to UL and CSA Standards	
IP rating: IP44	



J-Box cover plate
Included



LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)