


D86242

GENERAL	
Series:	Invisibili
Brand:	Panzeri
Division:	Design
Mounting Type:	Trimless
Mounting Location:	Ceiling
PHYSICAL	
Shape:	Square
Length (mm):	130
Length (in):	5 1/8"
Width (mm):	130
Width (in):	5 1/8"
Height (mm):	50
Height (in):	2.0
Min. Recessing Depth (mm):	120
Min. Recessing Depth (in):	4 3/4"
Light Distribution:	Downlight
Fixture Finish:	WHI
Fixture Material:	Plaster
ELECTRICAL	
Lamp Type:	LED
Max. Wattage Per Lamp (W):	6.8
Driver Included:	No
Driver Location:	Remote
Driver Type:	Remote LED driver 120Vac/350mA (Not Included - See components)
Constant Current (MA):	350
LED	
Number of LEDs:	1
Color Temperature (°K):	3000
Nominal Lumen (lm):	600
Lamp Life (hrs):	50000
OPTICAL	
Optic°:	43
RATINGS AND CERTIFICATIONS	
Certified By:	Certified for North American Standards
IP rating:	IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



D86264- : D86264-WHI

**GENERAL**  
Series: Invisibili  
Brand: Panzeri  
Division: Design  
Mounting Type: Trimless  
Mounting Location: Ceiling

**PHYSICAL**  
Length (mm): 350  
Length (in): 13 3/4  
Width (mm): 200  
Width (in): 7 7/8  
Height (mm): 120  
Height (in): 4 3/4  
Light Distribution: Downlight  
Fixture Material: Plaster


**ELECTRICAL**  
Number of Lamps: 2  
Lamp Type: LED  
Lamp Shape: AR111  
Bulb Included: Bulb Included  
Total Output Wattage (W): 24  
Max. Wattage Per Lamp (W): 2 x 12  
Lamp Base: G53  
Driver Included: Yes  
Driver Type: 2 x External 350mA non-dimming LED drivers included  
Input Voltage (V): 120

**LED**  
Number of LEDs: 2  
Color Temperature (°K): 3000  
Max. Delivered Lumen (lm): 840  
CRI: >80 CRI

**OPTICAL**  
Optic°: 25°

**RATINGS AND CERTIFICATIONS**  
Certified By: CSA Certified to UL and CSA Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



## LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimnable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

## IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

## IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)