

D92164

**GENERAL**  
Series: Robotic  
Brand: Milan  
Division: Design  
Mounting Type: Surface  
Mounting Location: Ceiling  
Subcategory: Spots


**PHYSICAL**  
Shape: Cylinder  
Length (mm): 90  
Length (in): 3 9/16  
Width (mm): 50  
Width (in): 1 15/16  
Height (mm): 90  
Height (in): 3 9/16  
Light Distribution: Adjustable / Direct  
Weight (kg): 1.8  
Weight (lbs): 4  
Fixture Finish: WHI  
Fixture Material: Metal

**ELECTRICAL**  
Number of Lamps: 1  
Lamp Type: LED  
Total Output Wattage (W): 6.6  
Dimming: Non-Dimmable  
Driver Included: Yes  
Driver Location: Integrated  
Driver Type: Constant Current  
Driver Class: Class 2  
Input Voltage (V): 120  
Constant Current (mA): 350  
Upon Request: Dimmable option available with remote driver upon request

**LED**  
Number of LEDs: 1  
Color Temperature (°K): 2700  
Max. Delivered Lumen (lm): 431.51  
Nominal Lumen (lm): 600  
CRI: >80 CRI

**OPTICAL**  
**RATINGS AND CERTIFICATIONS**  
Certified By: CSA Certified to UL and CSA Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



D92166

**GENERAL**  
Series: Robotic  
Brand: Milan  
Division: Design  
Mounting Type: Surface  
Mounting Location: Ceiling  
Subcategory: Spots

**PHYSICAL**  
Shape: Rectangle  
Diameter (mm): 60  
Diameter (in): 2 3/8  
Length (mm): 138  
Length (in): 5 7/16  
Width (mm): 80  
Width (in): 3 1/8  
Height (mm): 144  
Height (in): 5 11/16  
Light Distribution: Adjustable / Direct  
Weight (kg): 1.8  
Weight (lbs): 4  
Fixture Finish: WHI  
Fixture Material: Metal



**ELECTRICAL**  
Number of Lamps: 2  
Lamp Type: LED  
Total Output Wattage (W): 13.2  
Max. Wattage Per Lamp (W): 6.6  
Dimming: Non-Dimmable  
Driver Included: Yes  
Driver Location: External  
Driver Type: Constant Current  
Driver Class: Class 2  
Input Voltage (V): 120  
Lamp Voltage (V): 120  
Constant Current (MA): 2 x 175  
Upon Request: Dimmable option available with remote driver upon request

**LED**  
Number of LEDs: 2  
Color Temperature (°K): 2700  
Max. Delivered Lumen (lm): 2 x 431.54  
Nominal Lumen (lm): 2 x 800  
CRI: >80 CRI

**OPTICAL**  
Adjustability: Tilting and rotating

**RATINGS AND CERTIFICATIONS**  
Certified By: CSA Certified to UL and CSA Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE





J-Box cover plate  
Included




138mm 5 7/16"

1 15/16"  
50mm




144mm 5 11/16"



D93202

GENERAL	
Series: Robotic	
Brand: Milan	
Division: Design	
Mounting Type: Surface	
Mounting Location: Wall	
Subcategory: Uplight	
PHYSICAL	
Shape: Cylinder	
Diameter (mm): 50	
Diameter (in): 1 15⁄16	
Length (mm): 138	
Length (in): 5 7⁄16	
Height (mm): 116	
Height (in): 4 9⁄16	
Extension (mm): 115	
Extension (in): 4 1⁄2	
Light Distribution: Adjustable / Direct	
Weight (kg): 1.8	
Weight (lbs): 4	
Fixture Finish: WHI	
Fixture Material: Metal	
ELECTRICAL	
Number of Lamps: 2	
Lamp Type: LED	
Total Output Wattage (W): 13.2	
Max. Wattage Per Lamp (W): 6.6	
Dimming: Non-Dimmable	
Driver Included: Yes	
Driver Location: Integrated	
Driver Type: Constant Current	
Driver Class: Class 2	
Input Voltage (V): 120	
Constant Current (MA): 500 [2 x 250 parallel wiring]	
Upon Request: Dimmable option available with remote driver upon request	
LED	
Number of LEDs: 2	
Color Temperature (°K): 3000	
Max. Delivered Lumen (lm): 2 x 800	
CRI: >80 CRI	
OPTICAL	
Optic°: 47	
RATINGS AND CERTIFICATIONS	
Certified By: CSA Certified to UL and CSA Standards	
IP rating: IP20	

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



D96022

**GENERAL**  
Series: Robotic  
Brand: Milan  
Division: Design  
Mounting Type: Recessed  
Mounting Location: Ceiling

**PHYSICAL**  
Shape: Round  
Diameter (mm): 80  
Diameter (in): 3 1/8  
Height (mm): 53  
Height (in): 2 1/16  
Light Distribution: Direct  
Weight (kg): 1.81  
Weight (lbs): 4  
Fixture Finish: WHI  
Fixture Material: Metal


**ELECTRICAL**  
Input Wattage Range: 1 - 9 W  
Lamp Type: LED  
Total Output Wattage (W): 6.6  
Dimming: Non-Dimming / Phase Dimming (120Vac only) / 0-10V Dimming  
Driver Included: No  
Driver Location: Remote  
Driver Type: Constant Current - 120 / 277Vac  
Driver Class: Class 2  
Input Voltage (V): 120 - 277  
Constant Current (mA): 350

**LED**  
Number of LEDs: 1  
Color Temperature (°K): 2700  
Max. Delivered Lumen (lm): 463  
Nominal Lumen (lm): 600  
CRI: >80 CRI  
Lamp Life (hrs): 50000


**OPTICAL**  
Reflector°: 47

**RATINGS AND CERTIFICATIONS**  
Certified By: CSA Certified to UL and CSA Standards  
IP rating: IP20


PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	




Ø80mm 3 1/8"



Ø60mm 2 3/8"



53mm  
2 1/16"



165mm 6 1/2"

38mm  
1 1/2"

D



## LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/ control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

## IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

## IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)